


P0770EIS


N-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
700V	$1.5\Omega @ V_{GS} = 10V$	7A



TO-251(S)



ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	700	V
Gate-Source Voltage		V_{GS}	± 30	V
Continuous Drain Current ²	$T_C = 25\text{ }^\circ\text{C}$	I_D	7	A
	$T_C = 100\text{ }^\circ\text{C}$		4.4	
Pulsed Drain Current ^{1,2}		I_{DM}	20	
Avalanche Current ³		I_{AS}	2.2	
Avalanche Energy ³		E_{AS}	24	mJ
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	P_D	96	W
	$T_C = 100\text{ }^\circ\text{C}$		38	
Operating Junction & Storage Temperature Range		T_j, T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		1.3	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		62.5	

¹Pulse width limited by maximum junction temperature.

²Limited only by maximum temperature allowed

³ $V_{DD} = 50V$, $L = 10\text{mH}$, starting $T_J = 25\text{ }^\circ\text{C}$

P0770EIS

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	700			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2	2.9	4	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 30V$			± 100	nA
Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 700V, V_{GS} = 0V, T_C = 25\text{ }^{\circ}C$			1	μA
		$V_{DS} = 560V, V_{GS} = 0V, T_C = 100\text{ }^{\circ}C$			10	
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 3.5A$		1.2	1.5	mΩ
Forward Transconductance ¹	g_{fs}	$V_{DS}=10V, I_D = 3.5A$		10		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 25V, f = 1MHz$		1223		pF
Output Capacitance	C_{oss}			106		
Reverse Transfer Capacitance	C_{rss}			9		
Total Gate Charge ²	Q_g	$V_{DD} = 560V, I_D = 7A, V_{GS} = 10V$		28		nC
Gate-Source Charge ²	Q_{gs}			5		
Gate-Drain Charge ²	Q_{gd}			10		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{GS} = 10V, V_{DD} = 350V, I_D = 7A, R_G= 25\Omega$		35		nS
Rise Time ²	t_r			75		
Turn-Off Delay Time ²	$t_{d(off)}$			80		
Fall Time ²	t_f			57		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T _J = 25 °C)						
Continuous Current ³	I_S				7	A
Forward Voltage ¹	V_{SD}	$I_F = 7A, V_{GS} = 0V$			1	V
Reverse Recovery Time	t_{rr}	$I_F = 7A, di_F/dt = 100A / \mu S$		400		nS
Reverse Recovery Charge	Q_{rr}			4		uC

¹Pulse test : Pulse Width $\leq 300 \mu\text{sec}$, Duty Cycle $\leq 2\%$.


²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.


P0770EIS

N-Channel Enhancement Mode MOSFET


Output Characteristics




Transfer Characteristics




Gate charge Characteristics




Capacitance Characteristic



On-Resistance VS Gate-To-Source




On-Resistance VS Drain Current




P0770EIS

N-Channel Enhancement Mode MOSFET


On-Resistance VS Temperature




Source-Drain Diode Forward Voltage




Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve




P0770EIS

N-Channel Enhancement Mode MOSFET

Package Dimension

TO-251 (IS) MECHANICAL DATA


Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	6.3	6.6	6.8	H	2.1	2.3	2.5
B	4.8	5.3	5.5	J	0.4	0.5	0.6
C	6.7		7.57	K	0.35	0.5	0.65
D	3	3.5	4.5	L	0.9		1.5
E		2.3		M	5.3		6.22
F	0.6	0.9	1.1	N	1.4	1.6	2.1
G	0.4		0.89				




P0770EIS

N-Channel Enhancement Mode MOSFET

A. Marking Information



B. Tape&Reel Information:75pcs/Tube




P0770EIS

N-Channel Enhancement Mode MOSFET

C. Lot.No. & Date Code rule


1.LOT.NO.

M N 15M21 03




2.Date Code

D Y M X XXX



3.Date Code (for Small package)

XX Y WW





P0770EIS

N-Channel Enhancement Mode MOSFET

D.Label rule

标签内容(Label content)



1	Label Size	30 * 90 mm
2	Font style	Times New Roman or Arial (或可区分英文"0"和数字"0", "G"和"Q"的字型即可)
3	Great Power	Height: 4 mm
4	Package	Height: 2 mm
5	Date	Height: 2 mm Shipping date: YYYY/MM/DD, ex. 2008/09/12
6	Device	Height: 3 mm (Max: 16 Digit)
7	Lot	Height: 3 mm (Max: 9 Digit) Sub lot
8	D/C	Height: 3 mm (Max: 7 Digit)
9	QTY	Height: 3 mm (Max: 6 Digit) Thousand mark is no needed
10	Pb Free label	 Diameter: 1 cm bottom color: Green Font color: Black Font style: Arial
11	Halogen Free label	 Diameter: 1 cm bottom color: Green Font color: Black Font style: Arial
12	Scan info	Device / Lot / D/C / QTY , Insert "/" between every parts. for example: P3055LDG/G12345601/GGG2301/2000 DPI (Dots per inch): Over 300 dpi Code : Code 128 Height: 6 mm at least