

Description:

Fastener Length: 11/16", Thread: 1/4-28, Thread Length: "

NAS6404-5D Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Bolt, Shear
NSN:	5306-01-334-1309
NIIN:	013341309
FSC:	Bolts / 5306
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS6404-5D Specifications

Distance From Head Largest Bearing Surface To Shank Hole Center:	0.487 Inches Minimum First Hole And 0.537 Inches Maximum First Hole
Fastener Length:	0.667 Inches Minimum And 0.697 Inches Maximum
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Head Style:	Dished Hexagon
Material:	Titanium Alloy Uns R56400 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.250 Inches
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Specification/standard Data:	80205-nas6404 Professional/industrial Association Standard
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Thread Quantity Per Inch:	28
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear-bolts/NAS6404-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.