



Military-Fasteners.com

NAS1635-3LE7P SCREW SPEC

Description:

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16"

NAS1635-3LE7P Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-01-334-1454
NIIN:	013341454
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1635-3LE7P Specifications

Color:	Black
Fastener Length:	0.408 Inches Minimum And 0.438 Inches Maximum
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Head Style:	Pan
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Cross Recess Type 1
Locking Feature Material:	Plastic Polyamide
Locking Feature:	Patch Or Pellet Or Strip
Screw Surface Treatment:	Oxide
Screw Material:	Steel Corrosion Resisting
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard
Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.346 Inches Minimum And 0.438 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screw/NAS1635-3LE7P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.