


**T0805BH –
T0805NH TRIACS****8.0 A 200–800 V
5/5/5/5 mA**

The T0805 series of TRIAC's are high performance glass passivated PNPN devices. These parts are intended for general purpose applications where logic compatible gate sensitivity is required.

Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Parameter	Part Nr.	Symbol	Min.	Max.	Unit	Test Conditions
Repetitive Peak Off State Voltage	T0805BH	V_{DRM}	200		V	$T_j = -40^\circ\text{C} \text{ to } 125^\circ\text{C}$ $R_{GK} = 1\text{ k}\Omega$
	T0805DH		400		V	
	T0805MH		600		V	
	T0805NH		800		V	
On-State Current		$I_T(\text{RMS})$	8		A	All Conduction Angles $T_C = 85^\circ\text{C}$
Nonrept. On-State Current		I_{TSM}	77		A	Half Cycle, 60 Hz
Nonrept. On-State Current		I_{TSM}	70		A	Half Cycle, 50 Hz
Fusing Current		I^2t	24		A^2s	$t = 10\text{ ms}$
Peak Gate Current		I_{GM}	4		A	$10\mu\text{s}$ max.
Peak Gate Dissipation		P_{GM}	10		W	$10\mu\text{s}$ max.
Gate Dissipation		$P_{G(\text{AV})}$	1		W	20 ms max.
Operating Temperature		T_j	-40	125	$^\circ\text{C}$	
Storage Temperature		T_{stg}	-40	125	$^\circ\text{C}$	
Soldering Temperature		T_{sld}		250	$^\circ\text{C}$	1.6 mm from case, 10 s max.

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Min.	Max.	Unit	Test Conditions
Off-State Leakage Current	I_{DRM}		2	mA	$V_D = V_{DRM}$ $R_{GK} = 1\text{ k}\Omega$ $T_j = 125^\circ\text{C}$
Off-State Leakage Current	I_{DRM}		5	μA	$V_D = V_{DRM}$ $R_{GK} = 1\text{ k}\Omega$ $T_j = 25^\circ\text{C}$
On-State Voltage	V_T		1.85	V	at $I_T = 12\text{ A}$, $T_j = 25^\circ\text{C}$
On-State Threshold Voltage	$V_{T(\text{TO})}$		1.0	V	$T_j = 125^\circ\text{C}$
On-State Slope Resistance	r_T		80	$\text{m}\Omega$	$T_j = 125^\circ\text{C}$
Gate Trigger Current	$I_{GT\text{I+}}$ (1)		5	mA	$V_D = 12\text{ V}$
	$I_{GT\text{I-}}$ (2)		5	mA	$V_D = 12\text{ V}$
	$I_{GT\text{III-}}$ (3)		5	mA	$V_D = 12\text{ V}$
	$I_{GT\text{III+}}$ (4)		5	mA	$V_D = 12\text{ V}$
Gate Trigger Voltage	V_{GT}		2.5	V	$V_D = 12\text{ V}$ All Quadrants
Holding Current	I_H		5	mA	$R_{GK} = 1\text{ k}\Omega$
Critical Rate of Voltage Rise	dv/dt	10		$\text{V}/\mu\text{s}$	$V_D = .67 \times V_{DRM}$ $R_{GK} = 1\text{ k}\Omega$ $T_j = 125^\circ\text{C}$
Critical Rate of Rise, Off-State	dv/dt_c	1		$\text{V}/\mu\text{s}$	$I_T = 8\text{ A}$ $di/dt = 3.55\text{ A/ms}$ $T_C = 85^\circ\text{C}$
Thermal Resistance junc. to case	R_{ojc}	3		K/W	
Thermal Resistance junc. to amb.	R_{oja}	60		K/W	