

# 2N5486

## JFET VHF/UHF Amplifiers

### N-Channel — Depletion

#### Features

- Pb-Free Packages are Available\*

#### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)


Rating	Symbol	Value	Unit
Drain–Gate Voltage	$V_{DG}$	25	Vdc
Reverse Gate–Source Voltage	$V_{GSR}$	25	Vdc
Drain Current	$I_D$	30	mAdc
Forward Gate Current	$I_{G(f)}$	10	mAdc
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	350 2.8	mW mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	–65 to +150	$^\circ\text{C}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.




**ON Semiconductor®**

<http://onsemi.com>



**TO-92 (TO-226AA)  
CASE 29-11  
STYLE 5**

#### MARKING DIAGRAM



2N5486 = Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
■ = Pb-Free Package  
(Note: Microdot may be in either location)





#### ORDERING INFORMATION

Device	Package	Shipping
2N5486	TO-92	1000 Units / Bulk
2N5486G	TO-92 (Pb-Free)	1000 Units / Bulk

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.





**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
<b>OFF CHARACTERISTICS</b>					
Gate–Source Breakdown Voltage ( $I_G = -1.0\ \mu\text{Adc}$ , $V_{DS} = 0$ )	$V_{(BR)GSS}$	-25	–	–	Vdc
Gate Reverse Current ( $V_{GS} = -20\ \text{Vdc}$ , $V_{DS} = 0$ ) ( $V_{GS} = -20\ \text{Vdc}$ , $V_{DS} = 0$ , $T_A = 100^\circ\text{C}$ )	$I_{GSS}$	–	–	-1.0 -0.2	nAdc $\mu\text{Adc}$
Gate Source Cutoff Voltage ( $V_{DS} = 15\ \text{Vdc}$ , $I_D = 10\ \text{nAdc}$ )	$V_{GS(off)}$	-2.0	–	-6.0	Vdc
<b>ON CHARACTERISTICS</b>					
Zero–Gate Voltage Drain Current ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ )	$I_{DSS}$	8.0	–	20	mAdc
<b>SMALL–SIGNAL CHARACTERISTICS</b>					
Forward Transfer Admittance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 1.0\ \text{kHz}$ )	$ y_{fs} $	4000	–	8000	$\mu\text{mhos}$
Input Admittance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 400\ \text{MHz}$ )	$\text{Re}(y_{is})$	–	–	1000	$\mu\text{mhos}$
Output Admittance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 1.0\ \text{kHz}$ )	$ y_{os} $	–	–	75	$\mu\text{mhos}$
Output Conductance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 400\ \text{MHz}$ )	$\text{Re}(y_{os})$	–	–	100	$\mu\text{mhos}$
Forward Transconductance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 400\ \text{MHz}$ )	$\text{Re}(y_{fs})$	3500	–	–	$\mu\text{mhos}$
Input Capacitance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 1.0\ \text{MHz}$ )	$C_{iss}$	–	–	5.0	pF
Reverse Transfer Capacitance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 1.0\ \text{MHz}$ )	$C_{rss}$	–	–	1.0	pF
Output Capacitance ( $V_{DS} = 15\ \text{Vdc}$ , $V_{GS} = 0$ , $f = 1.0\ \text{MHz}$ )	$C_{oss}$	–	–	2.0	pF

**COMMON SOURCE CHARACTERISTICS ADMITTANCE PARAMETERS**( $V_{DS} = 15\ \text{Vdc}$ ,  $T_{\text{channel}} = 25^\circ\text{C}$ )**Figure 1. Input Admittance ( $y_{is}$ )****Figure 2. Reverse Transfer Admittance ( $y_{rs}$ )****Figure 3. Forward Transadmittance ( $y_{fs}$ )****Figure 4. Output Admittance ( $y_{os}$ )**





## COMMON SOURCE CHARACTERISTICS

## S-PARAMETERS

(V<sub>DS</sub> = 15 Vdc, T<sub>channel</sub> = 25°C, Data Points in MHz)Figure 5.  $S_{11s}$ Figure 6.  $S_{12s}$ Figure 7.  $S_{21s}$ Figure 8.  $S_{22s}$


## COMMON GATE CHARACTERISTICS

## ADMITTANCE PARAMETERS


(V<sub>DG</sub> = 15 Vdc, T<sub>channel</sub> = 25°C)Figure 9. Input Admittance ( $y_{ig}$ )Figure 10. Reverse Transfer Admittance ( $y_{rg}$ )Figure 11. Forward Transfer Admittance ( $y_{fg}$ )Figure 12. Output Admittance ( $y_{og}$ )

**COMMON GATE CHARACTERISTICS  
S-PARAMETERS**


( $V_{DS} = 15$  Vdc,  $T_{channel} = 25^\circ\text{C}$ , Data Points in MHz)




**Figure 13.  $S_{11g}$**



**Figure 14.  $S_{12g}$**



**Figure 15.  $S_{21a}$**





**Figure 16.  $S_{22a}$**

# 2N5486

## PACKAGE DIMENSIONS

TO-92 (TO-226AA)  
CASE 29-11  
ISSUE AL




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

### STYLE 5:

1. DRAIN
2. SOURCE
3. GATE

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative