

1A Avg.

600 Volts


FRED

10DRA60

■最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	V_{RRM}	600	V
平均整流電流 Average Rectified Forward Current	I_O	50Hz、正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	
		$T_a=58^{\circ}\text{C}^{*1}$	1.0 A
		$T_a=35^{\circ}\text{C}^{*2}$	1.0 A
実効順電流 R.M.S. Forward Current	$I_F(\text{RMS})$	1.57	A
サージ順電流 Surge Forward Current	I_{FSM}	35 50Hz正弦半波, 1サイクル, 非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	T_{jw}	$-40\sim+150$	$^{\circ}\text{C}$
保存温度範囲 Storage Temperature Range	T_{stg}	$-40\sim+150$	$^{\circ}\text{C}$

■OUTLINE DRAWING(mm)



■APPROX. NET WEIGHT:0.32g

■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	I_{RM}	$T_j=25^{\circ}\text{C}, V_{RM}=V_{RRM}$	—	—	10	μA
ピーク順電圧 Peak Forward Voltage	V_{FM}	$T_j=25^{\circ}\text{C}, I_{FM}=1\text{A}$	—	—	1.13	V
逆回復時間 Reverse Recovery Time	t_{rr}	$I_{FM}=1\text{A}, -di/dt=50\text{ A}/\mu\text{s}, T_j=25^{\circ}\text{C}$	—	—	120	ns
熱抵抗 Thermal Resistance	$R_{th(j-a)}$	接合部・周囲間 Junction to Ambient	—	—	81	$^{\circ}\text{C}/\text{W}$
		プリント基板実装 ^{*1} 単体フィン無し ^{*2}	—	—	115	$^{\circ}\text{C}/\text{W}$

*1: プリント基板実装 / P.C. Board mounted (L=8mm, Print Land=10×10, Both Sides)

*2: 単体フィン無し / Without Fin or P.C. Board mounted

■定格・特性曲線

