



180 Lafayette Road
North Hampton, NH 03862-2448
PH: 603-964-3165
FX: 603-964-3168
WWW.PDEELECTRONICS.COM

Full Wave Bridge Assembly

Standard, Fast, Ultra and Ultra Super Fast Recovery, Single Phase
HVFWB Series

FEATURES

- Low Forward Voltage Drop
- Low Reverse Leakage Current
- Very Fast Recovery Time
- Small Case Size
- Epoxy Case

QUICK REFERENCE DATA

- $V_R = 5000V - 20000V$
- $T_{rr} = 35nS - 250nS$
- $I_F = 1A - 3A$

ELECTRICAL CHARACTERISTICS						MAX RATINGS			
Type	Maximum Reverse Voltage V _R	Maximum Reverse Current Per Leg I _R @ V _R	Maximum Reverse Recovery Time T _{rr} *1	Maximum Forward Voltage V _F		Average Rectified Forward Current I _F	1 Cycle Surge Current I _{FSM}	Case Length L (Inches)	Figure
	T _C =25°C	T _C =25°C	T _A =25°C	T _A =25°C		T _C =55°C	T _C =25°C		
	Volts	µA	nS	Volts	Amps	Amps	Amps		
HVFWB-Standard Recovery 1.0 and 3.0 Amp Glass Passivated Rectifier Assemblies									
2HVFWB5KB	5000	0.5	-	4.8	2.0	2.0	50	1.25	A
2HVFWB8KB	8000	0.5	-	7.2	2.0	2.0	50	1.25	A
2HVFWB5KC	5000	0.5	-	4.8	2.0	2.0	50	1.5	B
2HVFWB10KC	10000	0.5	-	8.4	2.0	2.0	50	1.5	B
2HVFWB10KD	10000	0.5	-	8.4	2.0	2.0	50	2.0	B
2HVFWB15KD	15000	0.5	-	12.0	2.0	2.0	50	2.0	B
2HVFWB15KE	15000	0.5	-	12.0	2.0	2.0	50	2.5	B
2HVFWB20KE	20000	0.5	-	18.0	2.0	2.0	50	2.5	B
5HVFWB5KC	5000	0.5	-	5.2	5.0	5.0	150	1.5	B
5HVFWB7.5KD	7500	0.5	-	6.5	5.0	5.0	150	2.0	B
5HVFWB5KE	5000	0.5	-	5.2	5.0	5.0	150	2.5	B
5HVFWB10KE	10000	0.5	-	10.4	5.0	5.0	150	2.5	B
5HVFWB15KE	15000	0.5	-	13.0	5.0	5.0	150	2.5	B
HVFWB-F-Fast Recovery 1.0 and 3.0 Amp Glass Passivated Rectifier Assemblies									
1HVFWB5KBF	5000	0.3	250	7.2	1.0	1.0	20	1.25	A
1HVFWB10KBF	10000	0.3	250	14.4	1.0	1.0	20	1.25	A
1HVFWB5KCF	5000	0.3	250	7.2	1.0	1.0	20	1.5	B
1HVFWB10KCF	10000	0.3	250	14.4	1.0	1.0	20	1.5	B
2HVFWB5KDF	5000	0.5	150	6.5	2.0	2.0	50	2.0	B
2HVFWB10KDF	10000	0.5	150	13.0	2.0	2.0	50	2.0	B
2HVFWB10KEF	10000	0.5	150	13.0	2.0	2.0	50	2.5	B
2HVFWB15KEF	15000	0.5	150	20.0	2.0	2.0	50	2.5	B
4HVFWB5KCF	5000	0.5	250	7.0	4.0	4.0	100	1.5	B
4HVFWB5KDF	5000	0.5	250	7.0	4.0	4.0	100	2.0	B
5HVFWB5KEF	5000	0.5	250	7.5	5.0	5.0	100	2.5	B
5HVFWB10KEF	10000	0.5	250	14.0	4.0	4.0	100	2.5	B

Specifications subject to change without notice to ensure a better product

PD&E Electronics 180 Lafayette Rd. North Hampton, NH 03862

Ph: (603) 964-3165 Fx: (603) 964-3168 Web: WWW.PDEELECTRONICS.COM



180 Lafayette Road
North Hampton, NH 03862-2448
PH: 603-964-3165
FX: 603-964-3168
WWW.PDEELECTRONICS.COM

Full Wave Bridge Assembly

Standard, Fast, Ultra and Ultra Super Fast Recovery, Single Phase
HVFWB Series

ELECTRICAL CHARACTERISTICS						MAX RATINGS			
Type	Maximum Reverse Voltage	Maximum Reverse Current Per Leg I _R @ V _R	Maximum Reverse Recovery Time T _{rr} *1	Maximum Forward Voltage V _F		Average Rectified Forward Current I _F	1 Cycle Surge Current I _{FSM}	Case Length L (Inches)	Figure
	T _C =25°C	T _C =25°C	T _A =25°C	T _A =25°C		T _C =55°C	T _C =25°C		
	Volts	µA	nS	Volts	Amps	Amps	Amps		
HVFWB·UF-Ultra Fast Recovery T _{rr} 75 nsec 1.0 and 3.0 Amp Rectifier Assembly									
2HVFWB5KBUF	5000	1.0	75	8.0	2.0	2.0	35	1.25	A
2HVFWB8KBUF	8000	1.0	75	13.0	2.0	2.0	35	1.25	A
2HVFWB5KCUF	5000	1.0	75	8.0	2.0	2.0	35	1.5	B
2HVFWB10KCUF	10000	1.0	75	16.0	2.0	2.0	35	1.5	B
2HVFWB10KDUF	10000	1.0	75	16.0	2.0	2.0	35	2.0	B
2HVFWB15KDUF	15000	1.0	75	24.0	2.0	2.0	35	2.0	B
2HVFWB15KEUF	15000	1.0	75	24.0	2.0	2.0	35	2.5	B
2HVFWB20KEUF	20000	1.0	75	32.0	2.0	2.0	35	2.5	B
4HVFWB5KCUF	5000	5.0	75	7.0	4.0	4.0	150	1.5	B
4HVFWB5KDUF	5000	5.0	75	7.0	4.25	4.25	150	2.0	B
4HVFWB8KDUF	8000	5.0	75	11.2	4.0	4.0	150	2.0	B
4HVFWB10KEUF	10000	5.0	75	14.0	4.25	4.25	150	2.5	B
4HVFWB15KEUF	15000	5.0	75	21.0	4.0	4.0	150	2.5	B
HVFWB·USF-Ultra Super Fast Recovery T _{rr} 35 nsec 1.0 Amp Rectifier Assemblies									
1HVFWB5KBUSF	5000	1.0	35	7.0	1.0	1.0	10	1.25	A
1HVFWB5KCUSF	5000	1.0	35	7.0	1.0	1.0	10	1.5	B
1HVFWB8KCUSF	8000	1.0	35	11.2	1.0	1.0	10	1.5	B
1HVFWB10KDUSF	10000	1.0	35	14.0	1.0	1.0	10	2.0	B
1HVFWB15KDUSF	15000	1.0	35	21.0	0.9	0.9	10	2.0	B
1HVFWB15KEUSF	15000	1.0	35	21.0	1.0	1.0	10	2.5	B
1HVFWB20KEUSF	20000	1.0	35	28.0	0.9	0.9	10	2.5	B
HVFWB·USF-Ultra Super Fast Recovery T _{rr} 40 nsec 2.0 Amp Rectifier Assemblies									
3HVFWB5KCUSF	5000	5.0	40	10.0	3.0	3.0	60	1.5	B
3HVFWB5KDUSF	5000	5.0	40	10.0	3.0	3.0	60	2.0	B
3HVFWB15KDUSF	10000	5.0	40	20.0	2.75	2.75	60	2.0	B
3HVFWB10KEUSF	10000	5.0	40	20.0	3.0	3.0	60	2.5	B
3HVFWB15KEUSF	15000	5.0	40	30.0	2.75	2.75	60	2.5	B

* Measured on discretes prior to assembly in reverse recovery circuit switching from 0.5A forward to 1.0A reverse current recovering to 0.25A reverse current.

Specifications subject to change without notice to ensure a better product

PD&E Electronics 180 Lafayette Rd. North Hampton, NH 03862

Ph: (603) 964-3165 Fx: (603) 964-3168 Web: WWW.PDEELECTRONICS.COM



Standard, Fast, Ultra and Ultra Super Fast Recovery, Single Phase HVFWB Series

Operating and Storage Temperature.....	-55°C to +150°C
Maximum Thermal Impedance (typical).....	2.0 °C/W Junction to Case

PD&E Electronics 180 Lafayette Rd. North Hampton, NH 03862
Ph: (603) 964-3165 Fx: (603) 964-3168 Web: WWW.PDEELECTRONICS.COM