

2 Elements Mini Hihg VoltageSeries

ACPA-2RM Ø5.5mm ,6mm long

Specifications

Model Name	DC Breakdown Voltage	Maximum Impulse Breakdown Voltage		Maximum Impulse Discharge Current (8/20 μs)		Normal Alternating Discharge Current		Impulse Life (8/20μs) (100A)	DC Holdover Voltage	Minimum Insulation Resistance	Maximum Capacitance
	(V)	(V)		(KA)		(A)			(V)	(G⊠)	(pf)
	100V/s	100V/μs	1000V/μs	1 time	10 times	50Hz, 1sec	Single 9cycles	times	<150ms	Note2	1MHZ
2RM-1000	1000 ±20%	1600	1800	3	1.5	2	4	300	150	1	1
2RM-1200	1200 ±20%	1800	2000						150	1	1
2RM-1400	1400 ±20%	2200	2400						150	1	1
2RM-1600	1600 ±20%	2400	2600						150	1	1
2RM-2000	2000 ±20%	2800	3000						150	1	1
2RM-2500	2500 ±20%	3300	3500						150	1	1
2RM-3000	3000 ±20%	3800	4000						150	1	1
2RM-3500	3500 ±20%	4300	4500						150	1	1
2RM-3600	3600 ±20%	4400	4600						150	1	1

Note1 : UL1449 C-UL 3rd Recognized, File E315423

Note2 : DC Breakdown Voltage	DC Measuring Voltage
1000-2000 V	500V
2500-4000V	1000V

Dimensions

Unit: mm

Item	Dimensions
D	5.5 + 0.3,-0.5
T	6.0 + 0.3,-0.5
d	0.8 ± 0.05
L	20min.

