isc Silicon PNP Power Transistor 2SA1879

DESCRIPTION

- Collector-Emitter Sustaining Voltage-
  : $V_{CEO(SUS)}$= -80(V)(Min.)
- Low Collector Saturation Voltage
  :$V_{CE(sat)}$= -0.3(V)(Max.)@I_C= -3.5A
- Large Current Capability-I_C= -7A
- Minimum Lot-to-Lot variations for robust device performance and reliable operation



PIN 1. BASE
2.COLLECTOR
3.EMITTER
TO-220F package

APPLICATIONS

- Designed for use as a driver in DC/DC converters and actuators.

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	-80	V
V_{CEO}	Collector-Emitter Voltage	-80	V
V_{EBO}	Emitter-Base Voltage	-7	V
I_C	Collector Current-Continuous	-7	A
I_{CM}	Collector Current-Peak	-14	A
I_B	Base Current-Continuous	-1.5	A
I_{BM}	Base Current-Peak	-2	A
P_C	Total Power Dissipation @ T_C=25℃	25	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-55~150	℃



DIM	mm MIN	mm MAX
A	14.95	15.05
B	10.00	10.10
C	4.40	4.60
D	0.75	0.90
F	3.10	3.30
H	3.70	3.90
J	0.50	0.70
K	13.4	13.6
L	1.10	1.30
N	5.00	5.20
Q	2.70	2.90
R	2.20	2.40
S	2.65	2.90
U	6.40	6.60

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j\text{-}c}$	Thermal Resistance,Junction to Case	5	℃/W

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	I_C= -0.1A; I_B= 0	-80			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C= -3.5A; I_B= -0.35A			-0.3	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	I_C= -3.5A; I_B= -0.35A			-1.2	V
I_{CBO}	Collector Cutoff Current	V_{CB}= -80V; I_E= 0			-100	μA
I_{CEO}	Collector Cutoff Current	V_{CE}= -80V; I_B= 0			-100	μA
I_{EBO}	Emitter Cutoff Current	V_{EB}= -7V; I_C= 0			-100	μA
h_{FE}	DC Current Gain	I_C= -3.5A; V_{CE}= -2V	70			
f_T	Current-Gain—Bandwidth Product	I_C= -0.7A; V_{CE}= -10V		50		MHz
Switching Times						
t_{on}	Turn-on Time	I_C= -3.5A, I_{B1}= -I_{B2}= -0.35A, R_L= 8Ω, V_{BB2}= -4V;			0.3	μs
t_{stg}	Storage Time				1.5	μs
t_f	Fall Time				0.2	μs

Notice：
ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.
ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.
ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.