



CHENMKO ENTERPRISE CO.,LTD

Lead free devices

SMALL FLAT
NPN Epitaxial Transistor

VOLTAGE 50 Volts CURRENT 2 Ampere

2SC1766PT

APPLICATION

- * Power amplifier .

FEATURE

- * Small flat package. (SC-62/SOT-89)
- * Low saturation voltage $V_{CE(sat)} = -0.5V(max.) (I = -1A)$
- * High speed switching time: $t_{stg} = 1.0\mu Sec (typ.)$
- * $PC = 1.0$ to $2.0W$ (mounted on ceramic substrate).
- * High saturation current capability.

CONSTRUCTION

- * NPN Switching Transistor

MARKING

- * hFE Classification P: 1766



Q: Q1766

Y: Y1766



SC-62/SOT-89

CIRCUIT



Dimensions in millimeters

SC-62/SOT-89

MAXIMUM RATINGS (At $T_A = 25^{\circ}C$ unless otherwise noted)

RATINGS	CONDITION	SYMBOL	MIN.	MAX.	UNITS
Collector - Base Voltage	Open Emitter	V_{CBO}	-	50	Volts
Collector - Emitter Voltage	Open Base	V_{CEO}	-	50	Volts
Emitter - Base Voltage	Open Collector	V_{EBO}	-	5	Volts
Collector Current DC		I_C	-	2	Amps
Peak Collector Current		I_{CM}	-	2	Amps
Peak Base Current		I_{BM}	-	0.4	Amps
Total Power Dissipation	$T_A \leq 25^{\circ}C$; Note 1	P_{TOT}	-	1000	mW
Storage Temperature		T_{STG}	-55	+150	$^{\circ}C$
Junction Temperature		T_J	-	+150	$^{\circ}C$
Operating Ambient Temperature		T_{AMB}	-55	+150	$^{\circ}C$

Note

1. Transistor mounted on ceramic substrate 50mmX50mmX0.8t.
2. Measured at Pulse Width 300 μs , Duty Cycle 2%.

2003-8


www.DataSheet

RATING CHARACTERISTIC CURVES (2SC1766PT)

CHARACTERISTICS (At $T_A = 25^\circ\text{C}$ unless otherwise noted)







PARAMETERS	CONDITION	SYMBOL	MIN.	TYPE	MAX.	UNITS
Collector Cut-off Current	$I_E=0$; $V_{CB}=50\text{V}$	I_{CBO}	-	-	0.1	μA
Emitter Cut-off Current	$I_C=0$; $V_{EB}=5\text{V}$	I_{CEO}	-	-	0.1	μA
DC Current Gain	$V_{CE}=2\text{V}$; Note 1 $I_C=0.5\text{A}$; Note 2 $I_C=2.0\text{A}$	h_{FE}	70 20	- -	390 -	
Collector-Emitter Saturation Voltage	$I_C=1\text{A}$; $I_B=0.05\text{A}$	V_{CEsat}	-	-	0.5	Volts
Base-Emitter Saturatio Voltage	$I_C=1\text{A}$; $I_B=0.05\text{A}$	V_{BEsat}	-	-	1.2	mVolts
Collector Capacitance	$I_E=I_C=0$; $V_{CB}=-10\text{V}$; $f=1\text{MHz}$	C_C	-	40	-	pF
Transition Frequency	$I_C=0.5\text{A}$; $V_{CE}=2\text{V}$; $f=100\text{MHz}$	f_T	-	120	-	MHz

SWITCHING TIMES (Between 10% and 90% levels)

PARAMETERS	CONDITION	SYMBOL	MIN.	TYPE	MAX.	UNITS
Turn-on Time		t_{on}	-	0.1	-	μSec
Storage Time		t_s	-	1.0	-	μSec
Fall Time	$I_{B1}=I_{B2}=0.05\text{A}$ Duty cycle $\leq 1\%$	t_f	-	0.1	-	μSec

Note :

1. Pulse test: $t_p \leq 300\mu\text{Sec}$; $\delta \leq 0.02$.
2. $h_{FE}(1)$ Classification P:82 to 180 Q: 120 to 270, Y: 180 to 390

RATING CHARACTERISTIC CURVES (2SC1766PT)**Typical Electrical Characteristics****Figure 1. $V_{CE} - I_C$** **Figure 2. $V_{CE} - I_C$** **Figure 3. $V_{CE} - I_C$** **Figure 4. $h_{FE} - I_C$** **Figure 5. $V_{CE(sat)} - I_C$** **Figure 6. $V_{BE(sat)} - I_C$** 

RATING CHARACTERISTIC CURVES (2SC1766PT)

Typical Electrical Characteristics

Figure 7. $I_c - V_{BE}$




Figure 8. $P_c - T_A$




Figure 9. Safe Operation Area

