
2SC5237

Silicon NPN Epitaxial

HITACHI

Application

High frequency amplifier

Features

- Excellent high frequency characteristics
 $f_T = 400 \text{ MHz typ}$
- High voltage and low output capacitance
 $V_{CEO} = 250 \text{ V, } C_{ob} = 3.5 \text{ pF typ}$
- Suitable for wide band video amplifier

Outline

TO-126FM



1. Emitter
2. Collector
3. Base

2SC5237

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Collector to base voltage	V_{CBO}	250	V
Collector to emitter voltage	V_{CEO}	250	V
Emitter to base voltage	V_{EBO}	3	V
Collector current	I_C	150	mA
Collector peak current	$I_{C(peak)}$	300	mA
Collector power dissipation	P_C	1.4 8* ¹	W
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55 to +150	°C




Note: 1. $T_C = 25^\circ\text{C}$




Electrical Characteristics (Ta = 25°C)




Item	Symbol	Min	Typ	Max	Unit	Test conditions
Collector to base breakdown voltage	$V_{(BR)CBO}$	250	—	—	V	$I_C = 10\ \mu\text{A}$, $I_E = 0$
Collector to emitter breakdown voltage	$V_{(BR)CEO}$	250	—	—	V	$I_C = 1\ \text{mA}$, $R_{BE} = \infty$
Collector cutoff current	I_{CBO}	—	—	1.0	μA	$V_{CB} = 200\ \text{V}$, $I_E = 0$
Emitter cutoff current	I_{EBO}	—	—	10	μA	$V_{EB} = 3\ \text{V}$, $I_C = 0$
DC current transfer ratio	h_{FE}^{*1}	60	—	200	—	$V_{CE} = 10\ \text{V}$, $I_C = 10\ \text{mA}$
Base to emitter voltage	V_{BE}	—	—	1.0	V	$V_{CE} = 10\ \text{V}$, $I_C = 50\ \text{mA}$
Collector to emitter saturation voltage	$V_{CE(sat)}$	—	—	1.0	V	$I_C = 50\ \text{mA}$, $I_B = 5\ \text{mA}$
Gain bandwidth product	f_T	300	400	—	MHz	$V_{CE} = 30\ \text{V}$, $I_C = 50\ \text{mA}$
Collector output capacitance	C_{ob}	—	3.5	5.0	pF	$V_{CB} = 30\ \text{V}$, $I_E = 0$, $f = 1\ \text{MHz}$

Note: 1. The 2SC2537 is grouped by h_{FE} and its specification is as follows.

B	C
60 to 120	100 to 200







When using this document, keep the following in mind:

1. This document may, wholly or partially, be subject to change without notice.
2. All rights are reserved: No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without Hitachi's permission.
3. Hitachi will not be held responsible for any damage to the user that may result from accidents or any other reasons during operation of the user's unit according to this document.
4. Circuitry and other examples described herein are meant merely to indicate the characteristics and performance of Hitachi's semiconductor products. Hitachi assumes no responsibility for any intellectual property claims or other problems that may result from applications based on the examples described herein.
5. No license is granted by implication or otherwise under any patents or other rights of any third party or Hitachi, Ltd.
6. **MEDICAL APPLICATIONS:** Hitachi's products are not authorized for use in **MEDICAL APPLICATIONS** without the written consent of the appropriate officer of Hitachi's sales company. Such use includes, but is not limited to, use in life support systems. Buyers of Hitachi's products are requested to notify the relevant Hitachi sales offices when planning to use the products in **MEDICAL APPLICATIONS**.

HITACHI

Hitachi, Ltd.

Semiconductor & IC Div.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100, Japan
Tel: Tokyo (03) 3270-2111
Fax: (03) 3270-5109

For further information write to:

Hitachi America, Ltd.
Semiconductor & IC Div.
2000 Sierra Point Parkway
Brisbane, CA. 94005-1835
U S A
Tel: 415-589-8300
Fax: 415-583-4207

Hitachi Europe GmbH
Electronic Components Group
Continental Europe
Dornacher StraÙe 3
D-85622 Feldkirchen
München
Tel: 089-9 91 80-0
Fax: 089-9 29 30 00

Hitachi Europe Ltd.
Electronic Components Div.
Northern Europe Headquarters
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA
United Kingdom
Tel: 0628-585000
Fax: 0628-778322

Hitachi Asia Pte. Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 0104
Tel: 535-2100
Fax: 535-1533

Hitachi Asia (Hong Kong) Ltd.
Unit 706, North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon
Hong Kong
Tel: 27359218
Fax: 27306071