

isc Silicon NPN Darlington Power Transistor

2SD1826

DESCRIPTION



- High DC Current Gain-
: $h_{FE} = 2000(\text{Min})@ (V_{CE} = 2V, I_C = 3.5A)$
- Large Current Capability and Wide ASO.
- Complement to Type 2SB1224

APPLICATIONS

- Designed for use in control of motor drivers, printer hammer drivers, relay drivers, and constant-voltage regulators.

ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	70	V
V_{CEO}	Collector-Emitter Voltage	60	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	7	A
I_{CM}	Collector Current-Peak	10	A
P_C	Collector Power Dissipation @ $T_a = 25^\circ\text{C}$	2	W
	Collector Power Dissipation @ $T_c = 25^\circ\text{C}$	25	
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature	-55~150	$^\circ\text{C}$



isc Silicon NPN Darlington Power Transistor

2SD1826

ELECTRICAL CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 30mA; R _{BE} = ∞	60			V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	I _C = 5mA; I _E = 0	70			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 3.5A; I _B = 7mA			1.5	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 3.5A; I _B = 7mA			2.0	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 40V; I _E = 0			100	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0			3.0	mA
h _{FE}	DC Current Gain	I _C = 3.5A; V _{CE} = 2V	2000	5000		
f _T	Current-Gain—Bandwidth Product	I _C = 3.5A; V _{CE} = 5V		20		MHz

Switching Times

t _{on}	Turn-on Time	I _C = 3A, I _{B1} = -I _{B2} = 6mA, V _{CC} = 20V; R _L = 6.7 Ω		0.6		μ s
t _{stg}	Storage Time			3.0		μ s
t _f	Fall Time			1.7		μ s

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.