

## Phase Control Thyristors

### Features

1. 495 PT series Thyristors are designed for various power controls

2. Voltage rating up to 800 V.

3. Typical application

- DC motor control
- Controlled DC power supplies
- AC controllers

Ordering code

495	PT	xx	B	0
(1)	(2)	(3)	(4)	(5)

(1) Maximum average on-state current , A

(2) For Phase Control Thyristor


(3) Voltage code , code x 100 =  $V_{RRM} / V_{DRM}$

(4) package style : A , B , C , D , E for Disc Type

(5) Terminal types

0 - for eyelet







### B TYPE






All dimensions in millimeters ( inches )

### Electrical Characteristics

Symbol	Parameter	Condition	Value			Unit
			Min.	Type	Max.	
$I_T(AV)$	Mean on-state current	180° half sine wave , 50Hz Double side cooled , $T_C = 55^\circ C$			495	A
$I_T(RMS)$	Max. RMS on-state current	Double side cooled , $T_C=25^\circ C$			1032	A
$V_{RRM}$ $V_{DRM}$	Repetitive peak off-state voltage Repetitive peak reverse voltage	$V_{DRM} & V_{RRM} t_p=10ms$ $V_{DsM} & V_{RsM} = V_{DRM} & V_{RRM} + 100V$	200		800	V
$I_{TSM}$	Surge on-state current	10 ms half sine wave			6000	A
$I_t^2$	For fusing coordination	$V_R = 0.6V_{RRM}$			218	Ka <sup>2</sup> s
$V_{T(TO)}$	Threshold voltage				0.85	V
$r_t$	On-state slope resistance				0.53	mΩ
$V_{TM}$	Max. Forward voltage drop	$I_{TM}=900A , F=8.0KN$			1.26	V
$I_H$	Holding current	$V_A=12V , I_A=1A$			600	mA
$d_i/dt$	Critical rate of rise of turned-on current	Gate drive 20V , 20 Ω, $t_r \leq 0.5 \mu s$			1000	A/μs
$t_q$	Typical turn-off time	$I_{TM}=400A , d_V/dt=30V/\mu s$ $d_iRR/dt=-10 A/\mu s$			150	μs
$d_V/dt$	Critical rate of rise of off-state voltage	$V_{DM}=0.67 V_{DRM}$			1000	V/μs
$P_G$	Max. average gate power				2	W
$P_{GM}$	Max. peak gate power square	Square wavepulse width 100 μs			30	W
$I_{GT}$	Gate trigger current				150	mA
$V_{GT}$	Gate trigger voltage	$V_A=12V , I_A=1A$			3	V
$T_{stg}$	Storage temperature		-40		150	°C
$T_j$	Max.operating temperaturerange		-40		125	°C
$R_{th(j-h)}$	Thermal resistance(junction to heatsink)	Double side cooled , clamping force 8.0 KN			0.21	°C/ W
$F_m$	Mounting force		3.3		5.5	KN
$W_t$	Approximate weight			70		g

**Fig. 1**

**Fig. 3**

**Fig. 5**

**Fig. 2**

**Fig. 4**

**Fig. 6**


**Fig. 7**

**Fig. 8**

**Fig. 9**

**Fig. 10**
