

SPECIFICATION

Device Name : IGBT Module

Type Name : 7MBR20SA060D-01

Spec. No. : MS6M 0542

Date : Jun. - 02 - 2000

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.
Matsumoto Factory

	DATE	NAME	APPROVED	Fuji Electric Co., Ltd.			
DRAWN	Jun. - 2 - '00	<i>K. Kobayashi</i>	<i>T. Miyata</i>	DWG. NO.	MS6M 0542	1 / 10	
CHECKED	June - 2 - '00	<i>S. Kikuchi</i>					

Revised Records

[illegible]

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.

DWG. NO.


MS6M 0542

$$\frac{2}{10}$$


H04-004-06

7MBR20SA060D-01

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



Fuji Electric Co., Ltd.

DWG. NO.

MS6M 0542

3/10

H04-004-03

3. Absolute Maximum Ratings (at Tc= 25C unless otherwise specified)

Items		Symbols	Conditions	Maximum Ratings	Units	
Inverter	Collector-Emitter voltage	VCES		600	V	
	Gate-Emitter voltage	VGES		+20	V	
	Collector current	Ic	Continuous	20	A	
		Icp	1ms	40	A	
		-Ic		20	A	
Collector Power Dissipation		Pc	1 device	80	W	
Brake	Collector-Emitter voltage	VCES		600	V	
	Gate-Emitter voltage	VGES		+20	V	
	Collector current	Ic	Continuous	20	A	
		Icp	1ms	40	A	
	Collector Power Dissipation		Pc	1 device	50	W
	Repetitive peak reverse Voltage(Diode)		VRRM		600	V
Converter	Hepetitive peak reverse Voltage	VRRM		800	V	
	Average Output Current	Io	50Hz/60Hz sine wave	25	A	
	Surge Current (Non-Repetitive)	IFSM	Tj=150C,10ms	260	A	
	I²t (Non-Repetitive)	I²t	half sine wave	338	A²s	
Junction temperature		Tj		150	C	
Storage temperature		Tstg		-40~ +125	C	
Isolation voltage	between terminal and copper base ^{(*)1}	Viso	AC : 1min.	2500	V	
	between thermistor and others ^{(*)2}			2500	V	
Mounting Screw Torque ^{(*)3}				3.5	Nm	

(*)1 All terminals should be connected together when isolation test will be done.

(*)2 Terminal 8 and 9 should be connected together. Terminal 1 to 7 and 10 to 24 should be connected together and shorted to copper base.

(*)3 Recommendable Value : 2.5~3.5 Nm (M5)

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.

DWG.NO.

MS6M 0542

4/10

H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

4. Electrical characteristics (at $T_J = 25^\circ\text{C}$ unless otherwise specified)

	Items	Symbols	Conditions	Characteristics			Units
				min.	typ.	Max.	
Inverter	Zero gate voltage Collector current	ICES	VGE 0 V, VCE 600 V			1.0	mA
	Gate-Emitter leakage current	IGES	VCE 0 V, VGE +20 V			200	nA
	Gate-Emitter threshold voltage	VGE(th)	VCE 20 V, Ic = 20 mA	5.5	7.8	8.5	V
	Collector-Emitter saturation voltage	VCE(sat)	VGE 15 V, chip Ic = 20 A terminal		1.8		V
	Input capacitance	Cies	VGE 0 V, VCE 10 V f = 1 MHz		3000		pF
	Turn-on time	ton	Vcc = 300 V		0.45	1.2	us
		tr	Ic = 20 A		0.25	0.6	
		tr(f)	VGE +15 V		0.08		
	Turn-off time	toff	RG = 120 ohm		0.40	1.0	us
		tf			0.05	0.35	
	Forward on voltage	VF	IF = 20 A chip terminal		1.8		V
	Reverse recovery time	trr	IF = 20 A			300	ns
Brake	Zero gate voltage Collector current	ICES	VGE 0 V, VCE 600 V			1.0	mA
	Gate-Emitter leakage current	IGES	VCE 0 V, VGE +20 V			200	nA
	Collector-Emitter saturation voltage	VCE(sat)	VGE 15 V, chip Ic = 20 A terminal		1.8		V
	Turn-on time	ton	Vcc = 300 V		0.45	1.2	us
		tr	Ic = 20 A		0.25	0.6	
	Turn-off time	toff	VGE +15 V		0.40	1.0	us
		tf	RG = 120 ohm		0.05	0.35	
Converter	Reverse current	IRRM	VR = 600 V			1.0	mA
	Forward on voltage	VFM	IF = 20 A chip terminal		1.0		V
					1.1	1.5	
Thermistor	Reverse current	IRRM	VR = 800 V			1.0	mA
	Resistance	R	T = 25°C		5000		ohm
	B value	B	T = 100°C	465	495	520	K

5. Thermal resistance characteristics

Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Thermal resistance (1 device)	Rth(j-c)	Inverter IGBT			1.56	C/W
		Inverter FWD			3.00	
		Brake IGBT			2.50	
		Converter Diode			1.30	
Contact Thermal resistance	Rth(c-f)	with Thermal Compound (*)		0.05		C/W

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

Fuji Electric Co., Ltd.


DWG. NO.

MS6M 0542

5/10

H04-004-03

6. Indication on module



7. Applicable category


This specification is applied to Power Integrated Module named 7MBR20SA060D-01.

8. Storage and transportation notes

- The module should be stored at a standard temperature of 5 to 35°C and humidity of 45 to 75% .
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
- Avoid exposure to corrosive gases and dust.
- Avoid excessive external force on the module.
- Store modules with unprocessed terminals.
- Do not drop or otherwise shock the modules when transporting.
- Please connect adequate fuse or protector of circuit between three-phase line and this product to prevent the equipment from causing secondary destruction.

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

9. Definitions of switching time



Fuji Electric Co., Ltd.

DWG. NO.


MS6M 0542

6 / 10


H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


[Inverter]
Collector current vs. Collector-Emitter voltage
 $T_J = 25^\circ\text{C}$ (typ.)




[Inverter]
Collector current vs. Collector-Emitter voltage
 $T_J = 125^\circ\text{C}$ (typ.)




[Inverter]
Collector current vs. Collector-Emitter voltage
 $V_{GE} = 15\text{V}$ (typ.)




[Inverter]
Collector-Emitter voltage vs. Gate-Emitter voltage
 $T_J = 25^\circ\text{C}$ (typ.)



[Inverter]
Capacitance vs. Collector-Emitter voltage (typ.)
 $V_{GE} = 0\text{V}$, $f = 1\text{MHz}$, $T_J = 25^\circ\text{C}$



[Inverter]
Dynamic Gate charge (typ.)
 $V_{CC} = 3.00\text{V}$, $I_C = 20\text{A}$, $T_J = 25^\circ\text{C}$



Fuji Electric Co., Ltd.







DWG. NO.

MS6M 0542

7/10

H04-004-03

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.



Fuji Electric Co., Ltd.

DWG. NO.


MS6M 0542

8/10


H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


[Inverter]
Forward current vs. Forward on voltage (typ.)




[Inverter]
Reverse recovery characteristics (typ.)
 $V_C = 300\text{V}$, $V_{GE} = \pm 15\text{V}$, $R_g = 120\ \Omega$




[Converter]
Forward current vs. Forward on voltage (typ.)



Transient thermal resistance



[Thermistor]
Temperature characteristic (typ.)



Fuji Electric Co., Ltd.







DWGNO.

MS6M 0542

9/10

H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.



Fuji Electric Co., Ltd.

DWG. NO.

MS6M 0542

10/10

H04-004-03