

# International **IR** Rectifier

## **8AF SERIES**

### PRESSFIT RECTIFIER DIODES

#### Features and Descriptions

- Convenient pressfit package
- Available with and without leads
- High surge capabilities

50 A

#### Application

- Welders, Battery charges, Alternators

#### Major Ratings and Characteristics

| Parameters      | 8AF        | Units             |
|-----------------|------------|-------------------|
| $I_{F(AV)}$     | 50         | A                 |
| @ $T_c$         | 150        | °C                |
| $I_{F(RMS)}$    | 79         | A                 |
| $I_{FSM}$ @50Hz | 714        | A                 |
| @60Hz           | 747        | A                 |
| $I^2t$ @50Hz    | 2546       | A <sup>2</sup> s  |
| @60Hz           | 2324       | A <sup>2</sup> s  |
| $I^2/t$         | 25455      | A <sup>2</sup> /s |
| $V_{RRM}$ range | 100 to 800 | V                 |
| $T_j$           | -65 to 195 | °C                |

**IR Case Style B-47**

## 8AF Series

Bulletin I20262 Rev.A 06/03

International  
**IR** Rectifier

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

| Type number | Voltage Code | $V_{RRM}$ , maximum repetitive peak reverse voltage V | $V_{RSM}$ , maximum non-repetitive peak rev. voltage V | $I_{RRM}$ max. @ $T_J = 150^\circ C$ mA |
|-------------|--------------|---|--|---|
| 8AF         | 1            | 100   | 150  | 5                                       |
|             | 2            | 200   | 300  | 5                                       |
|             | 4            | 400   | 500  | 5                                       |
|             | 8            | 800   | 900  | 5                                       |

#### Forward Conduction

| Parameter   | 8AF   | Units         | Conditions   |                      |   |  |  |  |  |
|---|-------|---------------|--|----------------------|---|--|--|--|--|
| $I_{F(AV)}$ @ Case temperature  | 50    | A             | 180° conduction, half sine wave  |                      |   |  |  |  |  |
|   | 150   | °C            |  |                      |   |  |  |  |  |
| $I_{F(RMS)}$  | 79    | A             | 100% $V_{RRM}$ reapplied   | No voltage reapplied | Sinusoidal half wave,<br>Initial $T_J = T_J$ max. |  |  |  |  |
| $I_{FSM}$ Maximum peak, one-cycle forward, non-repetitive surge current | 714   | A             |  |                      |   |  |  |  |  |
|   | 747   |               |  |                      |   |  |  |  |  |
|   | 600   |               |  |                      |   |  |  |  |  |
|   | 628   |               |  |                      |   |  |  |  |  |
| $I^2t$ Maximum $I^2t$ for fusing  | 2546  | $A^2s$        | 100% $V_{RRM}$ reapplied   | No voltage reapplied | Initial $T_J = T_J$ max.                          |  |  |  |  |
|   | 2324  |               |  |                      |   |  |  |  |  |
|   | 1800  |               |  |                      |   |  |  |  |  |
|   | 1643  |               |  |                      |   |  |  |  |  |
| $I^2\sqrt{t}$   | 25455 | $A^2\sqrt{s}$ | t = 0.1 to 10ms, no voltage reapplied  |                      |   |  |  |  |  |
| $V_{F(TO)1}$  | 0.60  | V             | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , $T_J = T_J$ max. |                      |   |  |  |  |  |
| $V_{F(TO)2}$  | 0.68  |               | $(\pi \times I_{F(AV)} < I < 20 \times \pi \times I_{F(AV)})$ , $T_J = T_J$ max.     |                      |   |  |  |  |  |
| $r_{f1}$  | 6.66  | $m\Omega$     | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , $T_J = T_J$ max. |                      |   |  |  |  |  |
| $r_{f2}$  | 6.25  |               | $(\pi \times I_{F(AV)} < I < 20 \times \pi \times I_{F(AV)})$ , $T_J = T_J$ max.     |                      |   |  |  |  |  |
| $V_{FM}$  | 1.45  | V             | $T_J = 25^\circ C$ , $I_{FM} = \pi \times \text{rated } I_{F(AV)}$                   |                      |   |  |  |  |  |

#### Thermal and Mechanical Specifications

| Parameter   | 8AF        | Units      | Conditions              |  |
|---|------------|------------|-------------------------|--|
| $T_J$ Max. junction operating temperature range         | -65 to 195 | $^\circ C$ | DC operation            |  |
| $T_{stg}$ Storage temperature range                     | -65 to 195 |            | As per mounting details |  |
| $R_{thJC}$ Max. thermal resistance, junction to case    | 0.60       | K/W        |                         |  |
| $R_{thCS}$ Typical thermal resistance, case to heatsink | 0.50       |            |                         |  |
| wt Approximate weight                                   | 10 (0.36)  | g (oz)     |                         |  |
| Case style  | B-47       |            | See outline table       |  |

MOUNTING: A  $12.6 \pm 0.02$ mm (0.496 to 0.497 inch) diameter hole should be drilled in heatsink, the leading edge chamfered to 0.038mm (0.015 inch)  $\times 45^\circ$ . The diode should then be press fitted, ensuring that the sides of the diode are kept parallel to the sides of the hole.

$\Delta R_{thJC}$  Conduction


(The following table shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction | Rectangular conduction | Units | Conditions        |
|------------------|-----------------------|------------------------|-------|-------------------|
| 180°             | 0.042                 | 0.026                  | K/W   | $T_J = T_{J\max}$ |
| 120°             | 0.045                 | 0.043                  |       |                   |
| 90°              | 0.06                  | 0.06                   |       |                   |
| 60°              | 0.10                  | 0.10                   |       |                   |
| 30°              | 0.15                  | 0.15                   |       |                   |

Ordering Information Table

| Device Code |   | 8AF | 8 | N | LV |
|-------------|---|-----|---|---|----|
|             |   | 1   | 2 | 3 | 4  |
| <b>1</b>    | - Essential part number   |     |   |   |    |
| <b>2</b>    | - Voltage code: Code x 100 = $V_{RRM}$ (See Voltage Ratings Table)  |     |   |   |    |
| <b>3</b>    | - N = Normal Polarity (cathode to case)<br>R = Reverse Polarity (anode to case)                                     |     |   |   |    |
| <b>4</b>    | - PP = Without Lead<br>LH = Horizontal Lead<br>LV = Vertical Lead<br>Available as special product - Contact Factory |     |   |   |    |

Outline Table



## 8AF Series

Bulletin I20262 Rev.A 06/03

International  
**IR** Rectifier




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristic