



A030JTN01.0 product Spec	Version	1.0
	Page	1/49

# CUSTOMER APPROVAL SHEET

**Company Name**

**MODEL**

**A030JTN01.0**

**CUSTOMER**

Title :

**APPROVED**

Name :

- APPROVAL FOR SPECIFICATIONS ONLY (Spec. Ver. 1.0)
- APPROVAL FOR SPECIFICATIONS AND ES SAMPLE (Spec. Ver.       )
- APPROVAL FOR SPECIFICATIONS AND CS SAMPLE (Spec. Ver.       )
- CUSTOMER REMARK :

**AUO PM :**

**P/N : 97.03A35.000**

**Comment:**

**1 Li-Hsin Rd. 2. Science-Based Industrial Park  
Hsinchu 300, Taiwan, R.O.C.  
Tel: +886-3-500-8899  
Fax: +886-3-577-2730**



A030JTN01.0 product Spec	Version	1.0
	Page	2/49

Doc. version: 1.0

Total pages: 55

Date: 2012/01/30

## Product Specification

### 3.0" COLOR TFT-LCD MODULE

<b>Model Name</b>	<b>A030JTN01.0</b>
<b>Planned Lifetime:</b>	<b>From 2011/Sep To 2012/Sep</b>
<b>Phase-out Control:</b>	<b>From 2012/Oct To 2013/Mar</b>
<b>EOL Schedule:</b>	<b>2013/Mar</b>

< > Preliminary Specification

<◆> Final Specification

Note: The content of this specification is subject to change without prior notice.

© 2011 AU Optronics  
All Rights Reserved,  
Do Not Copy.



A030JTN01.0 product Spec	Version	1.0
	Page	3/49

## Record of Revision

Version	Revise Date	Page	Content
1.0	2012/01/30		First version



A030JTN01.0 product Spec	Version	1.0
	Page	4/49

## Contents

<b>Precaution in Design .....</b>	<b>6</b>
1. Notice .....	6
2. For Handing And System Design .....	7
3. For Operating LCD Module .....	9
4. Precaution For Storage .....	9
5. Other Notice .....	10
6. Precaution for Discarding Liquid Crystal Modules .....	10
<b>A. Physical specifications .....</b>	<b>11</b>
<b>B. Electrical specifications .....</b>	<b>12</b>
1. Pin assignment .....	12
2. Absolute maximum ratings .....	14
3. Electrical characteristics .....	14
3.1 Recommended operating conditions (GND=0V) .....	14
3.2 Electrical characteristics (GND=0V) .....	14
3.2 Digital input signal overshoot and undershoot limitation .....	15
3.3 Recommended Capacitance Values of External Capacitor .....	16
3.4 Backlight driving conditions.....	16
4. Input timing AC characteristic .....	17
5. Input timing format.....	18
5.1 UPS051 timing conditions (Refer to Fig.1 Fig.2 Fig.3).....	18
5.2 YUV 320 8-bit serial mode (Refer to Fig.4 Fig.5 ) .....	21
5.3 YUV 320 to RGB conversion.....	24
6. Serial control interface AC characteristic.....	25
6.1 Timing chart.....	25
6.2 The configuration of serial data at SDA terminal is at below.....	26
6.3 Register table .....	27
6.4 Register description .....	28
<b>C. Optical specification (Note 1, Note 2, Note 3).....</b>	<b>38</b>
<b>D. Reliability test items .....</b>	<b>41</b>
<b>E. Packing Design .....</b>	<b>43</b>
1. Packing form.....	43
<b>F. Outline dimension .....</b>	<b>44</b>
<b>G. Application note .....</b>	<b>45</b>
1. Input Data Timing .....	45
2. Application circuit.....	46
2.1 With external LED driver circuit.....	46



A030JTN01.0 product Spec	Version	1.0
	Page	5/49

3. Power on/off sequence .....	47
3.1 Power on (Standby Disabling) .....	47
3.2 Power off (Standby Enabling) .....	48
4. Recommended power on/off serial command settings .....	49
a. Recommended Power On Register Setting with external LED driver.....	49
b. Recommended Power Off Register Setting .....	49



A030JTN01.0 product Spec	Version	1.0
	Page	6/49

## Precaution in Design

### 1. Notice

- 1) These specification sheets are the proprietary product of AU Optronics Corporation (AUO) and include materials protected under copyright of AUO. Do not reproduce or cause any third party to reproduce them in any form or by any means, electronic or mechanical, for any purpose, in whole or in part, without the express written permission of AUO.
- 2) The application examples in these specification sheets are provided to explain the representative applications of the device and are not intended to guarantee any industrial property right or other rights or license you to use them. AUO assumes no responsibility for any problems related to any industrial property right of a third party resulting from the use of the device.
- 3) The device listed in these specification sheets was designed and manufactured for use in Telecommunication equipment (terminals)
- 4) In case of using the device for applications such as control and safety equipment for transportation (aircraft, trains, automobiles, etc. ), rescue and security equipment and various safety related equipment which require higher reliability and safety, take into consideration that appropriate measures such as fail-safe functions and redundant system design should be taken.
- 5) Do not use the device for equipment that requires an extreme level of reliability, such as aerospace applications, telecommunication equipment (trunk lines), nuclear power control equipment and medical or other equipment for life support.
- 6) AUO assumes no responsibility for any damage resulting from the use of the device which does not comply with the instructions and the precautions specified in these specification sheets.
- 7) Contact and consult with a AUO sales representative for any questions about this device.

### . Operating Precautions

- 1) Since front polarizer is easily damaged, please be cautious and not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or soft cloth.
- 5) Since the panel is made of glass, it may be broken or cracked if dropped or bumped on hard surface.
- 6) Do not open nor modify the module assembly.
- 7) Do not press the reflector sheet at the back of the module to any direction.
- 8) In case if a module has to be put back into the packing container slot after it was taken out from the container, do not press the center of the LED light bar edge. Instead, press at the far ends of the LED light bar edge softly. Otherwise the TFT Module may be damaged.



A030JTN01.0 product Spec	Version	1.0
	Page	7/49

## 2. For Handling And System Design

- 1) Do not scratch the surface of the polarizer film as it is easily damaged.
- 2) If the cleaning of the surface of the LCD panel is necessary, wipe it swiftly with cotton or other soft cloth. Do not use organic solvent as it damages polarizer.
- 3) Water droplets on polarizer must be wiped off immediately as they may cause color changes, or other defects if remained for a long time.
- 4) Since this LCD panel is made of glass, dropping the module or banging it against hard objects may cause cracks or fragmentation.
- 5) Certain materials such as epoxy resin (amine's hardener) or silicone adhesive agent (de-alcohol or de-oxy) emits gas to which polarizer reacts (color change). Check carefully that gas from materials used in system housing or packaging do not harm polarizer.
- 6) Liquid crystal material will freeze below specified storage temperature range and it will not get back to normal quality even after temperature comes back within specified temperature range. Liquid crystal material will become isotropic above specified temperature range and may not get back to normal quality. Keep the LCD module always within specified temperature range.
- 7) Do not expose LCD module to the direct sunlight or to strong ultraviolet light for long time.
- 8) If the LCD driver IC (COG) is exposed to light, normal operation may be impeded. It is necessary to design so that the light is shut off when the LCD module is.
- 9) Do not disassemble the LCD module as it may cause permanent damage.
- 10) As this LCD module contains components sensitive to electrostatic discharge, be sure to follow the instructions in below.

### ① Operators

Operators must wear anti-static wears to prevent electrostatic charge up and discharge from human body.

### ② Equipment and containers

Process equipment such as conveyor, soldering iron, working bench and containers may possibly generate electrostatic charge up and discharge. Equipment must be grounded through 100Mohms resistance. Use ion blower.

### ③ GND

To avoid ESD (Electro Static Discharge) damage, be sure to ground yourself before handling TFT- LCD Module.

### ④ Humidity

Proper humidity of working room may reduce the risk of electrostatic charge up and discharge. Humidity should be kept over 50% all the time.

### ⑤ Transportation/storage

Storage materials must be anti-static to prevent causing electrostatic discharge.

### ⑥ Others


Protective film is attached on the surface of LCD panel to prevent scratches or other damages. When removing this protective film, remove it slowly under proper anti-ESD control such as ion blower.

- 11) Hold LCD very carefully when placing LCD module into the system housing. Do not apply excessive stress

A030JTN01.0 product Spec	Version	1.0
	Page	8/49

or pressure to LCD module. Do not to use chloroprene rubber as it may affect on the reliability of the electrical interconnection.

- 12) Do not hold or touch LCD panel to flex interconnection area as it may be damaged.
- 13) As the binding material between LCD panel and flex connector mentioned in 12) contains an organic material, any type of organic solvents are not allowed to be used. Direct contact by fingers is also prohibited.
- 14) When carrying the LCD module, place it on the tray to protect from mechanical damage. It is recommended to use the conductive trays to protect the CMOS components from electrostatic discharge. When holding the module, hold the Plastic Frame of LCD module so that the panel, COG and other electric parts are not damaged.



- 15) Place a protective cover on the LCD module to protect the glass panel from mechanical damages.
- 16) LCD panel is susceptible to mechanical stress and even the slightest stress will cause a color change in background. So make sure the LCD panel is placed on flat plane without any continuous twisting, bending or pushing stress.
- 17) Protective film is placed onto the surface of LCD panel when it is shipped from factory. Make sure to peel it off before assembling the LCD module into the system. Be very careful not to damage LCD module by electrostatic discharge when peeling off this protective film. Ion blower and ground strap are recommended.
- 18) Make sure the mechanical design of the system in which the LCD module will be assembled matches specified viewing angle of this LCD module.
- 19) This LCD module does not contain nor use any ODS (1,1,1-Trichloroethane, CCL4) in all materials used, in all production processes.

A030JTN01.0 product Spec	Version	1.0
	Page	9/49


### 3. For Operating LCD Module

- 1) Do not operate or store the LCD module under outside of specified environmental conditions.
- 2) At the shipment, adjust the contrast of each LCD module with electric volume. LCD contrast may vary from panel to panel depending on variation of LCD power voltage from system.
- 3) As opt-electrical characteristics of LCD will be changed, dependent on the temperature, the confirmation of display quality and characteristics has to be done after temperature is set at 25 °C and it becomes stable.


### 4. Precaution For Storage

- 1) Do not expose the LCD module to direct sunlight or strong ultraviolet light for long periods. Store in a dark place.
- 2) The liquid crystal material will solidify if stored below the rated storage temperature and will become an isotropic liquid if stored above the rated storage temperature, and may not retain its original properties. Only store the module at normal temperature and humidity (25±5°C, 60~10%RH) in order to avoid exposing the front polarizer to chronic humidity.
- 3) Keeping Method

DON'T



DO



- a. Don't keeping under the direct sunlight.
- b. Keeping in the tray under the dark place.

- 4) Do not operate or store the LCD module under outside of specified environmental conditions.
- 5) Be sure to prevent light striking the chip surface.



A030JTN01.0 product Spec	Version	1.0
	Page	10/49

## 5. Other Notice

- 1) Do not operate or store the LCD module under outside of specified environmental conditions.
- 2) As electrical impedance of power supply lines (VCC-GND) are low when LCD module is working, place the de-coupling capacitor near by LCD module as close as possible.
- 3) Reset signal must be sent after power on to initialize LSI. LSI does not function properly until initialize it by reset signal.
- 4) Generally, at power on, in order not to apply DC charge directly to LCD panel, supply logic voltage first and initialize LSI logic function including polarity alternation. Then supply voltage for LCD bias. At power off, in order not to apply DC charge directly to LCD panel, execute Power OFF sequence and Discharge command.
- 5) Don't touch to FPC surface, exposed IC chip, electric parts and other parts, to any electric, metallic materials.
- 6) No bromide specific fire-retardant material is used in this module.
- 7) Do not display still picture on the display over 2 hours as this will damage the liquid crystal.
- 8) The connector used in this LCD module is the one AUO have not ever used.

Therefore, please note that the quality of this connector concerned is out of AUO's guarantee.

## 6. Precaution for Discarding Liquid Crystal Modules

COG: After removing the LSI from the liquid crystal panel, dispose of it in a similar way to circuit boards from electronic devices.

LCD panel: Dispose of as glass waste. This LCD module contains no harmful substances. The liquid crystal panel contains no dangerous or harmful substances. The liquid crystal panel only contains an extremely small amount of liquid crystal (approx.100mg) and therefore it will not leak even if the panel should break.

-Its median lethal dose (LD50) is greater than 2,000 mg/kg and a mutagenetic (Aims test: negative) material is employed.



A030JTN01.0 product Spec	Version	1.0
	Page	11/49

## A. Physical specifications

NO.	Item	Specification	Remark
1	Display resolution ( dot )	960(W) x 480(H)	
2	Active area ( mm )	60 x 45	
3	Screen size ( inch )	2.95 (Diagonal)	
4	Dot pitch ( um )	62.5x 93.75	
5	Color configuration	R, G, B delta	
6	Overall dimension ( mm )	70.2 x 51.4 x 2.2	Note 1
7	Weight ( g )	18	
8	Panel surface treatment	Hard Coating	

Note 1: Refer to F. Outline Dimension



A030JTN01.0 product Spec	Version	1.0
	Page	12/49

## B. Electrical specifications

### 1. Pin assignment

Pin no	Symbol	I/O	Description	Remark
1	VLED+	P	LED backlight anode	
2	VLED-	P	LED backlight cathode	
3	GND	P	Ground	
4	GRB	I	Global reset pin	
5	Dummy	D	Dummy pads. Internal connects floating	Note 1
6	CS	I	Chip select pin of SPI interface	
7	SDA	I	Data input pin of SPI mode	
8	SCL	I	Clock input pin of SPI mode	
9	VDDIO	P	Voltage input pin for digital power	
10	VDD_18V	C	Connect capacitor	
11	LCD_ID	D	Dummy pads. Internal connects floating	
12	GND	P	Ground	
13	DCLK	I	Data-clock and oscillator source	
14	GND	P	Ground	
15	VSYNC	I	Vertical synchronizing signal	
16	H SYNC	I	Horizontal synchronizing signal	
17	GND	P	Ground	
18	D07	I	Data signal (MSB)	
19	D06	I	Data signal	
20	D05	I	Data signal	
21	D04	I	Data signal	
22	D03	I	Data signal	
23	D02	I	Data signal	
24	D01	I	Data signal	
25	D00	I	Data signal (LSB)	
26	GND	P	Ground	
27	VCOMH	C	Connect capacitor	
28	GND	P	Ground	
29	VCOML	C	Connect capacitor	
30	VDD2	C	Connect capacitor	
31	C5P	C	Connect capacitor	
32	C5N	C	Connect capacitor	
33	VCL	C	Connect capacitor	

A030JTN01.0 product Spec	Version	1.0
	Page	13/49


34	C1P	C	Connect capacitor	
35	C1N	C	Connect capacitor	
36	C2P	C	Connect capacitor	
37	C2N	C	Connect capacitor	
38	C3N	C	Connect capacitor	
39	C3P	C	Connect capacitor	
40	VGH	C	Connect capacitor	
41	C4P	C	Connect capacitor	
42	C4N	C	Connect capacitor	
43	VGL	C	Connect capacitor	
44	VDD	P	Voltage input pin for analog power	
45	VDD	P	Voltage input pin for analog power	

I : Input, O : Output, C : Capacitor, P : Power

Note1: For AUO OTP function.

Note2:D[07:00]:serial 8-bit data input when YUV 320 8-bit or UPS051 timing.

Note3: Definition of scanning direction, Refer to figure as below :



A030JTN01.0 product Spec	Version	1.0
	Page	14/49

## 2. Absolute maximum ratings

Item	Symbol	Condition	Min.	Max.	Unit	Remark
Supply Voltage	VDD	GND=0V	-0.3	6.0		
Supply Voltage	VDDIO	GND=0V	-0.3	6.0	V	

Note 1: Functional operation should be restricted under ambient temperature (25°C).

Note 2: Maximum ratings are those values beyond which damages to the device may occur. Functional operation should be restricted to the limits in the Electrical Characteristics chapter.

## 3. Electrical characteristics

### 3.1 Recommended operating conditions (GND=0V)

Item		Symbol	Min.	Typ.	Max.	Unit	Remark
		VDD	3.0	3.3	3.6	V	
		VDDIO	3.0	3.3	3.6		
Input Signal	H Level	$V_{IH}$	$0.7^* VDDIO$	-	VDDIO	V	
	L Level	$V_{IL}$	GND	-	$0.3^* VDDIO$	V	


### 3.2 Electrical characteristics (GND=0V)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Input Current for $V_{VDD}$	$I_{VDD}$	$V_{VDD}=3.3V$	-	14	18	mA	Note 1
	$I_{VDD(STANDBY)}$		-	50	100	uA	
Input Current for $V_{VDDIO}$	$I_{VDDIO}$	$V_{VDDIO}=3.3V$	-	0.5	1	mA	Note 1
	$I_{VDDIO(STANDBY)}$		-	20	50	uA	
DC-DC voltage	$V_{GH}$	$V_{DD}=3.3V$	13	14	15	V	Note 2
	$V_{GL}$	$V_{DD}=3.3V$	-10	-9	-8	V	Note 2
VCOM voltage	$V_{CAC}$	-	4.8	5.4	6	Vp-p	AC component, Note 3

Note 1: Test Condition: 8colorbar+Grayscale pattern, UPS051 mode, Frame rate: 60Hz, other registers are default setting.

Note 2:  $V_{GH}$  and  $V_{GL}$  are output voltages of integrated LCD driver IC.

Note 3: The brightness of LCD panel could be adjusted by the adjustment of the AC component of VCOM.




A030JTN01.0 product Spec	Version	1.0
	Page	15/49

### 3.2 Digital input signal overshoot and undershoot limitation

The digital input signal overshoot and undershoot voltage should keep under VDDIO+0.3V and over GND-0.3V.

Symbol	Overshoot	Undershoot
D0-D15		
DCLK		
H SYNC		
V SYNC		
SCL	< VDDIO+0.3V	
SDA		> GND-0.3V
CS		
GRB		
STB		



A030JTN01.0 product Spec	Version	1.0
	Page	16/49

### 3.3 Recommended Capacitance Values of External Capacitor


The recommended capacitance values of the external capacitor are shown below. These values should be finally determined only after performing sufficient evaluation on the module.

Pin name	Recommended value of capacitors ( $\mu\text{F}$ )	Withstanding voltage (V)
VGH	1 to 2.2	25
VGL	1 to 2.2	16
VDD	1 to 2.2	6.3
VDDIO	1 to 2.2	6.3
VDD_18V	1 to 2.2	6.3
VDD2	1 to 4.7	10
VCL	1 to 2.2	10
VCOMH	1 to 4.7	10
VCOML	1 to 4.7	10
C1P,C1N	1	6.3
C2P,C2N	1	6.3
C3P,C3N	1	10
C4P,C4N	1	16
C5P,C5N	1	16

### 3.4 Backlight driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
LED current			25	27.5	mA	
LED voltage	$V_L$		12.8	14	V	4 LED's
Feedback voltage	$V_{FB}$				V	



Note1: To consider Backlight driver and feedback resistor tolerance.



#### 4. Input timing AC characteristic

(VDD=3.0 ~3.6V, AGND=GND=0V, TA=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
DCLK duty cycle	Tcw	40	50	60	%	
VSYNC setup time	Tvst	8	-	-	ns	
VSYNC hold time	Tvhd	8	-	-	ns	
Hsync setup time	Thst	8	-	-	ns	
Hsync hold time	Thhd	8	-	-	ns	
Data setup time	Tdst	8	-	-	ns	
Data hold time	Tdhd	8	-	-	ns	



t<sub>H</sub> means: HSYNC period



A030JTN01.0 product Spec	Version	1.0
	Page	18/49

## 5. Input timing format

### 5.1 UPS051 timing conditions (Refer to Fig.1 Fig.2 Fig.3)

Parameter	Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK frequency	$1/t_{DCLK}$	30	33	36	MHz	
HSYNC	Period	$t_H$	1004	1048	1399	$t_{DCLK}$
	Display period	$t_{hd}$		960		$t_{DCLK}$
	Back porch	$t_{hbp}$	20	40	255	$t_{DCLK}$
	Front porch	$t_{hfp}$	24	48	96	$t_{DCLK}$
	Pulse width	$t_{hsw}$	1	20	$t_{hbp} - 1$	$t_{DCLK}$
VSYNC	Period	$t_V$	485	525	576	$t$
	Display period	$t_{vd}$		480		$t_H$
	Back porch	$t_{vbp}$	3	27	31	$t_H$
	Front porch	$t_{vfp}$	2	18	66	$t_H$
	Pulse width	$t_{vsw}$	$1t_{DCLK}$	$1t_{DCLK}$	$6t_H$	

Note 1: The  $t_{hbp}$  time is adjustable by setting register HBLK; requirement of minimum blanking time and minimum front porch time must be satisfied.

Note 2: The  $t_{vbp}$  time is adjustable by setting register VBLK. UPS051 accepts both interlace and non-interlace vertical input timing.

Fig.1 UPS051 Input Horizontal Timing Chart






Fig.2 UPS051 Input Horizontal Data Sequence



A030JTN01.0 product Spec	Version	1.0
	Page	20/49

**Fig.3 UPS051 Input Vertical Timing Chart**





A030JTN01.0 product Spec	Version	1.0
	Page	21/49

## 5.2 YUV 320 8-bit serial mode (Refer to Fig.4 Fig.5 )


Parameter	Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK frequency	$1/t_{DCLK}$	23	24.5	25	MHz	
HSYNC	Period	$t_H$	710	780	877	$t_{DCLK}$
	Display period	$t_{hd}$		640		$t_{DCLK}$
	Back porch	$t_{hbp}$	20	40	127	$t_{DCLK}$
	Front porch	$t_{hfp}$	50	100	110	$t_{DCLK}$
	Pulse width	$t_{hsw}$	1	1	$t_{hbp} - 1$	$t_{DCLK}$
VSYNC	Period	$t_V$	485	525	576	$t$
	Display period	$t_{vd}$		480		$t_H$
	Back porch	$t_{vbp}$	3	27	31	$t_H$
	Front porch	$t_{vfp}$	2	18	66	$t_H$
	Pulse width	$t_{vsw}$	$1t_{DCLK}$	$1t_{DCLK}$	$6t_H$	

Note 1: The  $t_{hbp}$  time is adjustable by setting register HBLK; requirement of minimum blanking time and minimum front porch time must be satisfied.

Note 2: The  $t_{vbp}$  time is adjustable by setting register VBLK.


A030JTN01.0 product Spec	Version	1.0
	Page	22/49

**Fig.4 YUV 320 8-bit serial Input Horizontal Timing Chart**



A030JTN01.0 product Spec	Version	1.0
	Page	23/49

Fig.5 YUV 320 8-bit serial Input Vertical Timing Chart





A030JTN01.0 product Spec	Version	1.0
	Page	24/49

### 5.3 YUV 320 to RGB conversion

$$R_{2n-1} = 1.164 * (Y_{2n-1} - 16) + 1.596 * (C_{rn} - 128)$$

$$R_{2n} = 1.164 * (Y_{2n} - 16) + 1.596 * (C_{rn} - 128)$$

$$G_{2n-1} = 1.164 * (Y_{2n-1} - 16) - 0.813 * (C_{rn} - 128) - 0.391 * (C_{bn} - 128)$$


$$G_{2n} = 1.164 * (Y_{2n} - 16) - 0.813 * (C_{rn} - 128) - 0.391 * (C_{bn} - 128)$$

$$B_{2n-1} = 1.164 * (Y_{2n-1} - 16) + 2.017 * (C_{bn} - 128)$$

$$B_{2n} = 1.164 * (Y_{2n} - 16) + 2.017 * (C_{bn} - 128)$$


Where Y : 16~235      Cr : 16~240      Cb : 16~240

## 6. Serial control interface AC characteristic



Item	Symbol	Min	Typical	Max	Unit
CS input setup Time	$t_{S0}$	50	-	-	ns
Serial data input setup Time	$t_{S1}$	50	-	--	ns
CS input hold Time	$t_{H0}$	50	-	-	ns
Serial data input hold Time	$t_{H1}$	50	-	-	ns
SCL pulse low width	$t_{W1L}$	50	-	-	ns
SCL pulse high width	$t_{W1H}$	50	-	-	ns
CS pulse high width	$t_{W2}$	400	-	-	ns

### 6.1 Timing chart




1. Each serial command consists of 16 bits of data which is loaded one bit a time at the rising edge of serial clock SCL.
2. Command loading operation starts from the falling edge of CS and is completed at the next rising edge of CS.
3. The serial control block is operational after power on reset, but commands are established by the VSYNC signal. If command is transferred multiple times for the same register, the last command before the VSYNC signal is valid.
4. If less than 16 bits of SCL are input while CS is low, the transferred data is ignored.
5. If 16 bits or more of SCL are input while CS is low, the previous 16 bits of transferred data after the falling edge of CS pulse are valid data.
6. Serial block operates with the SCL clock.
7. Serial data can be accepted in the standby (power save) mode.

## 6.2 The configuration of serial data at SDA terminal is at below

MSB															LSB
A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0
Address	R/W	Address										DATA			

R/W: Establishes the Read mode when set to '1', and the Write mode when set to '0'.

### Write Mode:





## 6.3 Register table

No.	Register address							Register data							LSB							
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0						
R0	0	0	0	0	0	0	0	0	Y_CbCr (0)	x	x	x	x	x	x	x						
R3	0	0	0	0	0	0	1	1	Brightness (40h)													
R4	0	0	0	0	0	1	0	0	x	SEL (000)			x	x	VDIR (1)	HDIR (1)						
R5	0	0	0	0	0	1	0	1	x	GRB (1)	PFM_DUTY (011)			SHDB2 (1)	SHDB1 (1)	STB (0)						
R6	0	0	0	0	0	1	1	0	HBLK_EN (0)	LED_Current (00)		VBLK (1Bh)										
R7	0	0	0	0	0	1	1	1	HBLK(28h)													
R8	0	0	0	0	1	0	0	0	BL_DRV(00)		DRV_FREQ (00)		x	x	x	x						
R12	0	0	0	0	1	1	0	0	x	x	x	CbCr(0)	x	Vdpol(1)	Hdpol(1)	DCLKpol(0)						
R13	0	0	0	0	1	1	0	1	CONTRAST_RGB(40h)													
R14	0	0	0	0	1	1	1	0	x	SUB_CONTRAST_R(40h)												
R15	0	0	0	0	1	1	1	1	x	SUB_BRIGHTNESS_R(40h)												
R16	0	0	0	1	0	0	0	0	x	SUB_CONTRAST_B(40h)												
R17	0	0	0	1	0	0	0	1	x	SUB_BRIGHTNESS_B(40h)												
R21	0	0	0	1	0	1	0	1	LED_ON_CYCLE(0111)				LED_ON_RATIO(1111)									
R27	0	0	0	1	1	0	1	1	VCOM_SE L(0)	VCOMH(3Ch)												
R28	0	0	0	1	1	1	0	0	x	VCOML(47h)												

Note: 1. "x" => please set to '0'.



A030JTN01.0 product Spec	Version	1.0
	Page	28/49

#### 6.4 Register description

R0:

No.	Register address							MSB Register data							LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0
R0	0	0	0	0	0	0	0	0	Y_CbCr(0)	x	x	x	x	x	x	x

Y\_CbCr: Y & CbCr exchange position (only valid for 8-bit input YUV)

	CbCr(R12[4])='0' (Default)	CbCr(R12[4])='1'
Y_CbCr='0' (Default)	Cb1   Y1   Cr1   Y2   Cb2   Y3   Cr2   Y4	Cr1   Y1   Cb1   Y2   Cr2   Y3   Cb2   Y4
Y_CbCr='1'	Y1   Cb1   Y2   Cr1   Y3   Cb2   Y4   Cr2	Y1   Cr1   Y2   Cb1   Y3   Cr2   Y4   Cb2

R3:

No.	Register address							MSB Register data							LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0
R3	0	0	0	0	0	0	1	1	Brightness (40h)							

BRIGHTNESS: RGB bright level setting, setting accuracy: 1 step / bit

D7 ~ D0	Brightness gain
00h	Dark (-64)
40h(Default)	Center (0) (Default)
FFh	Bright (+191)



A030JTN01.0 product Spec	Version	1.0
	Page	29/49

R4:

No.	Register address							Register data							LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	
R4	0	0	0	0	0	1	0	0	x	SEL(000)			x	x	VDIR(1)	HDIR(1)

HDIR: Horizontal scan direction setting

HDIR	Function
0	Right to left scan
1	Left to right scan (Default)

VDIR: Vertical scan direction setting

VDIR	Function
0	Down to up scan
1	Up to down scan (Default)

SEL: Input data timing format selection

SEL			INPUT TIMING FORMAT
D6	D5	D4	
0	0	0	UPS051 (Default)
0	1	0	YUV 320 8-bit
0	1	1	YUV 320 16-bit
1	0	X	YUV 640 16-bit
1	1	X	YUV 720 16-bit



A030JTN01.0 product Spec	Version	1.0
	Page	30/49

R5:

No	Register address							Register data							LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0
R5	0	0	0	0	0	1	0	1	x	GRB(1)	PFM_DUTY(011)	SHDB2(1)	SHDB1(1)	STB(0)		

STB: Standby (Power saving) mode setting

STB	Function
0	Standby mode (Default)
1	Normal operation

SHDB1: Shut down for back light power converter

SHDB1	Function
0	The back light power converter is off
1	The back light power converter is controlled by power on/off sequence (Default)

SHDB2: Shut down for VGH/VGL charge pump

SHDB2	Function
0	VGH/VGL charge pump is always off
1	VGH/VGL charge pump is controlled by power on/off sequence (Default)

PFM\_DUTY: PFM duty cycle selection for back light power converter

PFM_DUTY			Function
D5	D4	D3	PFM duty cycle
0	0	0	93%
0	0	1	95%
0	1	0	65%
0	1	1	70%(Default)
1	0	0	75%
1	0	1	80%
1	1	0	85%
1	1	1	90%

GRB: Register reset setting

GRB	Function
0	Reset all registers to default value
1	Normal operation (Default)

When this command is sent to driver ic,it will be executed immediately


**R6 & R7:**

No	Register address							MSB Register data							LSB			
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0		
R6	0	0	0	0	0	1	1	0	HBLK_EN(0)	LED_Current(00)							VBLK(1Bh)	
R7	0	0	0	0	0	1	1	1	HBLK(28h)									

HBLK\_EN & HBLK: Horizontal blanking setting

HBLK_EN	HBLK(D7~D0)	HBLK	Unit	Remark	
x	14h	20	DCLK(*)	UPS051	
x	28h	40(Default)			
x	FFh	255			
0	-	40(fixed)	DCLK(*)	YUV320, YUV640, YUV720	
1	14h ~ FFh	20 ~ 127			

\*The frequency of DCLK is different under different input timing.



LED\_CURRENT: adjust LED current

DC-DC feedback voltage

D6	D5	Feedback Threshold voltage
0	0	0.6V(20mA) (default)
0	1	0.75V(25mA)
1	0	0.45V(15mA)
1	1	0.3V(10mA)



A030JTN01.0 product Spec	Version	1.0
	Page	32/49

R8:

No.	Register address								Register data								LSB
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0	
R8	0	0	0	0	1	0	0	0	BL_DRV(00)		DRV_FREQ(00)	x	x	x	x		

DRV\_FREQ: DRV signal frequency setting

DRV_FREQ		DRV signal frequency							
D5	D4								
0	0	DCLK / 64 (Default)							
0	1	DCLK / 64 / 2							
1	0	DCLK / 64 / 3							
1	1	DCLK / 64 / 4							

BL\_DRV: Backlight driving capability setting

D7	D6	BL_DRV capability
0	0	Normal capability (Default)
0	1	2 times the Normal capability
1	0	4 times the Normal capability
1	1	8 times the Normal capability

R12:

No.	Register address								Register data								LSB
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0	
R12	0	0	0	0	1	1	0	0	x	x	x	CbCr(0)	x	Vdpol(1)	Hdpol(1)	DCLKpol(0)	

DCLKpol: DCLK polarity selection

DCLKpol	Function
0	Positive polarity (Default)
1	Negative polarity


HDpol: HSYNC polarity selection

HDpol	Function
0	Positive polarity
1	Negative polarity (Default)


VDpol: VSYNC polarity selection

VDpol	Function
0	Positive polarity
1	Negative polarity (Default)


HDpol=1, VDpol=1, DCLKpol=0



HDpol=0, VDpol=0, DCLKpol=1



CbCr: Cb & Cr exchange position, (Please refer to the table of R0( Y\_CbCr) for detail description)





A030JTN01.0 product Spec	Version	1.0
	Page	34/49

### R13:

No.	Register address								Register data								LSB
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0	
R13	0	0	0	0	1	1	0	1	CONTRAST_RGB(40h)								

CONTRAST\_RGB: RGB contrast level setting, the gain changes (1/64) / bit

D7 ~ D0		Contrast gain
00h		0
40h		1(Default)
FFh		3.984

### R14~R17:

No.	Register address								Register data								LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0		
R14	0	0	0	0	1	1	1	0	x	SUB-CONTRAST_R(40h)								
R16	0	0	0	1	0	0	0	0	X	SUB-CONTRAST_B(40h)								

SUB-CONTRAST: R/B sub-contrast level setting, the gain changes (1/256) / bit

D6 ~ D0		Brightness gain
00h		0.75
40h		1(Default)
7Fh		1.246

No.	Register address								Register data								LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0		
R15	0	0	0	0	1	1		1	x	SUB-BRIGHTNESS_R(40h)								
R17	0	0	0	1	0	0	0	1	X	SUB-BRIGHTNESS_B(40h)								

SUB-BRIGHTNESS: R/B sub-bright level setting, setting accuracy : 1 step / bit

D6 ~ D0		Brightness gain
00h		Dark (-64)
40h		Center (0)(Default)
7Fh		Bright (+63)



A030JTN01.0 product Spec	Version	1.0
	Page	35/49

R21:


No.	Register address								Register data							
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0
R21	0	0	0	1	0	1	0	1	LED_ON_CYCLE (0111)							

LED\_ON\_RATIO: Set the active ratio of enable signal, and we can use it to adjust brightness of the LEDs.

LED ON RATIO				Value
D3	D2	D1	D0	
0	0	0	0	1/16
0	0	0	1	2/16
0	0	1	0	3/16
0	0	1	1	4/16
0	1	0	0	5/16
0	1	0	1	6/16
0	1	1	0	7/16
0	1	1	1	8/16
1	0	0	0	9/16
1	0	0	1	10/16
1	0	1	0	11/16
1	0	1	1	12/16
1	1	0	0	13/16
1	1	0	1	14/16
1	1	1	0	15/16
1	1	1	1	16/16(Default)

LED\_ON\_CYCLE : Set the cycle of enable signal , and we can use it to adjust brightness of the LEDs.

LED_ON_CYCLE				Value
D7	D6	D5	D4	
0	0	0	0	1
0	0	0	1	2
0	0	1	0	3
0	0	1	1	4
0	1	0	0	5
0	1	0	1	6
0	1	1	0	7
0	1	1	1	8(Default)
1	0	0	0	9
1	0	0	1	10
1	0	1	0	11
1	0	1	1	12
1	1	0	0	13
1	1	0	1	14
1	1	1	0	15
1	1	1	1	16



**16 \* LED\_ON\_CYCLE = LED\_ON\_CYCLE \* (LED\_ON\_RATIO \* 16) + LED\_ON\_CYCLE \* (16 - LED\_ON\_RATIO \* 16)**

<b>(Cycle)</b>	<b>(Enable)</b>	<b>(Disable)</b>	Unit : HS
----------------	-----------------	------------------	-----------

for example:

LED\_ON\_RATIO is “1001”, and LED\_ON\_CYCLE is “0111”, then:

Cycle =  $16 * 8 = 128$ (HSYNC)

$$\text{Enable} = 8 * ((10/16) * 16) = 80(\text{HSYNC})$$

$$\text{Disable} = 8 * (16 - (10/16) * 16) = 48(\text{HSYNC}) \quad \rightarrow 62.5\% \text{ on}$$

Unit : HS YNC

R27

R27[7]-VCOMH\_SEL=0 (for LOW VCOMH)

R27[6:0]-VCOMH:VCOMH level adjustment(1 step:20mv)

VCOMH level	(Unit:V)
00h	1.5v
...	step:20mV
3Ch(Default)	2.7(Default)
...	...
7Bh	3.96V
7Ch	3.97V
7Dh	3.98V
7Eh	4.00V
7Fh	4.02V



A030JTN01.0 product Spec	Version	1.0
	Page	37/49

R27[7]-VCOMH\_SEL=1 (for High VCOMH)

VCOMH level	(Unit:V)
00h	2.68v
...	step:20mV
7Bh	5.12V
7Ch	5.14V
7Dh	5.16V
7Eh	5.18V
7Fh	5.2V

R28

No.	Register address								Register data								LSB	
	A6	R/W	A5	A4	A3	A2	A1	A0	D7	D6	D5	D4	D3	D2	D1	D0		
R22	0	0	0	1	1	1	0	0	x								VCOML(47h)	

R28[6:0]-VCOML:VCOML level adjustment(1 step:20mv)

VCOMH level	(Unit:V)
00h	-0.1V
01h	-0.12V
02h	-0.14V
03h	-0.15V
04h	-0.16V
...	step:20mV
47h	-1.5V(Default)
...	...
7Fh	-2V

A030JTN01.0 product Spec	Version	1.0
	Page	38/49


### C. Optical specification (Note 1, Note 2, Note 3)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Response time		$\theta = 0^\circ$	-	10 25	40 50	ms ms	Note 4
	Rise Tr						
Contrast ratio	Fall Tf						
	CR	At optimized viewing angle	400	700	-		Note 5
Viewing angle	Top $\varphi_T$	$CR \geq 10$	40	50	-	deg.	Note 6
	Bottom $\varphi_B$		50	60	-		
	Left $\varphi_L$		50	60	-		
	Right $\varphi_R$		50	60	-		
Brightness *	$Y_I$	$\theta = 0^\circ$	360	50	-	cd/m <sup>2</sup>	Note 7,8
Luminance Uniformity			70	75		%	Note 9
Color Chromaticity	x	$\theta = 0^\circ$	0.273	0.313	0.353		
	y	$\theta = 0^\circ$	0.288	0.328	0.368		
	Rx	$\theta = 0^\circ$	0.537	0.577	0.617		
	Ry	$\theta = 0^\circ$	0.300	0.340	0.380		
	Gx	$\theta = 0^\circ$	0.305	0.345	0.385		
	Gy	$\theta = 0^\circ$	0.505	0.545	0.585		
	Bx	$\theta = 0^\circ$	0.113	0.153	0.193		
	By	$\theta = 0^\circ$	0.087	0.127	0.167		

Note 1. Ambient temperature =25°C.

Note 2. To be measured in the dark room.

Note 3. To be measured on the center area of panel with a field angle of 1° by Topcon luminance meter BM-5A, after 10 minutes operation.




A030JTN01.0 product Spec	Version	1.0
	Page	39/49

Note 4. Definition of response time:

The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time) and from "white" to "black"(rising time), respectively.

The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.




Note 5. Definition of contrast ratio:

Contrast ratio is calculated with the following for

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

Note 6. Definition of viewing angle:


Refer to figure as below.



Note 7. Measured at the center area of the panel in gray level 255.


A030JTN01.0 product Spec	Version	1.0
	Page	40/49

### Note 8. Color Filter Arrangement



### Note 9. Definition of luminance uniformity

$$\text{Luminance Uniformity} = \frac{\text{Min. Brightness of nine point}}{\text{Max. Brightness of nine point}}$$



A030JTN01.0 product Spec	Version	1.0
	Page	41/49

## D. Reliability test items


No.	Test items	Conditions	Remark
1	High temperature storage	Ta= 70°C 240Hrs	Note 1
2	Low temperature storage	Ta= -25°C 240Hrs	
3	High temperature operation	Ta= 60°C 240Hrs	
4	Low temperature operation	Ta= 0°C 240Hrs	
5	High temperature and high humidity	Ta= 60°C . 90% RH 240Hrs	Operation
6	Heat shock	-25°C ~60°C/50 cycle 2Hrs/cycle	Non-operation
7	Electrostatic discharge	Air-mode : +/- 8kV Contact-mode : +/- 4kV	Note.2, Note 3
8	Vibration	Frequency range : 10~55Hz Stroke : 1.5mm Sweep : 10~55Hz~10Hz 2 hours for each direction of X,Y,Z (6 hours for total)	Non-operation JIS C7021, A-10 condition A
9	Mechanical shock	100G . 6ms, ±X,±Y,±Z 3 times for each direction	Non-operation JIS C7021, A-7 condition C
10	Vibration (with carton)	Random vibration: 0.015G <sup>2</sup> /Hz from 5~200Hz -6dB/Octave from 200~500Hz	IEC 68-34
11	Drop (with carton)	Height: 60cm 1 corner, 3 edges, 6 surfaces	

Note 1. (for test item 1 to 6) Ta: Ambient temperature

Note 2. (for test item 1 to 6) Test method: check with recovery time 2hrs in the laboratory environment

Note 3. Judged by the on/off testing results of AUO's standard w/o functional fail.


Note 4. ESD Testing Flow as the below



A030JTN01.0 product Spec	Version	1.0
	Page	42/49

Note 5. ESD testing method.

1. Ambient: 24~26°C, 56~65%RH
2. Instruments: NoisekenESS-2000,
3. Operation System: "CX40FL-B" and adapter "A030JN01 V0"
4. Test Mode: Operating mode, test pattern: colorbar+8Gray scale
5. Test Method:
  - a. Contact Discharge:, 150pF(330Ω) 1sec, 5 points, 10 times/point
  - b. Air Discharge:, 150pF(330Ω) 1sec, 5 points, 10 times/point
6. Test point:




7. The metal casing is connected to power supply ground (0V) at four corners.
8. All register commands are repeating transfer.

A030JTN01.0 product Spec	Version	1.0
	Page	43/49


## E. Packing Design

### 1. Packing form



A030JTN01.0 product Spec	Version	1.0
	Page	44/49

## F. Outline dimension



A030JTN01.0 product Spec	Version	1.0
	Page	45/49

## G. Application note

### 1. Input Data Timing

In UPS051 input format, the conversion of image data to display dots is controlled by the user.

For UPS051 timing, the module accept one dot video data at the rising edge of DCLK, and display them one dot by one dot. Therefore the input data timing is different according to different panel resolutions and scan directions. Refer to the AC Timing of UPS051 part, you can use the typ. value for a typical case.

Because of delta color filter arrangement, the RGB data sequence for even and odd lines are different based on scan direction. For the RGB sequence, see Fig. 11.




Fig. 11 UPS051 Input RGB sequence

For the color filter arrangement, see Fig. 12.





Fig. 12 Color filter arrangement

## 2. Application circuit

## 2.1 With external LED driver circuit




Note1: Use external LED driver must set R5[1](SHDB1)= '0'.

### 3. Power on/off sequence

The register setting of standby mode disabling / enabling is used to control the build-in power on / off sequence.


#### 3.1 Power on (Standby Disabling)

After VDD power on, VSYNC/HSYNC/DCLK/DATA can be input, and serial control interface is also operational. The LCD driver is in default standby mode after VDD power-on, and setting register STB to '1' to disable the standby mode is required for normal operation. When the standby mode is disabled, a build-in power on sequence is started.



### 3.2 Power off (Standby Enabling)

When the register STB is set to '0' to enable standby mode, a build-in power off sequence is started.





A030JTN01.0 product Spec	Version	1.0
	Page	49/49

#### 4. Recommended power on/off serial command settings

##### a. Recommended Power On Register Setting with external LED driver

Number	Command(Binary)
1	00000101 00110100
	Delay 3ms
2	00000101 01110100
3	10010101 00000000
4	00011011 10111001
5	00011100 01001011
6	10011010 00000000
7	00000101 01110101

##### b. Recommended Power Off Register Setting

Number	Command(Binary)
1	00000101 01110000

Note: The recommended power on/ power off serial command setting needed to be applied into system