

ALO15B50

180 Watts


Total Power: 180 Watts
Input Voltage: 48V
of Outputs: Single

Special Features

- High efficiency (96% Typical)
- Industry standard package
8th Brick
0.90" x 2.30" x 0.38"
- High capacitive load limit on
start-up
- Output Enable Pin
- Undervoltage lockout
- Over Temperature Protection
- Meets Basic Insulation
- EU directive 2002/95/EC
compliant for RoHS

Safety

UL, cUL 60950
TUV EN60950



Rev. 04.02.08
ALO15B50
1 of 2

Electrical Specifications

Input	
Input range	36V to 55V
Efficiency	96%@ 12V (typical)
Over Voltage Protection	60V typical
Input UVLO	35 to 36V
Output	
Output current	0A to 15 max (180W output power)
Line regulation	-25% / +15% Vo, nom
Load regulation	5% Vo (typical)
Noise/ripple ¹	90mV (typical)
Over current limit	115% IO,MAX typical (autorecovery)
Over temperature protection	125°C average PCB temperature (autorecovery)
Switching frequency	200kHz
Control	
Enable	Positive and negative logic options
Isolation Voltage	
Input to Output	1500Vdc max

Environmental Specifications

Operating ambient temperature range	-40°C to +85°C ambient
Storage temperature	-55°C to +125°C
MTBF	>1 million hours



Ordering Information

Input Voltage	Output Voltage	Output Current	Efficiency ²	Model Number
36 - 55V	12V	15A	96% Typ	ALO15B50(N)-(6)(L)
Options:				
Enable Function	"N" = negative logic enable without "N" = positive logic enable (default)			
Pin Length Option	"-6" = 3.7mm (nominal) Standard pin length is 5mm nominal			
RoHS Version	"L" = RoHS Compliant (RoHS 6) without "L" = RoHS Compliant with lead (Pb) in solder exemption (RoHS 5)			

Pin Assignments


Single Output

1. +Vin
2. Enable
3. -Vin
4. -Vout
5. +Vout

Notes:

1. 20 MHz bandwidth. External 10 μ F tant. capacitor in parallel with 1 μ F ceramic capacitor placed across the output and secondary return ground.
2. Efficiency measurements are typical values taken at 48V input, 12V output, full load and $T_A = 25^\circ\text{C}$.
3. All specifications are typical at nominal line, full load and $T_A = 25^\circ\text{C}$ unless otherwise noted.
4. All specifications subject to change without notice.
5. Mechanical drawings are for reference only. Dimensions are in inches [millimeters]. Pin placement tolerance ± 0.005 [0.127]. Mechanical Tolerance ± 0.02 [0.5]. Pin diameter, $\varnothing = 0.06$ " for Pin 4 (-Vout) and Pin 5 (+Vout), the rest of the pins are $\varnothing = 0.04$ ".
6. Technical Reference Notes should be consulted for detailed information when available.
7. Warranty 1yr.

Mechanical Drawing



Americas

5810 Van Allen Way
Carlsbad, CA 92008
USA
Telephone: +1 (760) 930 4600
Facsimile: +1 (760) 930 0698

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
Telephone: +44 (0) 1384 842 211
Facsimile: +44 (0) 1384 843 355

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
Telephone: +852 2176 3333
Facsimile: +852 2176 3888

For global contact, visit:

www.powerconversion.com

techsupport.embeddedpower@emerson.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Emerson Network Power.

The global leader in enabling business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power**
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2008 Emerson Electric Co.