

AMERICAS

5810 Van Allen Way
 Carlsbad, CA 92008
 Telephone: 760-930-4600
 Facsimile: 760-930-0698

EUROPE

Astec House, Waterfront Business Park
 Merry Hill, Dudley
 West Midlands, DY5 1LX, UK
 Telephone: 44 (1384) 842-211
 Facsimile: 44 (1384) 843-355

ASIA

Units 2111-2116, Level 21
 Tower 1, Metroplaza
 223, Hing Fong Road
 Fwai Fong, New Territories
 Hong Kong
 Telephone: 852-2437-9662
 Facsimile: 852-2402-4426




Ordering Information

Input Voltage	Output Voltage	Output Current	Efficiency	Model Number
36V to 75V	5.0V	25A	91% Typ	ALQ25A48
36V to 75V	3.3V	35A	90% Typ	ALQ35F48
36V to 75V	2.5V	40A	89% Typ	ALQ40G48
36V to 75V	1.8V	40A	87% Typ	ALQ40Y48
36V to 75V	1.5V	40A	85% Typ	ALQ40M48
36V to 75V	1.2V	40A	84% Typ	ALQ40K48

NOTES: "N" = Negative logic enable (without "N" = Positive logic enable)

Pin Assignments



- J1: -Vin
- J2: ENABLE
- J3: +Vin
- J4: -Vo
- J5: -SENSE
- J6: TRIM
- J7: +SENSE
- J8: +Vo

Notes:

Nominal values apply with sense pins connected to +Vout and Ground Return with other control pins unconnected.

Specifications subject to change without