



N-Channel MOSFET

AO6424A (KO6424A)

■ Features

- $V_{DS} (V) = 30V$
- $I_D = 6.5 A$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 35m\Omega$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 48m\Omega$ ($V_{GS} = 4.5V$)

■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current	$T_A = 25^\circ C$	I_D	6.5	A
	$T_A = 70^\circ C$		5	
Pulsed Drain Current		I_{DM}	27	W
Power Dissipation	$T_A = 25^\circ C$	P_D	2.5	
	$T_A = 70^\circ C$		1.5	
Thermal Resistance.Junction- to-Ambient	$t \leq 10s$	R_{thJA}	50	$^\circ C/W$
	Steady-State		85	
Thermal Resistance.Junction- to-Lead		R_{thJL}	30	$^\circ C$
Junction Temperature		T_J	150	
Storage Temperature Range		T_{stg}	-55 to 150	

N-Channel MOSFET

AO6424A (KO6424A)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =250 μA, V _{GS} =0V	30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =30V, V _{GS} =0V			1	μA
		V _{DS} =30V, V _{GS} =0V, T _J =55°C			5	
Gate-Body Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250 μA	1.2		2.4	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =10V, I _D =5A			35	mΩ
		V _{GS} =10V, I _D =5A, T _J =125°C			53	
		V _{GS} =4.5V, I _D =4A			48	
Forward Transconductance	g _{FS}	V _{DS} =5V, I _D =5A		8		S
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =15V, f=1MHz		270		pF
Output Capacitance	C _{oss}			50		
Reverse Transfer Capacitance	C _{rss}			35		
Gate Resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1MHz	1.4		4.2	Ω
Total Gate Charge (10V)	Q _g	V _{GS} =10V, V _{DS} =15V, I _D =5A		6.3	12	nC
Total Gate Charge (4.5V)				3.2	8	
Gate Source Charge	Q _{gs}			0.65		
Gate Drain Charge	Q _{gd}			1.75		
Turn-On DelayTime	t _{d(on)}			3		
Turn-On Rise Time	t _r	V _{GS} =10V, V _{DS} =15V, R _L =3 Ω, R _G =3 Ω		2.5		ns
Turn-Off DelayTime	t _{d(off)}			17.5		
Turn-Off Fall Time	t _f			2.5		
Body Diode Reverse Recovery Time	t _{rr}	I _F = 5A, di/dt= 100A/μs		10		nC
Body Diode Reverse Recovery Charge	Q _{rr}			2.3		
Maximum Body-Diode Continuous Current	I _S				3	A
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V			1	V

* The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

■ Marking

Marking	4T**
---------	------

N-Channel MOSFET

AO6424A (KO6424A)

■ Typical Characteristics




Figure 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

N-Channel MOSFET

AO6424A (KO6424A)

■ Typical Characteristics

