



AO6700
**N-Channel Enhancement Mode Field Effect Transistor
with Schottky Diode**
General Description

The AO6700 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. A Schottky diode is provided to facilitate the implementation of a bidirectional blocking switch, or for DC-DC conversion applications. Standard Product AO6700 is Pb-free (meets ROHS & Sony 259 specifications). AO6700L is a Green Product ordering option. AO6700 and AO6700L are electrically identical.

Features
 $V_{DS} (V) = 20V$
 $I_D = 4.1A (V_{GS} = 4.5V)$
 $R_{DS(ON)} < 50m\Omega (V_{GS} = 4.5V)$
 $R_{DS(ON)} < 65m\Omega (V_{GS} = 2.5V)$
 $R_{DS(ON)} < 95m\Omega (V_{GS} = 1.8V)$
SCHOTTKY
 $V_{DS} (V) = 20V, I_F = 1A, V_F < 0.5V @ 0.5A$
**TSOP6
Top View**

Absolute Maximum Ratings $T_A = 25^\circ C$ unless otherwise noted

Parameter	Symbol	MOSFET	Schottky	Units
Drain-Source Voltage	V_{DS}	20		V
Gate-Source Voltage	V_{GS}	± 8		V
Continuous Drain Current ^A	$T_A = 25^\circ C$	I_D	4.1	A
	$T_A = 70^\circ C$		3.3	
Pulsed Drain Current ^B	I_{DM}	10		
Schottky reverse voltage	V_{KA}		20	V
Continuous Forward Current ^A	$T_A = 25^\circ C$	I_F	1.5	A
	$T_A = 70^\circ C$		1	
Pulsed Forward Current ^B	I_{FM}		10	
Power Dissipation	$T_A = 25^\circ C$	P_D	1.39	W
	$T_A = 70^\circ C$		0.89	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	-55 to 150	$^\circ C$

Parameter: Thermal Characteristics MOSFET		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	t ≤ 10s	R _{θJA}	70	90	°C/W
Maximum Junction-to-Ambient ^A	Steady-State		102	130	
Maximum Junction-to-Lead ^C	Steady-State	R _{θJL}	51	80	
Thermal Characteristics Schottky					
Maximum Junction-to-Ambient ^A	t ≤ 10s	R _{θJA}	129	160	°C/W
Maximum Junction-to-Ambient ^A	Steady-State		158	200	
Maximum Junction-to-Lead ^C	Steady-State	R _{θJL}	52	80	

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV _{DSS}	Drain-Source Breakdown Voltage	I _D =250μA, V _{GS} =0V	20			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =16V, V _{GS} =0V T _J =55°C			1 5	μA
I _{GSS}	Gate-Body leakage current	V _{DS} =0V, V _{GS} =±8V			100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} I _D =250μA	0.4	0.6	1	V
I _{D(ON)}	On state drain current	V _{GS} =4.5V, V _{DS} =5V	10			A
R _{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =4.5V, I _D =4.1A T _J =125°C		41.6	50	mΩ
		V _{GS} =2.5V, I _D =3.6A		54	65	mΩ
		V _{GS} =1.8V, I _D =3A		74	95	mΩ
g _{FS}	Forward Transconductance	V _{DS} =5V, I _D =4.1A		10.5		S
V _{SD}	Diode Forward Voltage	I _S =1A, V _{GS} =0V		0.8	1	V
I _S	Maximum Body-Diode Continuous Current				1.8	A
DYNAMIC PARAMETERS						
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =10V, f=1MHz		449	550	pF
C _{oss}	Output Capacitance			74		pF
C _{rss}	Reverse Transfer Capacitance			51.6		pF
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, f=1MHz		4.9	6	Ω
SWITCHING PARAMETERS						
Q _g	Total Gate Charge	V _{GS} =4.5V, V _{DS} =10V, I _D =4.1A		5.9	7.2	nC
Q _{gs}	Gate Source Charge			0.36		nC
Q _{gd}	Gate Drain Charge			1.3		nC
t _{D(on)}	Turn-On DelayTime	V _{GS} =5V, V _{DS} =10V, R _L =2.35Ω, R _{GEN} =0Ω		4.5		ns
t _r	Turn-On Rise Time			6		ns
t _{D(off)}	Turn-Off DelayTime			32.7		ns
t _f	Turn-Off Fall Time			7.1		ns
t _{rr}	Body Diode Reverse Recovery Time	I _F =4.1A, dI/dt=100A/μs		13	16	ns
Q _{rr}	Body Diode Reverse Recovery Charge	I _F =4.1A, dI/dt=100A/μs		3.3		nC
SCHOTTKY PARAMETERS						
V _F	Forward Voltage Drop	I _F =0.5A		0.39	0.5	V
I _{rm}	Maximum reverse leakage current	V _R =16V V _R =16V, T _J =125°C			0.02 20	mA
C _T	Junction Capacitance	V _R =10V		34		pF
t _{rr}	Schottky Reverse Recovery Time	I _F =1A, dI/dt=100A/μs		5.2	10	ns
Q _{rr}	Schottky Reverse Recovery Charge	I _F =1A, dI/dt=100A/μs		0.8		nC

A: The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t_{θJA} ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The R_{θJA} is the sum of the thermal impedance from junction to lead R_{θJL} and lead to ambient.







D: The static characteristics in Figures 1 to 6 are obtained using 80 μs pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

Rev 2 : Sept 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

MOSFET TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



MOSFET TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

