



BUTTON AUTOMOTIVE RECTIFIER

AR2505 THRU AR258
ARS2505 THRU ARS258

VOLTAGE RANGE 50 to 600 Volts


CURRENT 25.0 Amperes

FEATURES

- Low Leakage
- Low forward voltage drop
- High current capability
- High forward surge current capacity

MECHANICAL DATA

- Case: transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Lead: Plated slug, solderable per MIL-STD-202 Emethod 208C
- Polarity: Color ring denotes cathode end
- Mounting Position: any
- Weight: 0.064 ounces, 1.82 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60HZ, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	AR2505 ARS2505	AR251 ARS251	AR252 ARS252	AR254 ARS254	AR256 ARS256	AR258 ARS258	UNIT
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	Volts
Maximum Average Forward Rectified Current, At Tc=110℃	I _O	25.0						Amps
Peak Forward Surge Current 3.3mS single half sine wave superimposed on Rated load (JEDEC method)	I _{FSM}	400						Amps
Maximum instantaneous Forward Voltage at 80A	V _F	1.1						Volts
Maximum DC Reverse Current at Rated TA=25℃ DC Blocking Voltage per element TA=100℃	I _R	5.0						UA
		250						
Typical Thermal Resistance	R _{θJC}	1.0						℃/W
Operating and Storage Temperature Range	T _J ,T _{STG}	(-65 to +175)						℃
Polarity and voltage demotion color band		Red	Yellow	Silver	Green	Green	Blue	

Notes:

1. Enough heatsink must be considered in application.




BUTTON AUTOMOTIVE RECTIFIER

AR2505 THRU AR258
ARS2505 THRU ARS258


VOLTAGE RANGE 50 to 600 Volts
CURRENT 25.0 Amperes

RATINGS AND CHARACTERISTIC CURVES AR2505 THRU AR258 ARS2505 THRU ARS258


F1G.1 TYPICAL FORWARD CURRENT
DERATING CURVE



F1G.2 MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT



F1G.3 TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS



F1G.4 FORWARD POWER DISSIPATION

