



MVSILICON

AU7850 USB HOST MP3/WMA DECODER

AU7850 Datasheet

USB Host MP3/WMA Decoder SOC

Rev0.2

DISCLAIMER

All information and data contained in this document are without any commitment, are not to be considered as an offer for conclusion of a contract, nor shall they be construed as to create any liability. Any new issue of this document invalidates previous issues. Product availability and delivery are exclusively subject to our respective order confirmation form; the same applies to orders based on development samples delivered. By this publication, Shanghai Mountain View Silicon Technology Co. Ltd. (“MVSILICON”) does not assume responsibility for patent infringements or other rights of third parties that may result from its use.

No part of this publication may be reproduced, photocopied, stored in a retrieval system, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of Shanghai Mountain View Silicon Technology Co. Ltd.

Shanghai Mountain View Silicon Technology Co. Ltd. assumes no responsibility for any errors contained herein.



Revision History

Data	Revision	Description
	V0.1	Initial
	V0.2	



Contents

Revision History	iii
Contents.....	iv
Figures	v
Tables.....	vi
1. Overview.....	1
1.1 Features	1
1.2 Chip Architecture	2
2. System Application	3
3. Pin Description	4
3.1 Pin Description	4
4. Package.....	5
4.1 Package Diagram.....	5
4.2 Package Dimension Parameter	6
5. Electrical Specification	7
5.1 Absolute Maximum Ratings (Note 1).....	7
5.2 Recommended Operating Conditions	7
5.3 Electrical Characteristics	7
5.4 Audio Performance	7
Contact Information.....	9



Figures

Figure 1 AU7850 Functional Block Diagram	2
Figure 2 MP3/WMA Audio System.....	3
Figure 3 Package Diagram (LQFP48-7x7mm / TOP View)	5
Figure 4 LQFP48-7x7mm Package Dimension Parameter.....	6



Tables

Table 1 Pin Description.....	4
Table 2 Absolute Maximum Ratings	7
Table 3 Recommended Operating Conditions.....	7
Table 4 Electrical Characteristics	7
Table 5 Audio Performance.....	7



1. Overview

A highly integrated SOC for MP3/WMA player, AU7850 integrates MCU, MP3/WMA decoder, USB Host controller, SD/MMC card controller, SAR-ADC, audio DAC, RTC, LCD driver and an IR decoder in a single chip. Compared with traditional flash-MP3 player, AU7850 offers low cost, low power consumption, flexible and more powerful host MP3/WMA player solution.

1.1 Features

- | Low power 0.18um CMOS technology
- | Enhanced 8051, up to 10 times faster than standard 8051
- | USB2.0 full-speed host controller
- | SD/MMC card controller
- | Support MPEG 1/2/2.5 layer2/3 decoding, data rate 32kbps ~ 320kbps, including VBR
- | Support WMA format, data rate 32kbps ~ 384kbps
- | Support 9 sampling frequency:
8kHz/11.025kHz/12kHz/16kHz/22.05kHz/24kHz/32kHz/44.1kHz/48kHz
- | Embedded sound equalizer
- | Support tag format ID3v1 and ID3v2.4
- | Support FAT16/FAT32 file system
- | Embedded 16-bit DAC
- | 1 channel AUX in
- | 1 channel FM in
- | 9 channel 12bit SARADC for peripheral controls
- | Embedded segment LCD driver, support 1/3 bias or 1/4 bias two types
- | Embedded low power RTC module
- | Support IR Remote control
- | GPIO for various purposes
- | Embedded LDO, convert 5V to 3.3V and 1.8V
- | Embedded Power-on-Reset
- | Embedded 32KB OTP for program code storage



1.2 Chip Architecture




Figure 1 AU7850 Functional Block Diagram

2. System Application

I MP3/WMA audio system




Figure 2 MP3/WMA Audio System



3. Pin Description

AU7850 is a CMOS device. Floating level on input signals causes unstable device operation and abnormal current consumption. Pull-up or Pull-down resistors should be used appropriately for input or bidirectional pins.

Notation	Description
I	Input
O	Output
I/O	Bidirectional
PWR	Power
GND	Ground

3.1 Pin Description

Table 1 Pin Description

Pin name	Pin #	Type	Description
USB interface pins			
USB_DP	14	I/O	USB Function D+ bus
USB_DM	13	I/O	USB Function D- bus
DAC interface pins			
DAC_R	41	AO	audio right channel output
DAC_L	42	AO	audio left channel output
DACVMID	40	AI	Internal voltage reference
DAC_AUX_R	43	AI	External AUX right channel in
DAC_AUX_L	44	AI	External AUX left channel in
GPIO/MCU IO pins			
GPIO_A[1:0]	37:36	I/O	GPIO PORT, bank A
GPIO_A[2]	9	I/O	GPIO PORT, bank A
GPIO_A[3]	6	I/O	GPIO PORT, bank A
GPIO_A[4]	8	I/O	GPIO PORT, bank A
GPIO_A[5]	7	I/O	GPIO PORT, bank A
GPIO_A[7:6]	46:45	I/O	GPIO PORT, bank A
GPIO_B[5:0]	33:28	I/O	GPIO PORT, bank B
GPIO_B[6]	1	I/O	GPIO PORT, bank B
GPIO_B[7]	3	I/O	GPIO PORT, bank B
GPIO_C[0]	5	I/O	GPIO PORT, bank C
GPIO_C[1]	34	I/O	GPIO PORT, bank C
GPIO_C[2]	4	I/O	GPIO PORT, bank C
GPIO_C[3]	48	I	GPIO PORT, bank C
GPIO_D[7:0]	27:20	I/O	GPIO PORT, bank D
CLK pins			
XIN	18	I	12MHz Crystal oscillator input for PLL



XOUT	19	O	12MHz Crystal oscillator output for PLL
RTC_XIN	11	I	32.768KHz Crystal oscillator input for RTC
RTC_XOUT	10	O	32.768KHz Crystal oscillator output for RTC
Power/Ground pins			
VDD33	2 35	PWR	power for digital
DVSS	47	GND	ground for digital
LDO180	17	PWR	LDO 1.8V out
LDO330	15	PWR	LDO 3.3V out
LDO5V	16	PWR	LDO 5V power in
DACVDD33	38	PWR	power for DAC
DACVSS	39	GND	ground for DAC
RTC_PWR	12	PWR	Power for RTC

4. Package

4.1 Package Diagram




Figure 3 Package Diagram (LQFP48-7x7mm / TOP View)



4.2 Package Dimension Parameter




Figure 4 LQFP48-7x7mm Package Dimension Parameter

5. Electrical Specification

5.1 Absolute Maximum Ratings (Note 1)

Table 2 Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Power Supply Voltage (IO)	VCC_IO_AB	-0.5 to 4.6	V
Power Supply Voltage (Core)	VCC_CORE_AB	0 to 2	V
Storage Temperature	TEMP_STG	-65 to 150	C

5.2 Recommended Operating Conditions

Table 3 Recommended Operating Conditions

Parameter	Symbol	Min	Typ	Max	Unit
Power Supply Voltage (IO)	VCC_IO_OP	3	3.3	3.6	V
Power Supply Voltage (Core)	VCC_CORE_OP	1.62	1.8	1.98	V
Input Voltage	VIN	0		3.6	V
Input Voltage (GPIO_C3)	VIN	0		5.5	V
Operating Free Air Temperature	TEMP_OPR	-20		70	C

5.3 Electrical Characteristics

Table 4 Electrical Characteristics

Symbol	Parameter	Condition	Min	Typ	Max	Unit
V _{IH}	Input High Voltage		1.57		3.6	V
V _{IL}	Input Low Voltage		-0.3		1.2	V
V _{OH}	Output high voltage	@IOH=2mA	3.0			V
V _{OL}	Output low voltage	@IOL=2mA			0.3	V
I _L	Input leakage current		-10		10	uA
P _{PLAY}	Power consumption when playing	Playing mode		85		mW

5.4 Audio Performance

Table 5 Audio Performance

Characteristics	Min	Typ	Max	Unit
Frequency Response 40Hz ~ 20KHz		<=1		DB
THD+N(1KHz out = 800mv rms)		<0.3		%
S/N (1KHz out = 800mv rms)		> -65		DB
L/R Channel Difference		0		DB
L/R Channel Separation		-65		DB
Max Noise Out		<0.5		MV



Note:

1. “Absolute Maximum Ratings” are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the device should be operated at these limits.



Contact Information

Shanghai Mountain View Silicon Technology Co Ltd

Shanghai Headquarter:

Suite 403, Jinying Tower A, 1518 Minsheng Road, Pudong New Area,
Shanghai, P.R. China

Zip code: 200135

Tel: 86-21-68549851

Fax: 86-21-68549859

Shenzhen Sales & Technical Support Office:

Suite 6A Olympic Plaza, Shangbao Road, Futian District,
Shenzhen, Guangdong, P.R. China

Zip code: 518034

Tel: 86-755-83522955

Fax: 86-755-83522957

Email: support@mvsilicon.com

Website: <http://www.mvsilicon.com>