



APATL0000180

IPS Alpha Technology, Ltd.

Date: Aug.24,2007

For Messrs. KAOLUNG TAMURA ELECTRONICS CO., LTD.**CUSTOMER'S ACCEPTANCE SPECIFICATIONS****AX066B001F****CONTENTS**

No.	Item	Sheet No.	Page
-	COVER	IPS4PS 2601- AX066B001F-1	1-1/1
-	RECORD OF REVISION	IPS4PS 2602 - AX066B001F-1	2-1/1
-	DESCRIPTION	IPS4PS 2603- AX066B001F-1	3-1/1
1	ABSOLUTE MAXIMUM RATINGS	IPS4PS 2604- AX066B001F-1	4-1/1
2	INITIAL OPTICAL CHARACTERISTICS	IPS4PS 2605- AX066B001F-1	5-1/2~2/2
3	ELECTRICAL CHARACTERISTICS	IPS4PS 2606- AX066B001F-1	6-1/1
4	BLOCK DIAGRAM	IPS4PS 2607- AX066B001F-1	7-1/1
5	INTERFACE PIN ASSIGNMENT	IPS4PS 2608- AX066B001F-1	8-1/6~6/6
6	INTERFACE TIMING	IPS4PS 2609- AX066B001F-1	9-1/3~3/3
7	DIMENSIONAL OUTLINE	IPS4PS 2610- AX066B001F-1	10-1/2~2/2
8	DESIGNATION OF LOT MARK	IPS4PS 2611- AX066B001F-1	11-1/1
9	COSMETIC SPECIFICATIONS	IPS4PS 2612- AX066B001F-1	12-1/3~3/3
10	PRECAUTION	IPS4PS 2613- AX066B001F-1	13-1/3~3/3

Please return 1 copy with your signature on this page for approval.

Accepted by: _____

Proposed by: _____

Date: _____

IPS Alpha Technology,Ltd.	Sheet No.	IPSA4PS 2601 - AX066B001F - 1	Page	1-1/1
------------------------------	--------------	-------------------------------	------	-------

**RECORD OF REVISION**

Date	The upper section : Before revision The lower section : After revision		Summary
	Sheet No.	Page	



DESCRIPTION

The following specifications are applied to the following Super-TFT module.

Note : Inverter for back light unit is built in this module.

Product Name : AX066B001F

General Specifications

Effective Display Area	: (H)575.769×(V)323.712	(mm)
Number of Pixels	: (H)1,366×(V)768	(pixels)
Pixel Pitch	: (H)0.4215×(V)0.4215	(mm)
Color Pixel Arrangement	: R+G+B	Vertical Stripe
Display Mode	: Transmissive Mode	Normally Black Mode
Top Polarizer Type	: Anti-Glare	
Number of Colors	: 16,777,216	(colors)
Viewing Angle Range	: Super Wide Version	(Horizontal & Vertical : 170°, CR≥10)
Input Signal	: 1-channel LVDS (LVDS:Low Voltage Differential Signaling)	
Back Light	: 7pcs. of CCFL (Type:U-Shape)	
External Dimensions	: (H)626.0×(V)373.0×(t)47.5	(mm)
Weight	: 5,100g	typ.

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2603 - AX066B001F - 1	Page	3-1/1
----------------------------	------	-------------	-----------	------------------------------	------	-------

1. ABSOLUTE MAXIMUM RATINGS

1.1 Environmental Absolute Maximum Ratings

ITEM	Operating		Storage		Unit	Note
	Min.	Max.	Min.	Max.		
Temperature	0	50	-20	60	°C	1),5),6)
Humidity	2)		2)		%RH	1)
Vibration	—	4.9(0.5G)	—	14.7 (1.5G)	m/s ²	3)
Shock	—	29.4(3G)	—	294 (30G)	m/s ²	4)
Corrosive Gas	Not Acceptable		Not Acceptable		—	
Illumination at LCD Surface	—	50,000	—	50,000	lx	

- Note 1) Temperature and Humidity should be applied to the glass surface of a Super-TFT module, not to the system installed with a module.
The temperature at the center of rear surface should be less than 70°C on the condition of operating. The brightness of a CCFL tends to drop at low temperature. Besides, the life-time becomes shorter at low temperature.
- 2) $T_a \leq 40^\circ\text{C}$ ······Relative humidity should be less than 85%RH max. Dew is prohibited.
 $T_a > 40^\circ\text{C}$ ······Relative humidity should be lower than the moisture of the 85%RH at 40°C.
- 3) Frequency of the vibration is between 15Hz and 100Hz. (Remove the resonance point)
- 4) Pulse width of the shock is 10 ms.
- 5) Long operation under low temperature may cause some portion of display area to be reddish for several minutes after turning on the product.
However, it does not affect the characteristics and reliability of the product.

1.2 Electrical Absolute Maximum Ratings

(1) Super-TFT Module

V_{SS} = 0 V

ITEM	SYMBOL	Min.	Max.	Unit	Note
Power Supply Voltage	V _{DD}	0	13.2	V	
Input Voltage for logic	V _I	-0.3	3.6	V	1)
Electrostatic Durability	V _{ESD0}	±100		V	2),3)
	V _{EDS1}	±8		kV	2),4)

- Note 1) It is applied to pixel data signal and clock signal.
2) Discharge Coefficient : 200pF-250Ω, Environmental : 25°C-70%RH
3) It is applied to I/F connector pins.
4) It is applied to the surface of a metallic bezel and a LCD panel.

(2) Back-light Inverter

V_{SS} = 0 V

ITEM	SYMBOL	Min.	Max.	Unit	Note
Input Voltage	V _{in}	-1.0	28.0	V	
ON/OFF Control Input Voltage	ON/OFF	-1.0	5.5	V	
Brightness Control Voltage	BRT	-1.0	5.5	V	



2. INITIAL OPTICAL CHARACTERISTICS

The following optical characteristics are measured under stable conditions. It takes about 30 minutes to reach stable conditions. The measuring point is the center of display area unless otherwise noted.

The optical characteristics should be measured in a dark room or equivalent state.


Measuring equipment: CS-1000A, or equivalent

Ambient Temperature =25°C、VDD=12.0V、f V=60Hz、

Vin=24V、BRT=3.15V

ITEM		SYMBOL	CONDITION	Min.	Typ.	Max.	UNIT	NOTE
Contrast Ratio		CR	$\theta=0^{\circ}$ 1)	500	750	—	—	2)
Response Time	Rise	ton		—	9	20	ms	3)
	Fall	toff		—	7	20	ms	3)
Brightness of white		Bwh		350	450	—	cd/m ²	
Brightness uniformity		Buni		—	—	30	%	4)
Color Chromaticity (CIE)	Red	χ		0.62	0.65	0.68	—	[Gray scale =255]
		y		0.30	0.33	0.36		
	Green	χ		0.26	0.29	0.32		
		y		0.58	0.61	0.64		
	Blue	χ		0.12	0.15	0.18		
		y		0.04	0.07	0.10		
	White	χ		0.242	0.272	0.302		
		y		0.248	0.278	0.308		
Variation of Color Position (CIE)	Red	$\Delta \chi$	$\theta=+50^{\circ}$ $\varphi=0^{\circ}, 90^{\circ}$ $180^{\circ}, 270^{\circ}$ 1)	—	—	0.04	—	5) [Gray scale =255]
		Δy		—	—	0.04		
	Green	$\Delta \chi$		—	—	0.04		
		Δy		—	—	0.04		
	Blue	$\Delta \chi$		—	—	0.04		
		Δy		—	—	0.04		
	White	$\Delta \chi$		—	—	0.04		
		Δy		—	—	0.04		
Contrast Ratio at 85°		CR85°		10	—	—	—	Estimated Value


Note 1) Definition of Viewing Angle




2) Definition of Contrast Ratio (CR)

$$CR = \frac{(\text{Luminance at displaying WHITE})}{(\text{Luminance at displaying BLACK})}$$

3) Definition of Response Time



4) Definition of Brightness Uniformity



Display pattern is white (255 level). The brightness uniformity is defined as the following equation. Brightness at each point is measured, and average, maximum and minimum brightness is calculated.

$$B_{uni} = \frac{|B_{max \text{ or } B_{min}} - B_{ave}|}{B_{ave}} \times 100$$

where, B_{max} = Maximum brightness

B_{min} = Minimum brightness

$$B_{ave} = \text{Average brightness} = \frac{\sum_{k=1}^9 (B(k))}{9}$$

5) Variation of color position on CIE is defined as difference between colors at $\theta=0^\circ$ and at $\theta=50^\circ$ & $\phi=0^\circ, 90^\circ, 180^\circ, 270^\circ$.


3. ELECTRICAL CHARACTERISTICS

3.1 TFT-LCD Module

Ta=25°C, Vss=0V

ITEM	SYMBOL	Min.	Typ.	Max.	Unit	Note
Power Supply Voltage	V _{DD}	11.4	12.0	12.6	V	
Power Supply Current	I _{DD}	—	0.4	0.6	A	1),2)
Ripple Voltage of Power Supply	V _{DDR}	—	—	0.15	V	

Note 1) DC current at fv=60.0Hz, fCLK=82MHz, VDD=12.0V and Display pattern is Horizontal stripe.



- 2) Current fuse is built in a module. Current capacity of power supply for VDD should be larger than 4A, so that the fuse can be opened at the trouble of power supply.





3.2 Back Light

ITEM		Symbol	VALUE			Unit	Notes
			Min	Typ	Max		
Input Voltage		VBL	21.6	24.0	26.4	V	
Input Current		IBL	—	2.84	3.4	A	Vin=24.0V,BRT=3.15V 1)
ON/OFF Control Input Voltage	ON	ON/OFF	2.0	—	5.5	V	
	OFF		-0.3	—	0.8	V	
Brightness Control Input Voltage	Min. Brightness	BRT	—	0	—	V	
	Max. Brightness		3.0	3.15	3.3	V	
PWM Duty	Min. Brightness	On-Duty	20	—	—	%	Vin=24.0V,BRT=0V
	Max. Brightness		—	—	100	%	Vin=24.0V,BRT=3.15V
Output current		IL	5.0	6.0	7.0	mArms	Vin=24.0V,BRT=3.15V
Open Output Voltage		Vopen	1700	1800	1900	Vrms	
Output Frequency		fL	48	50	52	kHz	

1) This characteristics should be applied putting on the lamp about 30 minutes later with ambient temperature. (Ta=25 ± 2°C)

4. BLOCK DIAGRAM

(1) Super-TFT Module





5. INTERFACE PIN ASSIGNMENT

5.1 TFT-LCD MODULE

CN1 : HIROSE FX15S-41S-0.5SH

(Matching connector :HIROSE FX15S-41P-C)

Pin No.	Symbol	Description	Note
1	VDD	Power Supply (typ.+12V)	1)
2	VDD		
3	VDD		
4	VDD		
5	VDD		
6	VDD		
7	VSS	GND(0V)	2)
8	VSS		
9	VSS		
10	VSS		
11	VSS		
12	VSS		
13	Rx0-	Pixel Data	3)
14	Rx0+		
15	VSS	GND(0V)	2)
16	Rx1-	Pixel Data	3)
17	Rx1+		
18	VSS	GND(0V)	2)
19	Rx2-	Pixel Data	3)
20	Rx2+		
21	VSS	GND(0V)	2)
22	CLK-	Pixel Clock	3)
23	CLK+		
24	VSS	GND(0V)	2)
25	Rx3-	Pixel Clock	3)
26	Rx3+		
27	VSS	GND(0V)	2)
28	IC	Internally Conected , Keep Open	
29	IC	Internally Conected , Keep Open	
30	IC	Internally Conected , Keep Open	
31	IC	Internally Conected , Keep Open	
32	IC	Internally Conected , Keep Open	
33	IC	Internally Conected , Keep Open	
34	IC	Internally Conected , Keep Open	
35	IC	Internally Conected , Keep Open	
36	IC	Internally Conected , Keep Open	
37	IC	Internally Conected , Keep Open	
38	IC	Internally Conected , Keep Open	
39	IC	Internally Conected , Keep Open	
40	IC	Internally Conected , Keep Open	
41	IC	Internally Conected , Keep Open	

- Notes
- 1) All VDD pins shall be connected to +12.0V(Typ.).
 - 2) All VSS pins shall be grounded. Metal bezel is internally connected to VSS.
 - 3) Rx n+ and Rx n- (n=0,1,2,3) should be wired by twist-pairs or side-by-side FPC patterns, respectively.

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2608 - AX066B001F - 1	Page	8-1/6
----------------------------	------	-------------	-----------	------------------------------	------	-------

5.2 BACK-LIGHT UNIT

CN2 : JST S14B-PH-SM4-TB

(Matching connector : JST PHR-14)

Pin No.	SYMBOL	Description	Note
1	VIN	Power supply(Typ. 24.0V)	1)
2	VIN		
3	VIN		
4	VIN		
5	VIN		
6	VSS	GND(0V)	2)
7	VSS		
8	VSS		
9	VSS		
10	VSS		
11	NC	NC	
12	ON/OFF	High:Lamp ON, Low:Lamp OFF	3)
13	BRT	High : Max. Brightness , Low : Min. Brightness	4)
14	PWM_SEL	GND(0V)	

Notes 1) All VIN pins shall be connected to +24.0V(Typ.).

2) All VSS pins shall be grounded. Metal bezel is internally connected to VSS.

3) High level:2.2~5.5V, Low level:-0.3~0.8V

4) High level : 3.15V , Low level : 0V


CN3 : JST S10B-PH-SM4-TB

(Matching connector : JST PHR-10)

Pin No.	SYMBOL	Description	Note
1	NC		1)
2	NC		
3	NC		
4	NC		
5	NC		
6	NC		
7	NC		
8	NC		
9	NC		
10	NC		

Note 1) CN3 is not used.

5.3 BLOCK DIAGRAM OF INTERFACE



R0~R7 : Pixel R Data
G0~G7 : Pixel G Data
B0~B7 : Pixel B Data
HSYNC : Horizontal synchronization signal
VSYNC : Vertical synchronization signal
DTMG : Display timing signal

- Notes
- 1) The system must have the transmitter to drive the module.
 - 2) LVDS cable impedance shall be 50 ohms per signal line or about 100 ohms per twist-pair line when it is used differentially.



5.4 LVDS INTERFACE

	SIGNAL	TRANSMITTER THC63LVDM83A		INTERFACE CONNECTOR		RECEIVER THC63LVDF84A		TFT CONTROL INPUT
		PIN	INPUT	PC	TFT-LCD	PIN	OUTPUT	
24bit	R2	51	Tx IN0	TA OUT0+	Rx 0+	27	Rx OUT0	R2
	R3	52	Tx IN1			29	Rx OUT1	R3
	R4	54	Tx IN2			30	Rx OUT2	R4
	R5	55	Tx IN3			32	Rx OUT3	R5
	R6	56	Tx IN4	TA OUT0-	Rx 0-	33	Rx OUT4	R6
	R7	3	Tx IN6			35	Rx OUT6	R7
	G2	4	Tx IN7			37	Rx OUT7	G2
	G3	6	Tx IN8			38	Rx OUT8	G3
	G4	7	Tx IN9	TA OUT1+	Rx 1+	39	Rx OUT9	G4
	G5	11	Tx IN12			43	Rx OUT12	G5
	G6	12	Tx IN13			45	Rx OUT13	G6
	G7	14	Tx IN14			46	Rx OUT14	G7
	B2	15	Tx IN15	TA OUT1-	Rx 1-	47	Rx OUT15	B2
	B3	19	Tx IN18			51	Rx OUT18	B3
	B4	20	Tx IN19			53	Rx OUT19	B4
	B5	22	Tx IN20			54	Rx OUT20	B5
	B6	23	Tx IN21	TA OUT2+	Rx 2+	55	Rx OUT21	B6
	B7	24	Tx IN22			1	Rx OUT22	B7
	HSYNC	27	Tx IN24			3	Rx OUT24	HSYNC
	VSYNC	28	Tx IN25			5	Rx OUT25	VSYNC
	DTMG	30	Tx IN26	TA OUT2-	Rx 2-	6	Rx OUT26	DTMG
	R0	50	Tx IN27			7	Rx OUT27	R0
	R1	2	Tx IN5			34	Rx OUT5	R1
	G0	8	Tx IN10	TA OUT3+	Rx 3+	41	Rx OUT10	G0
	G1	10	Tx IN11			42	Rx OUT11	G1
	B0	16	Tx IN16			49	Rx OUT16	B0
	B1	18	Tx IN17			50	Rx OUT17	B1
	RSVD 1)	25	Tx IN23	TA OUT3-	Rx 3-	2	Rx OUT23	not connect
	DCLK	31	TxCLK IN			26	RxCLK OUT	DCLK
				TxCLK OUT+	RxCLK IN+			
				TxCLK OUT-	RxCLK IN-			

R0~R7 : Pixel R Data (7;MSB, 0;LSB)

G0~G7 : Pixel G Data (7;MSB, 0;LSB)

B0~B7 : Pixel B Data (7;MSB, 0;LSB)

HSYNC : Horizontal synchronization signal

VSYNC : Vertical synchronization signal


DTMG : Display timing signal

Notes 1) RSVD(reserved) pins on the transmitter shall be "H" or "L".

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2608 - AX066B001F - 1	Page	8-4/6
----------------------------	------	-------------	--------------	------------------------------	------	-------


5.5 CORRESPONDENCE BETWEEN INPUT DATA AND DISPLAY IMAGE

Display data of adjacent one pixel is latched during one cycle of DCLK.



pixel : R0~R7 :R data
G0~G7 :G data
B0~B7 :B data

1, 1	1, 2	1, 3	-----	1, 1366
2, 1	2, 2	2, 3	-----	2, 1366
3, 1	3, 2	3, 3	-----	3, 1366
⋮	⋮	⋮		⋮
768, 1	768, 2	768, 3	-----	768, 1366





5.6 RELATIONSHIP BETWEEN DISPLAY COLORS AND INPUT SIGNALS

Input Color		Red Data								Green Data								Blue Data							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
		MSBLSB								MSBLSB								MSBLSB							
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (255)	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(255)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Blue (255)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (1)	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (2)	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red (254)	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (255)	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (255)	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Green(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(254)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
	Green(255)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Green(255)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(254)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue(255)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Blue(255)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1


Notes 1) Definition of gray scale:

Color(n).....Number in parenthesis indicates gray scale level. Larger n corresponds to brighter level.

2) Data: 1:High, 0:Low

6. INTERFACE TIMING

6.1 LVDS RECEIVER TIMING



$$Rx0 = (Rx0+) - (Rx0-)$$

$$Rx1 = (Rx1+) - (Rx1-)$$


$$Rx2 = (Rx2+) - (Rx2-)$$

$$Rx3 = (Rx3+) - (Rx3-)$$

$$CLK = (CLK+) - (CLK-)$$


	Item	Symbol	Min.	Typ.	Max.	Unit
RCLK	Cycle Time	1/tCLK	65	82	85	MHz
Rx0 Rx1 Rx2 Rx3	0 data position	tRP0	1/7tCLK-0.41	1/7tCLK	1/7tCLK+0.41	ns
	1st data position	tRP1	-0.41	0	+0.41	
	2nd data position	tRP2	6/7tCLK-0.41	2/7tCLK	6/7tCLK+0.41	
	3rd data position	tRP3	5/7tCLK-0.41	3/7tCLK	5/7tCLK+0.41	
	4th data position	tRP4	4/7tCLK-0.41	4/7tCLK	4/7tCLK+0.41	
	5th data position	tRP5	3/7tCLK-0.41	5/7tCLK	3/7tCLK+0.41	
	6th data position	tRP6	2/7tCLK-0.41	6/7tCLK	2/7tCLK+0.41	

6.2 SYNCHRONIZATION SIGNAL TIMING



Item		Symbol	Min.	Typ.	Max.	Unit	Note
DE	Vertical Frequency	fV	57	60	63	Hz	
	Vertical Period	tV	773	784	1500	tH	
	Vertical Valid	tVd	768			tH	
	Horizontal Frequency	fH	46.5	46.9	48.5	kHz	
	Horizontal Period	tH	1400	1406	2000	tCLK	
	Horizontal Valid	tHd	1366			tCLK	

6.3 TIMING BETWEEN INTERFACE SIGNALS AND POWER SUPPLY



$$0 \leq T1 \leq 10$$

$$350 \leq T2$$

$$0 \leq T3$$

$$1 \leq T4$$

$$-100 \leq T5$$

$$-100 \leq T6$$

$$0 \leq T7$$


$$350 \leq T8$$

Unit : ms

Note 1) In all periods, the backlight ON/OFF signal voltage and the BRT signal voltage should be lower than the backlight power supply voltage.


7. DIMENSIONAL OUTLINE

(1) FRONT VIEW



Note 1)The dimension in a parenthesis is a reference value.
2)Unspecified tolerance to be ±0.8


(2)BACK VIEW



Note 1)The dimension in a parenthesis is a reference value.
2)Unspecified tolerance to be ±0.8

8. DESIGNATION OF LOT MARK

8.1 LOT MARK



Notes

1)

Year	Mark
2006	06
2007	07
2008	08

2)

Month	Mark	Month	Mark
1	01	7	07
2	02	8	08
3	03	9	09
4	04	10	10
5	05	11	11
6	06	12	12

3)

Week(Day)	Mark
1 ~ 7	1
8 ~ 14	2
15 ~ 21	3
22 ~ 28	4
29 ~ 31	5

4) It is the mark that was opened up by production person to take correspondence with production number.

8.2 Revision (REV.) control

REV. is the column for manufacturing convenience. A-Z except I and O may be written on this column.

8.3 Location of lot mark

Lot mark is printed on a label. The label is on the metallic bezel as shown in 7. External Dimensional. The style of character will be changed without notice.



9. COSMETIC SPECIFICATIONS

9.1 Condition for cosmetic inspection


(1) Viewing zone

- a) The figure shows the correspondence between eyes (of inspector) and TFT-LCD module.

$\theta \leq 45^\circ$: when non-operating inspection

$\theta \leq 5^\circ$: when operating inspection

- b) Inspection should be executed only from front side and only A-zone.
Cosmetic of B-zone and C-zone are ignore.
(refer to 9.2 Definition of zone)




(2) Environmental

- a) Temperature : 25 degrees

- b) Ambient light : about 700 lx and non-directive when operating inspection.
: about 1000 lx and non-directive when non-operating inspection.

- c) Back-light : when non-operating inspection, back-light should be off.

9.2 Definition of zone



- A-zone : Display area (pixel area)
- B-zone : Area between A-zone and C-zone
- C-zone : Metallic bezel area



9.3 COSMETIC SPECIFICATIONS

When displaying conditions are not stable (ex. at turn on or off), the following specifications are not applied.

	No.	ITEM			Max. acceptable number	Unit	Note
					A-zone		
Operating inspection	1	Dot defect	Sparkle mode	1-dot	2	pcs	1),2),4)
				2-dots	0	Units	1),2),5)
				3-dots	0		
				4-dots	0		
				Density	2	pcs/ ϕ 20mm	1),2),6)
				Total	2	pcs	1),2)
			Black mode	1-dot	7	pcs	1),3),4)
				2-dots	1	Units	1),3),5)
				3-dots	0		
				4-dots	0		
				Density	4	pcs/ ϕ 20mm	1),3),6)
				Total	7	pcs	1),3)
			Total	7	pcs	1)	
	2	Line defect			Serious one is not allowed.	—	—
	3	Uneven brightness					
	4	Stain inclusion <div>Line shape W : width (mm) L : length (mm)</div>	$W \leq 0.02$	L : Ignore	Ignore	pcs	7)
				$W \leq 0.04$	$L \leq 4.0$		
			$W \leq 0.08$		$L > 4.0$		
				$W \leq 0.08$	$L \leq 2.0$		
			$L > 2.0$		0		
			$W > 0.08$	—	(See dot shape)		
	5	Stain inclusion <div>Dot shape D : ave. dia. (mm)</div>	$D \leq 0.22$		Ignore	pcs	7)
			$D \leq 0.5$		8		
$D > 0.5$			0				
6	Scratch on polarizer <div>Line shape W : width (mm) L : length (mm)</div>	$W \leq 0.02$	L : Ignore	Ignore	pcs	8)	
		$W \leq 0.08$	$L \leq 20$	10			
			$L > 20$	0			
		$W > 0.08$	—	0			
7	Scratch on polarizer <div>Dot shape D : ave. dia. (mm)</div>	$D \leq 0.2$		Ignore	pcs	8)	
		$D \leq 0.6$		10			
		$D > 0.6$		0			



	No.	ITEM		Max. acceptable number A-Zone	Unit	Note
Non-operating inspection	8	Bubbles,peeling in polarizer [D: ave. dia.(mm)]	$D \leq 0.2$	Ignore	pcs	8)
			$D \leq 0.5$	10		
			$D > 0.5$	0		
	9	Wrinkles on polarizer		Serious one is not allowed.	—	—

- Note
- 1) Dot defect : defect area $> 1/2$ dot
 - 2) Sparkle mode : brightness of dot is more than 30% at black. (visible to eye)
 - 3) Black mode : brightness of dot is less than 70% at white. (visible to eye)
 - 4) 1 dot : defect dot is isolated, not attached to other defect dot.
 - 5) N dots : N defect dots are consecutive. (N means the number of defects dots)
 - 6) Density : number of defect dots inside 20mm ϕ .
 - 7) Those stains which can be wiped out easily are acceptable.
 - 8) Polarizer area inside of B-zone is not applied.
 - 9) No major (serious) defects when viewed in gray scale mode.

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2612 - AX066B001F - 1	Page	12-3/3
----------------------------	------	-------------	--------------	------------------------------	------	--------

10. PRECAUTION

Please pay attention to the followings when a Super-TFT module with a back-light unit is used, handled and mounted.

10.1 Precaution to handling and mounting

- (1) Applying strong force to a part of the module may cause partial deformation of frame or mold, and cause damage to the display.
- (2) The module should gently and firmly be held by both hands. Never hold by just one hand in order to avoid any internal damage. Never drop or hit the module.
- (3) The module should be installed with mounting holes of a module.
- (4) Uneven force such as twisted stress should not be applied to a module when a module is mounted on the cover case. The cover case must have sufficient strength so that external force can not be transmitted directly to a module.
- (5) It is recommended to leave a space between a module and a holding board of a module so that partial force is not applied to a module.




Fig.1 Cross sectional view of a monitor set

- (6) The edge of a cover case should be located inside more than 1mm from the edge of a module front frame.
- (7) A transparent protective plate should be added on the display area of a module in order to protect a polarizer and Super-TFT cell. The transparent protective plate should have sufficient strength so that the plate can not touch a module by external force.
- (8) Materials included acetic acid and choline should not be used for a cover case as well as other parts and boards near a module. Acetic acid attacks a polarizer. Choline attacks electric circuits due to electro-chemical reaction.
- (9) The polarizer on a TFT cell should carefully be handled due to its softness, and should not be touched, pushed or rubbed with glass, tweezers or anything harder than HB pencil lead. The surface of a polarizer should not be touched and rubbed with bare hand, greasy clothes or dusty clothes.
- (10) The surface of a polarizer should be gently wiped with absorbent cotton, chamois or other soft materials slightly contained petroleum benzene when the surface becomes dirty. Normal-hexane as cleaning chemicals is recommended in order to clean adhesives which fix front/rear polarizers on a Super-TFT cell. Other cleaning chemicals such as acetone, toluen and alcohol should not be used to clean adhesives because they cause chemical damage to a polarizer.
- (11) Saliva or water drops should be immediately wiped off. Otherwise, the portion of a polarizer may be deformed and its color may be faded.
- (12) The module should not be opened or modified. It may cause not to operate properly.

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2613 - AX066B001F - 1	Page	13-1/3
----------------------------	------	-------------	-----------	------------------------------	------	--------



- (13) Metallic bezel of a module should not be handled with bare hand or dirty gloves. Otherwise, color of a metallic frame may become dirty during its storage. It is recommended to use clean soft gloves and clean finger stalls when a module is handled at incoming inspection process and production (assembly) process.
- (14) Lamp(CCFL) cables should not be pulled and held.

10.2 Precaution to operation

- (1) The ambient temperature near the operated module should be satisfied with the absolute maximum ratings. Unless it meets the specifications, sufficient cooling system should be adopted to system.
- (2) The spike noise causes the mis-operation of a module. The level of spike noise should be as follows:
-200mV<=over- and under- shoot of VDD<= +200mV
VDD including over- and under- shoot should be satisfied with the absolute maximum ratings.
- (3) Optical response time, luminance and chromaticity depend on the temperature of a Super-TFT module. Response time and saturation time of CCFL luminance become longer at lower temperature operation.
- (4) Sudden temperature change may cause dew on and/or in the a module. Dew males damage to a polarizer and/or electrical contacting portion. Dew causes fading of displayed quality.
- (5) Fixed patterns displayed on a module for a long time may cause after-image. It will be recovered soon.
- (6) A module has high frequency circuits. Sufficient suppression to electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be effective to minimize the interference.
- (7) Noise may be heard when a back-light is operated. If necessary, sufficient suppression should be done by system manufacturers.
- (8) The module should not be connected or removed while a main system works.
- (9) Inserting or pulling I/F connectors causes any trouble when power supply and signal dates are on-state.I/F connectors should be inserted and pulled after power supply and signal dates are turned off.

10.3 Electrostatic discharge control

- (1) Since a module consists of a Super-TFT cell and electronic circuits with CMOS-ICs, which are very weak to electrostatic discharge, persons who are handling a module should be grounded through adequate methods such as a list band. I/F connector pins should not be touched directly with bare hands.
- (2) Protection film for a polarizer on a module should be slowly peeled off so that the electrostatic charge can be minimized.

10.4 Precaution to strong light exposure

- (1) A module should not be exposed under strong light. Otherwise, characteristics of a polarizer and color filter in a module may be degraded.

10.5 Precaution to storage

When modules for replacement are stored for a long time, following precautions should be taken care of:

- (1) Modules should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light during storage. Modules should be stored at 0 to 35-C at normal humidity (60%RH or less).
- (2) The surface of polarizers should not come in contact with any other object. It is recommended that modules should be stored in the Hitachi's shipping box.

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2613 - AX066B001F - 1	Page	13-2/3
----------------------------	------	-------------	-----------	------------------------------	------	--------



10.6 Precaution to handling protection film

- (1) The protection film for polarizers should be peeled off slowly and carefully by persons who are electrically grounded with adequate methods such as a list band. Besides, ionized air should be blown over during peeling action. Dusts on a polarizer should be blown off by an ionized nitrogen gun and so on.
- (2) The protection film should be peeling off without rubbing it to the polarizer. Because, if the film is rubbed together with the polarizer, since the film is attached to the polarizer with a small amount of adhesive, the adhesive may remain on a polarizer.
- (3) The module with protection film should be stored on the conditions explained in 10.5 (1). However, in case that the storage time is too long, adhesive may remain on a polarizer even after a protection film is peeled off. Besides, in case that a module is stored at higher temperature and/or higher humidity, adhesive may remain on a polarizer. The remained adhesive may cause non-uniformity of display image.
- (4) The adhesive can be removed easily with Normal-Hexane. The remained adhesive or its vestige on the polarizer should be wiped off with absorbent cotton or other soft materials such as chamois slightly contained Normal-Hexane.

10.7 Safety

- (1) Since a Super-TFT cell and lamps are made of glass, handling to the broken module should be taken care sufficiently in order not to be injured. Hands touched liquid crystal from a broken cell should be washed sufficiently.
- (2) The module should not be taken apart during operation so that back-light drives by high voltage.

10.8 Environmental protection

- (1) The Super-TFT module contains cold cathode fluorescent lamps. Please follow local ordinance or regulations for its disposal.
- (2) Flexible printed circuits and printed circuits board used in a module contain small amount of lead. Please follow local ordinance or regulations for its disposal.

10.9 Use restrictions and limitations

- (1) This product is not authorized for use in life support devices or systems, military applications or other applications which pose a significant risk of personal injury.
- (2) In no event shall Hitachi, Ltd., be liable for any incidental, indirect or consequential damages in connection with the installation or use of this product, even if informed of the possibility thereof in advance. These limitations apply to all causes of action in the aggregate, including without limitation breach of contract, breach of warranty, negligence, strict liability, misrepresentation and other torts.

10.10 Others

- (1) Electrical components which may not affect electrical performance are subjective to change without notice because of their availability.

IPS Alpha Technology, Ltd.	Date	Aug.24,2007	Sheet No.	IPS4PS 2613 - AX066B001F - 1	Page	13-3/3
----------------------------	------	-------------	-----------	------------------------------	------	--------