


$V_{RRM}$  = 650 V

$I_F (T_C=150^\circ\text{C})$  = 8 A

$Q_c$  = 24 nC

TO-220-isolated



## Features

- Ceramic package provides 2.5kV isolation
- Extremely low reverse current
- No reverse recovery current
- Temperature independent switching
- Positive temperature coefficient on  $V_F$
- Excellent surge current capability
- Low capacitive charge

## Benefits

- Electrically isolated package
- Essentially no switching losses
- System efficiency improvement over Si diodes
- Increased power density
- Enabling higher switching frequency
- Reduction of heat sink requirements
- System cost savings due to smaller magnetics
- Reduced EMI

## Applications

- Switch mode power supplies (SMPS)
- Uninterruptible power supplies
- Motor drivers
- Power factor correction

## Package Pin Definitions

- Pin1- Cathode
- Pin2- Anode

## Package Parameters

Part Number	Marking	Package
B2D08065KS	B2D08065KS	TO-220-isolated



**Maximum Ratings (T<sub>c</sub>=25°C unless otherwise specified)**

Symbol	Parameter	Test conditions	Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage		650	V
V <sub>RSM</sub>	Non-repetitive peak reverse voltage		650	V
I <sub>F</sub>	Continuous forward current	T <sub>c</sub> =25°C T <sub>c</sub> =150°C	26 8	A
I <sub>FSM</sub>	Non-Repetitive forward surge current	T <sub>c</sub> =25°C , t <sub>p</sub> =10ms, Half Sine Wave	64	A
∫i <sup>2</sup> dt	i <sup>2</sup> t value	T <sub>c</sub> =25°C , t <sub>p</sub> =10ms	20.48	A <sup>2</sup> S
P <sub>tot</sub>	Power dissipation	T <sub>c</sub> =25°C T <sub>c</sub> =110°C	86 37	W
T <sub>j</sub>	Operating junction temperature		-55~175	°C
T <sub>stg</sub>	Storage temperature		-55~175	°C
	TO-220 mounting torque	M3 Screw	0.7	Nm

**Thermal Characteristics**

Symbol	Parameter	Value			Unit
		Min.	Typ.	Max.	
R <sub>th(jc)</sub>	Thermal resistance from junction to case		1.73		K/W

### Electrical Characteristics

#### Static Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
$V_{DC}$	DC blocking voltage	$T_j=25^\circ C$	650			V
$V_F$	Diode forward voltage	$I_F=8A T_j=25^\circ C$ $I_F=8A T_j=175^\circ C$		1.28 1.54		V
$I_R$	Reverse current	$V_R=650V T_j=25^\circ C$ $V_R=650V T_j=175^\circ C$		1 10		$\mu A$

#### AC Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
$Q_c$	Total capacitive charge	$V_R=400V T_j=25^\circ C$ $Q_c = \int_0^{V_R} C(V)dV$		24		nC
C	Total capacitance	$V_R=1V f=1MHz$ $V_R=300V f=1MHz$ $V_R=600V f=1MHz$		365 41.1 40.7		pF
$E_c$	Capacitance stored energy	$V_R=400V$		6		$\mu J$

### Typical Performance




Figure 1. Typical forward characteristics




Figure 2. Typical reverse current as function of reverse voltage




Figure 3. Diode forward current as function of temperature, D=duty cycle




Figure 4. Typical capacitance as function of reverse voltage,  $C=f(V_R)$ ;  $T_j=25^\circ\text{C}$ ;  $f=1\text{ MHz}$

### Typical Performance




Figure 5. Typical reverse charge as function of reverse voltage




Figure 6. Power dissipation as function of case temperature




Figure 7. Capacitance stored energy






Figure 8. Max. transient thermal impedance,  $Z_{thjc} = f(t)$ , parameter:  $D = t/T$

## Package Dimensions



SYMBOL	mm		
	MIN	NOM	MAX
A	4.40	4.50	4.60
B	0.61	0.75	0.88
C	0.46	0.58	0.70
C2	1.21	1.265	1.32
C3	2.40	2.56	2.72
D	8.60	9.15	9.70
E	9.80	10.1	10.4
F	6.55	6.75	6.95
G	5.08 BSC		
H	28.0	28.9	29.8
L1		3.75	
L2	1.14		1.70
L3	2.65	2.80	2.95
V1		45°	
φ P			3.88

## Revision History

Document Version	Date of Release	Description of changes
Rev. 0.1	2021-01-26	Release of the preliminary datasheet.

**BASiC Semiconductor Ltd.**  
**Shenzhen, China**  
**© 2021 BASiC Semiconductor Ltd.**  
**All Rights Reserved.**

### Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest BASiC Semiconductor Office

### Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, BASiC semiconductor Ltd. hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.