

Applications

- Refrigerators
- Deep freezers

Features


- Thermistor in molded plastic case
- PVC-insulated connecting cable (white), $T_{\max} = 105\text{ }^{\circ}\text{C}$
- Conductor cross section: $2 \times 0,34\text{ mm}^2$
- Construction based on DIN EN 60 730-1/VDE protection class 2

Options

Alternative resistance ratings,
rated temperatures,
resistance tolerance and cable lengths
available on request

Delivery mode

Bulk



Dimensions
in mm

TNT0350-Q

Climatic category (IEC 60068-1)		40/80/56	
Max. power at 25 °C	P_{25}	350	mW
Resistance tolerance	$\Delta R_N/R_N$	± 2 %	
Rated temperature	T_N	0	°C
B value tolerance	$\Delta B/B$	± 1,5 %	
Dissipation factor (in air)	δ_{th}	approx. 10	mW/K
Thermal time constant (in water)	τ_a	approx. 35	s
Insulation resistance	R_{is}	> 1000	MΩ

R_{25}	R_0	No. of R/T characteristic	$B_{25/100}$	Ordering code
Ω	Ω		K	
5000	16330	2003	3980	B57020M2502A017

Reliability data

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature $T: 80\text{ }^{\circ}\text{C}$ $t: 1000\text{ h}$	< 2 %	No visible damage
Storage in coldness		Storage at lower category temperature $T: -40\text{ }^{\circ}\text{C}$ $t: 1000\text{ h}$	< 2 %	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: $40\text{ }^{\circ}\text{C}$ Relative humidity of air: 93 % Duration: 56 days	< 2 %	No visible damage
Rapid temperature cycling	IEC 60068-2-14	Lower test temperature: $-40\text{ }^{\circ}\text{C}$ Upper test temperature: $80\text{ }^{\circ}\text{C}$ Time to change from lower to upper temperature: < 30 s; Number of cycles: 1000 Medium: air	< 2 %	No visible damage
Storage in water		Temperature of water: $30\text{ }^{\circ}\text{C}$ $t: 4000\text{ h}$ Applied voltage with drop resistor 10 k Ω : 10 V_{dc} switched between on ($t_{on} = 30\text{ min}$) and off ($t_{off} = 30\text{ min}$)	< 2 %	No visible damage
Temperature cycling test		Lower test temperature: $-30\text{ }^{\circ}\text{C}$ Upper test temperature: $10\text{ }^{\circ}\text{C}$ Test frequency < 15 min under wetness and frozen water Number of cycles: 50000 Medium: air	< 2 %	No visible damage
Voltage proof test		3750 V; 1 min		No flash-over
Insulation test		The sensors are placed in a vessel containing metallic balls of 1 mm diameter (with total immersed head). The applied voltage is 500 V_{dc} .		Above 1000 M Ω

Herausgegeben von EPCOS AG**Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND****☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG**Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY****☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.