



Military-Fasteners.com

BACR15BA3D6C SOLID RIVET SPEC

Description:

Fastener Length: 3/8"

BACR15BA3D6C Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Rivet, Solid
NSN:	5320-01-456-6261
NIIN:	014566261
FSC:	Rivets / 5320
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

See page 2 for technical characteristics

BACR15BA3D6C Specifications

Countersink Angle:	100.0 Degrees Nominal
Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Major Diameter:	0.184 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Shank Diameter:	0.0938 Inches Minimum And 0.0963 Inches Maximum
Shank Style:	Straight
Specification/standard Data:	81205-bacr15ba Professional/industrial Association Standard
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall
Surface Treatment:	Chromate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid-rivets/BACR15BA3D6C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.