



NPN General Purpose Amplifier



Features:

- For general AF applications
- Complementary PNP type available BC807
- High collector current
- High current gain
- Low collector-emitter saturation voltage

Pin Configuration:

1. Base
2. Emitter
3. Collector

Applications:

- General purpose medium power amplifier
- Switching requiring collector currents up to 1.2mA

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector - Base Voltage	V_{CBO}	50	V
Collector - Emitter Voltage	V_{CEO}	45	
Emitter - Base Voltage	V_{ebo}	5	
Collector Current Continuous	I_C	500	mA
Collector Dissipation	P_C	300	mW
Junction and Storage Temperature	T_j, T_{stg}	-65 to +150	°C

NPN General Purpose Amplifier


Electrical Characteristics ($T_{amb} = 25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector - Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=10\mu\text{A}, I_E=0$	50			V
Collector - Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	45			
Emitter - Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=10\mu\text{A}, I_C=0$	5			
Collector Cut-off Current	I_{CBO}	$V_{CB}=25\text{V}, I_E=0$			-0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{CE}=4\text{V}, I_E=0$			-0.1	
DC Current Gain	BC817 BC817-16 BC817-25 BC817-40	h_{FE}	$V_{CE}=1\text{V}, I_C=-100\text{mA}$	100 100 160 250	600 250 400 600	
DC Current Gain	BC817 BC817-16 BC817-25 BC817-40	h_{FE}	$V_{CE}=1\text{V}, I_C=-300\text{mA}$	40 60 100 170		
Collector - Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=500\text{mA}, I_B=50\text{mA}$			0.7	V
Base - Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=500\text{mA}, I_B=50\text{mA}$			1.2	
Output Capacitance	C_{obo}	$V_{CB}=10\text{V}, f=1\text{MHz}$		6		pF
Transition Frequency	f_T	$V_{CE}=5\text{V}, I_C=50\text{mA}$ $f=100\text{MHz}$		170		MHz

Typical Characteristics: $T_{amb}=25^{\circ}\text{C}$ unless otherwise specified


Ratings & Characteristic Curves

Total power dissipation $P_{tot} = f(T_S)$



Transition frequency $f_T = f(I_C)$

$V_{CE} = 5\text{V}$




NPN General Purpose Amplifier

Typical Characteristics: $T_{amb} = 25^\circ\text{C}$ unless otherwise specified

Ratings & Characteristic Curves


Permissible pulse load

$$P_{totmax} / P_{totDC} = f(t_p)$$




Collector cutoff current $I_{CBO} = f(T_A)$

$$V_{CBO} = 25\text{V}$$




Base-emitter saturation voltage

$$I_C = f(V_{BEsat}), h_{FE} = 10$$



Collector-emitter saturation voltage


$$I_C = f(V_{CEsat}), h_{FE} = 10$$



NPN General Purpose Amplifier


DC current gain $h_{FE} = f(I_C)$

$V_{CE} = 1V$



Package Outline


Plastic surface mounted package



Dimensions	Min.	Max.
A	1.8	2.2
B	1.15	1.35
C	1 Typical	
D	0.15	0.35
E	0.25	0.4
G	1.2	1.4
H	0.02	0.1
J	0.1 Typical	
K	2.1	2.3

Dimensions : Millimetres

Soldering Footprint



Dimensions : Millimetres

Part Number Table

Description	Part Number
Transistor, NPN, 0.5A, 45V, SOT23	BC817
	BC817-16
	BC817-25
	BC817-40

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.