

特征 FEATURES

- .大电流承受能力.High current capability
- .高压利用能力.High voltage available
- .玻璃被钝化的压模结构.Glass passivated die construction
- .高浪涌承受能力.High surge current capability
- .35A 工作在表面温度是 125℃,无热损耗的情况下.

35Ampere Operation At $T_L=125^{\circ}\text{C}$ With No Thermal Runaway

机械数据 MECHANICAL DATA

.BD351N 代表阴性的

BD351-N N-Lead ,P-Case




.BD351P 代表阳性的

BD351-P P-Lead ,N-Case



BLOCK DIODE



Dimension in millimeters

极限值和电参数 $T_A=25^{\circ}\text{C}$ 除非另有规定. 单相,正半弦波,60HZ,阻抗或电感负载.为电容装载,减少电流的 20%

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C Ambient temp. Unless otherwise specified.Single phase, half sine wave, 60HZ,resistive or inductive load.

For capacitive load, derate current by 20%

	SYMBOL	BD351N	BD351P	UNITS
最大峰值反向电压 Maximum Current Peak Reverse Voltage	VRRM	100	100	Volts
最大反向有效电压 Maximum RMS Voltage	VRMS	70	70	Volts
最大直流阻断电压 Maximum DC Blocking Voltage	VDC	100	100	Volts
最大正向平均整流电流 $T_L=100^{\circ}\text{C}$ Maximum Average Forward Rectified Current	I(AV)	35		Amps
正向峰值浪涌电流 Peak Forward Surge Current 8.3ms Single Sine-wave on Rated Load (JEDEC Method)	IFSM	350		Amps
35A 直流电时最大正向瞬间电压降 Maximum Instantaneous Forward Voltage Drop at 35A DC	VF	1.1		Volts
最大反向漏电流 Maximum DC Reverse Current $T_A=25^{\circ}\text{C}$ at Rated DC Blocking Voltage $T_A=100^{\circ}\text{C}$	IR	5 500		μA
典型热阻抗 Typical thermal resistance	R θ JA	1.0		$^{\circ}\text{C/W}$
工作温度存储温度 Operating AND Storage Temperature Range	TSTG/ TJ	-55 to +150		$^{\circ}\text{C}$

RATING AND CHARACTERISTIC CURVES BD351N THRU BD351P

FIG. 1 –最大正向平均电流降额

FIG. 1 –MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG. 2 –最大非重复正向浪涌电流

FIG. 2 –MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 –反向特性曲线(典型)

FIG. 3 –TYPICAL REVERSE CHARACTERISTICS




FIG. 4 –正向特性曲线(典型)

FIG. 4 –TYPICAL FORWARD CHARACTERISTICS

