

# BLF6G10-200RN; BLF6G10LS-200RN

Power LDMOS transistor

Rev. 3 — 1 September 2015

**AMPLEON**  
Product data sheet

## 1. Product profile

### 1.1 General description

200 W LDMOS power transistor for base station applications at frequencies from 700 MHz to 1000 MHz.

**Table 1. Typical performance**

*Typical RF performance at  $T_{case} = 25\text{ °C}$  in a class-AB production test circuit.*

| Mode of operation | f<br>(MHz) | V <sub>DS</sub><br>(V) | P <sub>L(AV)</sub><br>(W) | G <sub>p</sub><br>(dB) | η <sub>D</sub><br>(%) | ACPR<br>(dBc)      |
|-------------------|------------|------------------------|---------------------------|------------------------|-----------------------|--------------------|
| 2-carrier W-CDMA  | 869 to 894 | 28                     | 40                        | 20                     | 28.5                  | -39 <sup>[1]</sup> |

[1] Test signal: 3GPP; test model 1; 64 DPCH; PAR = 7.5 dB at 0.01 % probability on CCDF per carrier; carrier spacing 5 MHz.

#### CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Therefore care should be taken during transport and handling.

### 1.2 Features





- Typical 2-carrier W-CDMA performance at frequencies of 869 MHz and 894 MHz, a supply voltage of 28 V and an I<sub>DQ</sub> of 1400 mA:
  - ◆ Average output power = 40 W
  - ◆ Power gain = 20 dB
  - ◆ Efficiency = 28.5 %
  - ◆ ACPR = -39 dBc
- Easy power control
- Integrated ESD protection
- Enhanced ruggedness
- High efficiency
- Excellent thermal stability
- Designed for broadband operation (700 MHz to 1000 MHz)
- Internally matched for ease of use
- Compliant to Directive 2002/95/EC, regarding restriction of hazardous substances (RoHS)

### 1.3 Applications

- RF power amplifiers for GSM, GSM EDGE, W-CDMA and CDMA base stations and multicarrier applications in the 700 MHz to 1000 MHz frequency range.

## 2. Pinning information

Table 2. Pinning

| Pin                       | Description                | Simplified outline  | Graphic symbol   |
|---------------------------|----------------------------|---|--|
| BLF6G10-200RN (SOT502A)   |                            |   |  |
| 1                         | drain                      |  |   |
| 2                         | gate                       |   |  |
| 3                         | source <a href="#">[1]</a> |   |  |
| BLF6G10LS-200RN (SOT502B) |                            |   |  |
| 1                         | drain                      |  |  |
| 2                         | gate                       |   |  |
| 3                         | source <a href="#">[1]</a> |   |  |

[1] Connected to flange.

## 3. Ordering information

Table 3. Ordering information

| Type number     | Package |   |         |
|-----------------|---------|---|---------|
|                 | Name    | Description   | Version |
| BLF6G10-200RN   | -       | flanged LDMOST ceramic package; 2 mounting holes; 2 leads | SOT502A |
| BLF6G10LS-200RN | -       | earless flanged LDMOST ceramic package; 2 leads           | SOT502B |

## 4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol    | Parameter            | Conditions | Min  | Max  | Unit |
|-----------|----------------------|------------|------|------|------|
| $V_{DS}$  | drain-source voltage |            | -    | 65   | V    |
| $V_{GS}$  | gate-source voltage  |            | -0.5 | +13  | V    |
| $I_D$     | drain current        |            | -    | 49   | A    |
| $T_{stg}$ | storage temperature  |            | -65  | +150 | °C   |
| $T_j$     | junction temperature |            | -    | 225  | °C   |

## 5. Thermal characteristics

**Table 5. Thermal characteristics**

| Symbol           | Parameter                                | Conditions  | Type            | Typ  | Unit |
|------------------|--|---|-----------------|------|------|
| $R_{th(j-case)}$ | thermal resistance from junction to case | $T_{case} = 80\text{ °C};$<br>$P_L = 40\text{ W}$ | BLF6G10-200RN   | 0.50 | K/W  |
|                  |  |   | BLF6G10LS-200RN | 0.35 | K/W  |

## 6. Characteristics

**Table 6. Characteristics**

$T_j = 25\text{ °C}$  unless otherwise specified.

| Symbol        | Parameter                        | Conditions   | Min   | Typ  | Max   | Unit          |
|---------------|----------------------------------|--|-------|------|-------|---------------|
| $V_{(BR)DSS}$ | drain-source breakdown voltage   | $V_{GS} = 0\text{ V}; I_D = 0.9\text{ mA}$                         | 65    | -    | -     | V             |
| $V_{GS(th)}$  | gate-source threshold voltage    | $V_{DS} = 10\text{ V}; I_D = 270\text{ mA}$                        | 1.4   | 2.0  | 2.4   | V             |
| $V_{GSq}$     | gate-source quiescent voltage    | $V_{DS} = 28\text{ V};$<br>$I_D = 1620\text{ mA}$                  | 1.7   | 2.2  | 2.7   | V             |
| $I_{DSS}$     | drain leakage current            | $V_{GS} = 0\text{ V}; V_{DS} = 28\text{ V}$                        | -     | -    | 4.2   | $\mu\text{A}$ |
| $I_{DSX}$     | drain cut-off current            | $V_{GS} = V_{GS(th)} + 3.75\text{ V};$<br>$V_{DS} = 10\text{ V}$   | 40    | 48   | -     | A             |
| $I_{GSS}$     | gate leakage current             | $V_{GS} = 11\text{ V}; V_{DS} = 0\text{ V}$                        | -     | -    | 420   | nA            |
| $g_{fs}$      | forward transconductance         | $V_{DS} = 10\text{ V}; I_D = 9.45\text{ A}$                        | 11    | 18   | 26    | S             |
| $R_{DS(on)}$  | drain-source on-state resistance | $V_{GS} = V_{GS(th)} + 3.75\text{ V};$<br>$I_D = 9.45\text{ A}$    | 0.012 | 0.07 | 0.093 | $\Omega$      |
| $C_{rs}$      | feedback capacitance             | $V_{GS} = 0\text{ V}; V_{DS} = 28\text{ V};$<br>$f = 1\text{ MHz}$ | -     | 3    | -     | pF            |

## 7. Application information

**Table 7. Application information**


Mode of operation: 2-carrier W-CDMA; PAR 7.5 dB at 0.01 % probability on CCDF; 3GPP test model 1; 1-64 PDPCH;  $f_1 = 871.5\text{ MHz}; f_2 = 876.5\text{ MHz}; f_3 = 886.5\text{ MHz}; f_4 = 891.5\text{ MHz};$  RF performance at  $V_{DS} = 28\text{ V}; I_{Dq} = 1400\text{ mA}; T_{case} = 25\text{ °C};$  unless otherwise specified; in a class-AB production test circuit.

| Symbol      | Parameter                    | Conditions                | Min | Typ   | Max  | Unit |
|-------------|------------------------------|---------------------------|-----|-------|------|------|
| $P_{L(AV)}$ | average output power         |                           | -   | 40    | -    | W    |
| $G_p$       | power gain                   | $P_{L(AV)} = 40\text{ W}$ | 19  | 20    | -    | dB   |
| IRL         | input return loss            | $P_{L(AV)} = 40\text{ W}$ | -   | -6.4  | -4.5 | dB   |
| $\eta_D$    | drain efficiency             | $P_{L(AV)} = 40\text{ W}$ | 25  | 28.5  | -    | %    |
| ACPR        | adjacent channel power ratio | $P_{L(AV)} = 40\text{ W}$ | -   | -39.4 | -36  | dBc  |


### 7.1 Ruggedness in class-AB operation

The BLF6G10-200RN and BLF6G10LS-200RN are enhanced rugged devices and are capable of withstanding a load mismatch corresponding to VSWR = 10 : 1 through all phases under the following conditions:  $V_{DS} = 28\text{ V}; I_{Dq} = 1400\text{ mA}; P_L = 200\text{ W};$   $f = 894\text{ MHz}.$


7.2 One-tone CW



7.3 Two-tone CW




7.4 2-carrier W-CDMA



$V_{DS} = 28\text{ V}$ ;  $I_{DQ} = 1400\text{ mA}$ ;  $f = 881\text{ MHz}$  ( $\pm 5\text{ MHz}$ ); carrier spacing 10 MHz.


Fig 4. 2-carrier W-CDMA power gain and drain efficiency as function of average load power; typical values



$V_{DS} = 28\text{ V}$ ;  $I_{DQ} = 1400\text{ mA}$ ;  $f = 881\text{ MHz}$  ( $\pm 5\text{ MHz}$ ); carrier spacing 10 MHz.

Fig 5. 2-carrier W-CDMA adjacent channel power ratio and third order intermodulation distortion as function of average load power; typical values

8. Test information



The drawing is not to scale.

Fig 6. Test circuit for operation at 800 MHz




Table 8. List of components

See [Figure 6](#) and [Figure 7](#).

| Component             | Description                       | Value                | Remarks                                  |
|-----------------------|-----------------------------------|----------------------|--|
| C1, C3, C11, C12, C16 | multilayer ceramic chip capacitor | 68 pF                | [1] solder vertically                    |
| C2                    | multilayer ceramic chip capacitor | 13 pF                | [1] solder vertically                    |
| C5, C6                | multilayer ceramic chip capacitor | 10 pF                | [1] solder vertically                    |
| C7, C8, C9, C10       | electrolytic capacitor            | 220 nF               | Vishay VJ1206Y224KXB                     |
| C13, C14              | multilayer ceramic chip capacitor | 4.7 $\mu$ F; 50 V    | [2]                                      |
| C15                   | multilayer ceramic chip capacitor | 1.5 pF               | [1] solder vertically                    |
| C17, C18              | electrolytic capacitor            | 220 $\mu$ F; 63 V    |  |
| L1                    | ferrite SMD bead                  | -                    | Ferroxcube BDS 3/3/4.6-4S2 or equivalent |
| Q1                    | BLF6G10LS-200RN                   | -                    |  |
| R1, R2, R3            | SMD resistor                      | 9.1 $\Omega$ ; 0.1 W |  |

[1] American Technical Ceramics type 100B or capacitor of same quality.

[2] TDK or capacitor of same quality.

9. Package outline

Flanged ceramic package; 2 mounting holes; 2 leads

SOT502A




Fig 8. Package outline SOT502A

Earless flanged ceramic package; 2 leads

SOT502B




Fig 9. Package outline SOT502B



## 10. Abbreviations

Table 9. Abbreviations

| Acronym | Description   |
|---------|---|
| 3GPP    | Third Generation Partnership Project                    |
| CCDF    | Complementary Cumulative Distribution Function          |
| CDMA    | Code Division Multiple Access                           |
| CW      | Continuous Wave   |
| DPCH    | Dedicated Physical CHannel                              |
| EDGE    | Enhanced Data rates for GSM Evolution                   |
| GSM     | Global System for Mobile communications                 |
| LDMOS   | Laterally Diffused Metal-Oxide Semiconductor            |
| LDMOST  | Laterally Diffused Metal-Oxide Semiconductor Transistor |
| PAR     | Peak-to-Average power Ratio                             |
| PDPCH   | transmission Power of the Dedicated Physical CHannel    |
| RF      | Radio Frequency   |
| SMD     | Surface Mounted Device                                  |
| VSWR    | Voltage Standing-Wave Ratio                             |
| W-CDMA  | Wideband Code Division Multiple Access                  |

## 11. Revision history

Table 10. Revision history

| Document ID                | Release date   | Data sheet status  | Change notice | Supersedes                 |
|----------------------------|--|--------------------|---------------|----------------------------|
| BLF6G10-200RN_10LS-200RN#3 | 20150901   | Product data sheet | -             | BLF6G10-200RN_10LS-200RN_2 |
| Modifications:             | <ul style="list-style-type: none"> <li>The format of this document has been redesigned to comply with the new identity guidelines of Ampleon.</li> <li>Legal texts have been adapted to the new company name where appropriate.</li> </ul> |                    |               |                            |
| BLF6G10-200RN_10LS-200RN_2 | 20100121   | Product data sheet | -             | BLF6G10-200RN_10LS-200RN_1 |
| BLF6G10-200RN_10LS-200RN_1 | 20090119   | Product data sheet | -             | -                          |

## 12. Legal information

### 12.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

### 12.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

### 12.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

**Right to make changes** — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

### 12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Any reference or use of any 'NXP' trademark in this document or in or on the

surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own Any reference or use of any 'NXP' trademark in this document or in or on the

surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own trademarks.

## 13. Contact information

---

For more information, please visit:

<http://www.ampleon.com>

For sales office addresses, please visit:

<http://www.ampleon.com/sales>

## 14. Contents

---

|           |  |           |
|-----------|--|-----------|
| <b>1</b>  | <b>Product profile</b> . . . . .           | <b>1</b>  |
| 1.1       | General description . . . . .              | 1         |
| 1.2       | Features . . . . .                         | 1         |
| 1.3       | Applications . . . . .                     | 2         |
| <b>2</b>  | <b>Pinning information</b> . . . . .       | <b>2</b>  |
| <b>3</b>  | <b>Ordering information</b> . . . . .      | <b>2</b>  |
| <b>4</b>  | <b>Limiting values</b> . . . . .           | <b>2</b>  |
| <b>5</b>  | <b>Thermal characteristics</b> . . . . .   | <b>3</b>  |
| <b>6</b>  | <b>Characteristics</b> . . . . .           | <b>3</b>  |
| <b>7</b>  | <b>Application information</b> . . . . .   | <b>3</b>  |
| 7.1       | Ruggedness in class-AB operation . . . . . | 3         |
| 7.2       | One-tone CW . . . . .                      | 4         |
| 7.3       | Two-tone CW . . . . .                      | 4         |
| 7.4       | 2-carrier W-CDMA . . . . .                 | 5         |
| <b>8</b>  | <b>Test information</b> . . . . .          | <b>5</b>  |
| <b>9</b>  | <b>Package outline</b> . . . . .           | <b>7</b>  |
| <b>10</b> | <b>Abbreviations</b> . . . . .             | <b>9</b>  |
| <b>11</b> | <b>Revision history</b> . . . . .          | <b>9</b>  |
| <b>12</b> | <b>Legal information</b> . . . . .         | <b>10</b> |
| 12.1      | Data sheet status . . . . .                | 10        |
| 12.2      | Definitions . . . . .                      | 10        |
| 12.3      | Disclaimers . . . . .                      | 10        |
| 12.4      | Trademarks . . . . .                       | 10        |
| <b>13</b> | <b>Contact information</b> . . . . .       | <b>11</b> |
| <b>14</b> | <b>Contents</b> . . . . .                  | <b>12</b> |

---

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

---

© Ampleon The Netherlands B.V. 2015. All rights reserved.

For more information, please visit: <http://www.ampleon.com>  
For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 1 September 2015

Document identifier: BLF6G10-200RN\_10LS-200RN#3