



晶丰明源半导体

BPM0605CG

60V Complementary MOSFET

General Description

The BPM0605CG uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

- H-bridge
- Inverters

Features

N channel

- $V_{DS} = 60V$, $I_D = 6.3A$
 $R_{DS(ON)} < 30m\Omega$ @ $V_{GS} = 10V$

P channel

- $V_{DS} = -60V$, $I_D = -5A$
 $R_{DS(ON)} < 80m\Omega$ @ $V_{GS} = -10V$
- High power and current handling capability
- Lead free product is acquired
- Surface mount package

Application

Typical Application




Figure 1. Schematic Diagram

Ordering Information

Part Number	Package	Operating Temperature	Packing Type	Marking
BPM0605CG	SOP-8	-40 °C to 105 °C	Tape&Reel 4,000pcs/Reel	BPM0605 XXXXXY CGXWW

Pin Configuration and Marking Information




Figure 2. Pin Configuration and Marking Information

Pin Definition

Pin No.	Name	Description
1	S1	NMOS Source
2	G1	NMOS Gate
3	S2	PMOS Source
4	G2	PMOS Gate
5	D2	PMOS Drain
6	D2	PMOS Drain
7	D1	NMOS Drain
8	D1	NMOS Drain

Absolute Maximum Rating (note 1) (Unless otherwise specified, T_A=25°C)

Symbol	Parameter	N-Channel	P-Channel	Unit
V _{DS}	Drain-Source Voltage	60	-60	V
V _{GS}	Gate-Source Voltage	±20	±20	V
I _D	Continuous Drain Current	T _C =25°C	6.3	A
		T _C =70°C	4.5	
I _{DM}	Pulsed Drain Current (note 2)	40	-25	A
P _D	Maximum Power Dissipation	T _C =25°C	2	W
T _J , T _{STG}	Operating Junction and Storage Temperature Range	-55 to 150	-55 to 150	°C
R _{θJA}	Thermal Resistance, Junction-to-Ambient (note 3)	62.5	62.5	°C/W

Note 1: Stress beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. Under “recommended operating



晶丰明源半导体

BPM0605CG

60V Complementary MOSFET

conditions" the device operation is assured, but some particular parameter may not be achieved. The electrical characteristics table defines the operation range of the device, the electrical characteristics is assured on DC and AC voltage by the test program. For the parameters without minimum and maximum value in the EC table, the typical value defines the operation range, the accuracy is not guaranteed by spec.

Note 2: Repetitive Rating: Pulse width limited by maximum junction temperature.

Note 3: Surface Mounted on FR4 Board, $t \leq 10$ sec.

N-Channel Electrical Characteristics (note 4, 5) (Unless otherwise specified, $T_A=25^\circ\text{C}$)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
Off Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V I _D =250μA	60	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =60V, V _{GS} =0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
On Characteristics (Note 6)						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.2	1.6	2.5	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =6A	-	26	30	mΩ
g _{FS}	Forward Transconductance	V _{DS} =5V, I _D =6A	15	-	-	S
Dynamic Characteristics (Note7)						
C _{iss}	Input Capacitance	V _{DS} =15V, V _{GS} =0V, F=1.0MHz	-	415	-	PF
C _{oss}	Output Capacitance		-	112	-	PF
C _{rss}	Reverse Transfer Capacitance		-	11	-	PF
Switching Characteristics (Note 7)						
t _{d(on)}	Turn-on Delay Time	V _{DD} =30V, R _L =4.7Ω V _{GS} =10V, R _{GEN} =3Ω	-	5	-	nS
t _r	Turn-on Rise Time		-	2.6	-	nS
t _{d(off)}	Turn-Off Delay Time		-	16.1	-	nS
t _f	Turn-Off Fall Time		-	2.3	-	nS
Q _g	Total Gate Charge	V _{DS} =15V, I _D =6A, V _{GS} =10V	-	25	-	nC
Q _{gs}	Gate-Source Charge		-	4.5	-	nC
Q _{gd}	Gate-Drain Charge		-	6.5	-	nC
Drain-Source Diode Characteristics						
V _{SD}	Diode Forward Voltage (Note 6)	V _{GS} =0V, I _S =6A	-	0.8	1.2	V



晶丰明源半导体

BPM0605CG

60V Complementary MOSFET

P-Channel Electrical Characteristics(note 4, 5) (Unless otherwise specified, $T_A=25^{\circ}\text{C}$)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
Off Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V I _D =-250μA	-60	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-60V, V _{GS} =0V	-	-	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
On Characteristics (Note 6)						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1.5	-2.6	-3.5	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =-10V, I _D =-5A	-	64	80	mΩ
g _{FS}	Forward Transconductance	V _{DS} =-15V, I _D =-5A	16	-	-	S
Dynamic Characteristics (Note7)						
C _{ISS}	Input Capacitance	V _{DS} =-20V, V _{GS} =0V, F=1.0MHz	-	1450	-	PF
C _{OSS}	Output Capacitance		-	145	-	PF
C _{rss}	Reverse Transfer Capacitance		-	110	-	PF
Switching Characteristics (Note 7)						
t _{d(on)}	Turn-on Delay Time	V _{DD} =-30V, R _L =30Ω V _{GS} =-10V, R _{GEN} =6Ω	-	8	-	nS
t _r	Turn-on Rise Time		-	9	-	nS
t _{d(off)}	Turn-Off Delay Time		-	65	-	nS
t _f	Turn-Off Fall Time		-	30	-	nS
Q _g	Total Gate Charge	V _{DS} =-30V, I _D =-5A, V _{GS} =-10V	-	26	-	nC
Q _{gs}	Gate-Source Charge		-	45	-	nC
Q _{gd}	Gate-Drain Charge		-	7	-	nC
Drain-Source Diode Characteristics						
V _{SD}	Diode Forward Voltage (Note 6)	V _{GS} =0V, I _S =-5A	-	-0.8	-1.2	V

Note 4: Production testing of the chip is performed at 25°C .

Note 5: The maximum and minimum parameters specified are guaranteed by test, the typical value are guaranteed by design, characterization and statistical analysis.

Note 6: Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

Note 7: Guaranteed by design, not subject to production

N-Channel Typical Electrical and Thermal Characteristics Curves




Figure 3. Switching Test Circuit




Figure 4. Switching Waveforms




Figure 5. Output Characteristics




Figure 6. Transfer Characteristics




Figure 7. Drain-Source On-Resistance










Figure 8. Drain-Source On-Resistance



晶丰明源半导体

BPM0605CG

60V Complementary MOSFET






Figure 15. Normalized Maximum Transient Thermal Impedance

P-Channel Typical Electrical and Thermal Characteristics Curves




Figure 16. Output Characteristics




Figure 17. $R_{DS(ON)}$ -Junction Temperature




Figure 18. Transfer Characteristics




Figure 19. Gate Charge



晶丰明源半导体

BPM0605CG

60V Complementary MOSFET




Figure 20. $R_{DS(on)}$ - Drain Current




Figure 21. Source-Drain Diode Forward




Figure 22. Capacitance vs V_{DS}




Figure 23. BV_{DS} - Junction Temperature




Figure 24. Safe Operation Area




Figure 25. $V_{GS(th)}$ vs. Junction Temperature





Figure 26. Normalized Maximum Transient Thermal Impedance

Physical Dimension

SOP8 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°