## **BR305** -WILLAS THRU **BR310** SINGLE-PHASE SILICON BRIDGE RECTIFIER VOLTAGE RANGE 50 to 1000 Volts CURRENT 3.0 Amperes Pb Free Product FEATURES \* Surge overloab rating: 50 amperes peak \* Low forward voltage drop \* Small size: simple installation \* Silver-plated copper leads \* Mounting position: Any BR-3 \* Mounting: Hole thru for # 6 screw \* Weight: 3.36 grams .213 (5.4) **MECHANICAL DATA** Ì I .193 (4.9) \* UL listed the recognized component directory, file #E195711 \* Epoxy: Device has UL flammability classification 94V-O

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.



Dimensions in inches and (millimeters)

#### MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	BR305	BR31	BR32	BR34	BR36	BR38	BR310	UNITS
Maximum Recurrent Peak Reverse Voltage	Vrrm	50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage	Vrms	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Output Current at Tc = 50°C	lo	3.0						Amps	
Peak Forward Surge Current 8.3 ms single half sine-wave	Icon		50						
superimposed on rated load (JEDEC method)	IFSM	30							Amps
Operating Temperature Range	TJ	-55 to + 125							٥C
Storage Temperature Range	Тѕтс	-55 to + 150							٥C

#### ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS		SYMBOL	BR305	BR31	BR32	BR34	BR36	BR38	BR310	UNITS
Maximum Forward Voltage Drop per element at 1.5A DC		Vf	1.0							Volts
Maximum Reverse Current at Rated	@TA = 25°C	la la	5							uAmps
DC Blocking Voltage per element	@Tc = 100°C	IR IR	0.1							mAmps



# RATING AND CHARACTERISTIC CURVES (BR305 THRU BR310)

FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE



WILLAS ELECTRONIC CORP.