



BTA16

Preliminary


TRIAC

16A TRIACS

DESCRIPTION


The UTC **BTA16** is a 16A triacs which can be operated in 4 quadrants, it uses UTC's advanced technology to provide customers with high commutation performances, etc.

The UTC **BTA16** is suitable for AC switching application and phase control application such as fan speed and temperature modulation control, lighting control and static switching relay, either in through-hole or surface-mount packages.



TO-220F

SYMBOL



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
BTA16L-x-x-TF3-T	BTA16G-x-x-TF3-T	TO-220F	MT1	MT2	G	Tube

BTA16L-x-x-TF3-T	
(1)Packing Type	(1) T: Tube
(2)Package Type	(2) TF3: TO-220F
(3)Sensitivity and type	(3) refer to SENSITIVITY AND TYPE
(4)Voltage	(4) 6: 600V, 8: 800V
(5)Lead Free	(5) L: Lead Free, G: Halogen Free

SENSITIVITY AND TYPE

PART NUMBER	VOLTAGE		SENSITIVITY	TYPE
	600V	800V		
B	⊙	⊙	50mA	STANDARD
C	⊙		25mA	STANDARD

⊙: Available

MARKING INFORMATION

PACKAGE	MARKING
TO-220F	UTC BTA16 Lot Code 1 L: Lead Free G: Halogen Free Data Code

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER			SYMBOL	RATINGS	UNIT
RMS On-State Current (Full Sine Wave)		T _C =86°C	I _{T(RMS)}	16	A
Non Repetitive Surge Peak On-State Current (Full Cycle, T _J initial=25°C)	F=50 Hz	t=20ms	I _{TSM}	160	A
	F=60 Hz	t=16.7ms		168	A
I ² t Value for Fusing	t _p =10ms		I ² t	144	A ² s
Critical Rate of Rise of On-State Current I _G =2xI _{GT} , tr≤100ns	F=120 Hz	T _J =125°C	di/dt	50	A/μs
Non Repetitive Surge Peak Off-State Voltage	t _p =10ms	T _J =25°C	V _{DSM} /V _{RSM}	V _{DRM} /V _{RRM} +100	V
Peak Gate Current	t _p =20μs	T _J =125°C	I _{GM}	4	A
Average Gate Power Dissipation		T _J =125°C	P _{G(AV)}	1	W
Operating Junction Temperature			T _J	-40~+125	°C
Storage Junction Temperature			T _{STG}	-40~+150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL RESISTANCES

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	60	$^{\circ}\text{C}/\text{W}$
Junction to Case (AC)	θ_{JC}	2.1	$^{\circ}\text{C}/\text{W}$

■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$ unless otherwise specified.)

FOR STANDARD TYPE (4 QUADRANTS)

PARAMETER	SYMBOL	TEST CONDITIONS	C			B			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Gate Trigger Current (Note 1)	I_{GT}	$V_D=12\text{V}$, $R_L=33\Omega$	I-II-III		25			50	mA
					50			100	mA
Gate Trigger Voltage	V_{GT}		ALL		1.3			1.3	V
Gate Non-Trigger Voltage	V_{GD}	$V_D=V_{DRM}$, $R_L=3.3\text{k}\Omega$, $T_J=125^{\circ}\text{C}$	ALL	0.2		0.2			V
Holding Current (Note 2)	I_H	$I_T=500\text{mA}$			25			50	mA
Latching Current	I_L	$I_G=1.2 I_{GT}$	I-III-IV		40			60	mA
			II		80			120	mA
Critical Rate of Rise of Off-State Voltage (Note 2)	dV/dt	$V_D=67\%V_{DRM}$, Gate Open, $T_J=125^{\circ}\text{C}$	200			400			$\text{V}/\mu\text{s}$
Critical Rate of Rise of Off-State Voltage at Commutation (Note 2)	$(dV/dt)_c$	$(di/dt)_c=7\text{A/ms}$, $T_J=125^{\circ}\text{C}$	5			10			$\text{V}/\mu\text{s}$

■ STATIC CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Peak On-State Voltage (Note 2)	V_{TM}	$I_{TM}=22.5\text{A}$, $t_p=380\mu\text{s}$ $T_J=25^{\circ}\text{C}$			1.55	V
Threshold Voltage (Note 2)	V_{TO}	$T_J=125^{\circ}\text{C}$			0.85	V
Dynamic Resistance (Note 2)	R_D	$T_J=125^{\circ}\text{C}$			25	$\text{m}\Omega$
Repetitive Peak Off-State Current	I_{DRM}	$V_{DRM}=V_{RRM}$ $T_J=25^{\circ}\text{C}$			5	μA
	I_{RRM}				2	mA

Note: 1. Minimum I_{GT} is guaranteed at 5% of I_{GT} max.

2. For both polarities of MT2 referenced to MT1.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.