

PowerMOS transistor

Voltage clamped logic level FET

BUK553-48C

GENERAL DESCRIPTION



Protected N-channel enhancement mode logic level field-effect power transistor in a plastic envelope. The device is intended for use in automotive applications. It has built-in zener diodes providing active drain voltage clamping.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MIN.	TYP.	MAX.	UNIT
$V_{(CL)DSR}$	Drain-source clamp voltage	40	48	58	V
I_D	Drain current (DC)		21	21	A
P_{tot}	Total power dissipation		75	75	W
T_j	Junction temperature		175	175	°C
W_{DSRR}	Repetitive clamped turn off energy; $T_j = 150^\circ\text{C}$		50	50	mJ
$R_{DS(ON)}$	Drain-source on-state resistance; $V_{GS} = 5\text{ V}$		85	85	$\text{m}\Omega$

PINNING - TO220AB

PIN	DESCRIPTION
1	gate
2	drain
3	source
tab	drain

PIN CONFIGURATION**SYMBOL****LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{DS}	Drain-source voltage	continuous	-	30	V
V_{DG}	Drain-gate voltage	continuous	-	30	V
$\pm V_{GS}$	Gate-source voltage	-	-	15	V
I_D	Drain current (DC)	$T_{mb} = 25^\circ\text{C}$	-	21	A
I_D	Drain current (DC)	$T_{mb} = 100^\circ\text{C}$	-	15	A
I_{DM}	Drain current (pulse peak value)	$T_{mb} = 25^\circ\text{C}$	-	84	A
P_{tot}	Total power dissipation	$T_{mb} = 25^\circ\text{C}$	-	75	W
T_{stg}	Storage temperature	-	-55	175	°C
T_j	Junction Temperature	-	-55	175	°C

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th j-mb}$	Thermal resistance junction to heatsink	with heatsink compound	-	-	2	K/W
$R_{th j-a}$	Thermal resistance junction to ambient		-	60	-	K/W

PowerMOS transistor
Voltage clamped logic level FET

BUK553-48C

STATIC CHARACTERISTICS $T_j = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(\text{BR})\text{DG}}$	Drain-gate zener voltage	$0.2 \leq -I_G \leq 0.4 \text{ mA}; -55^\circ\text{C} \leq T_j \leq 150^\circ\text{C}$	38	45	54	V
$V_{\text{GS}(\text{TO})}$	Gate threshold voltage	$V_{\text{DS}} = V_{\text{GS}}; I_D = 1 \text{ mA}$	1.0	1.5	2.0	V
$V_{\text{GS}(\text{ON})}$	Gate voltage	$V_{\text{DS}} = 10 \text{ V}; I_D = 10 \text{ A}; -55^\circ\text{C} \leq T_j \leq 150^\circ\text{C}$	2.0	3.1	4.0	V
I_{DSS}	Zero gate voltage drain current	$V_{\text{DS}} = 30 \text{ V}; V_{\text{GS}} = 0 \text{ V}; T_j = 150^\circ\text{C}$	-	0.01	1.0	mA
I_{GSS}	Gate source leakage current	$V_{\text{GS}} = \pm 15 \text{ V}; V_{\text{DS}} = 0 \text{ V}; T_j = 150^\circ\text{C}$	-	0.1	10	μA
$R_{\text{DS}(\text{ON})}$	Drain-source on-state resistance	$V_{\text{GS}} = 5 \text{ V}; I_D = 10 \text{ A}$	-	65	85	$\text{m}\Omega$

DYNAMIC CHARACTERISTICS $T_j = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(\text{CL})\text{DSR}}$	Drain source clamp voltage (peak value)	$R_G = 10 \text{ k}\Omega; I_D = 10 \text{ A}; -55 \leq T_j \leq 150^\circ\text{C}; \text{Inductive load.}$	40	48	58	V
g_{fs}	Forward transconductance	$V_{\text{DS}} = 25 \text{ V}; I_D = 10 \text{ A}$	7	12	-	S
C_{iss}	Input capacitance	$V_{\text{GS}} = 0 \text{ V}; V_{\text{DS}} = 25 \text{ V}; f = 1 \text{ MHz}$	-	550	825	pF
C_{oss}	Output capacitance		-	240	350	pF
C_{rss}	Feedback capacitance		-	100	160	pF
$t_{d\text{ on}}$	Turn-on delay time	$V_{DD} = 12 \text{ V}; I_D = 5 \text{ A}; V_{\text{GS}} = 5 \text{ V}; R_G = 10 \text{ k}\Omega;$	-	3.5	-	μs
t_r	Turn-on rise time		-	22	-	μs
$t_{d\text{ off}}$	Turn-off delay time		-	16	-	μs
t_f	Turn-off fall time		-	18	-	μs
L_d	Internal drain inductance	Measured from drain lead 6 mm from package to centre of die	-	4.5	-	nH
L_s	Internal source inductance	Measured from source lead 6 mm from package to source bond pad	-	7.5	-	nH

REVERSE DIODE LIMITING VALUES AND CHARACTERISTICS $T_j = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{DR}	Continuous reverse drain current	-	-	-	21	A
I_{DRM}	Pulsed reverse drain current	-	-	-	84	A
V_{SD}	Diode forward voltage	$I_F = 21 \text{ A}; V_{\text{GS}} = 0 \text{ V}$	-	1.3	1.7	V

PowerMOS transistor
Voltage clamped logic level FET

BUK553-48C

CLAMPED ENERGY LIMITING VALUE

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
W_{DSRS}	Non-repetitive drain-source clamped inductive turn off energy	$T_j = 25^\circ\text{C}$ prior to clamping; $I_D = 10 \text{ A}$; $V_{DD} \leq 16 \text{ V}$; $V_{GS} = 5 \text{ V}$; $R_G = 10 \text{ k}\Omega$; inductive load	-	200	mJ
W_{DSRR}	Drain-source repetitive clamped inductive turn off energy	$T_j = 150^\circ\text{C}$ prior to clamping; $I_D = 10 \text{ A}$; $V_{DD} \leq 16 \text{ V}$; $V_{GS} = 5 \text{ V}$; $R_G = 10 \text{ k}\Omega$; inductive load	-	50	mJ




Fig.1. Normalised power dissipation.
 $PD\% = 100 \cdot P_D / P_{D, 25^\circ\text{C}} = f(T_{mb})$




Fig.3. Normalised continuous drain current.
 $ID\% = 100 \cdot I_D / I_{D, 25^\circ\text{C}} = f(T_{mb})$; conditions: $V_{GS} \geq 5 \text{ V}$




Fig.2. Safe operating area. $T_{mb} = 25^\circ\text{C}$
 I_D & $I_{DM} = f(V_{DS})$; I_{DM} single pulse; parameter t_p




Fig.4. Transient thermal impedance.
 $Z_{th j-mb} = f(t)$; parameter $D = t_p/T$

PowerMOS transistor

Voltage clamped logic level FET

BUK553-48C




Fig.5. Typical output characteristics, $T_j = 25^\circ\text{C}$.
 $I_D = f(V_{DS})$; parameter V_{GS}




Fig.8. Typical transfer characteristics.
 $I_D = f(V_{GS})$; conditions: $V_{DS} = 25\text{V}$.




Fig.6. Typical on-state resistance, $T_j = 25^\circ\text{C}$.
 $R_{DS(ON)} = f(I_D)$; parameter V_{GS}




Fig.9. Typical transconductance.
 $g_{fs} = f(I_D)$; conditions: $V_{DS} = 25\text{V}$




Fig.7. Typical clamping voltage
 $V_{(CL)DSR} = f(I_D)$; conditions: $R_G = 10\text{k}\Omega$




Fig.10. Typical clamping voltage
 $V_{(CL)DSR} = f(R_G)$; conditions: $I_D = 10\text{A}$.

PowerMOS transistor

Voltage clamped logic level FET

BUK553-48C




Fig.11. Normalised drain-source on-state resistance.
 $a = R_{DS(ON)}/R_{DS(ON)25} = f(T_j); I_D = 10 \text{ A}; V_{GS} = 5 \text{ V}$




Fig.14. Gate threshold voltage.
 $V_{GS(TO)} = f(T_j)$; conditions: $I_D = 1 \text{ mA}$; $V_{DS} = V_{GS}$




Fig.12. Sub-threshold drain current.
 $I_D = f(V_{GS})$; conditions: $T_j = 25 \text{ }^\circ\text{C}$; $V_{DS} = V_{GS}$




Fig.15. Typical reverse diode current.
 $I_F = f(V_{SDS})$; conditions: $V_{GS} = 0 \text{ V}$; parameter T_j




Fig.13. Typical capacitances, C_{iss} , C_{oss} , C_{rss} .
 $C = f(V_{DS})$; conditions: $V_{GS} = 0 \text{ V}$; $f = 1 \text{ MHz}$






Fig.16. Typical turn-on gate-charge characteristics.
 $V_{GS} = f(Q_G)$; conditions: $I_D = 10 \text{ A}$; parameter V_{DS}

**PowerMOS transistor
Voltage clamped logic level FET****BUK553-48C**

**PowerMOS transistor
Voltage clamped logic level FET****BUK553-48C****MECHANICAL DATA***Dimensions in mm*

Net Mass: 2 g




Fig.19. TO220AB; pin 2 connected to mounting base.

Notes

1. Observe the general handling precautions for electrostatic-discharge sensitive devices (ESDs) to prevent damage to MOS gate oxide.
2. Refer to mounting instructions for TO220 envelopes.
3. Epoxy meets UL94 V0 at 1/8".

**PowerMOS transistor
Voltage clamped logic level FET****BUK553-48C****DEFINITIONS**

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© Philips Electronics N.V. 1996	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

1) Level: Warning

Message: Picture is too large; will be automatically scaled
Location: Document Body: [PICTURE]
Page: 6 Distance from TOF: 6.47cm
Level: 1 Section: 24 Block: Headline Column: 1