

# PowerMOS transistor

## Logic level FET

BUK556-60H

**GENERAL DESCRIPTION**



N-channel enhancement mode logic level field-effect power transistor in a plastic envelope.  
The device is intended for use in automotive and general purpose switching applications.

**QUICK REFERENCE DATA**

SYMBOL	PARAMETER	MAX.	UNIT
$V_{DS}$	Drain-source voltage	60	V
$I_D$	Drain current (DC)	60	A
$P_{tot}$	Total power dissipation	150	W
$T_j$	Junction temperature	175	°C
$R_{DS(ON)}$	Drain-source on-state resistance; $V_{GS} = 5$ V	22	$m\Omega$

**PINNING - TO220AB**

PIN	DESCRIPTION
1	gate
2	drain
3	source
tab	drain

**PIN CONFIGURATION****SYMBOL****LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{DS}$	Drain-source voltage	-	-	60	V
$V_{DGR}$	Drain-gate voltage	$R_{GS} = 20$ kΩ	-	60	V
$\pm V_{GS}$	Gate-source voltage	-	-	15	V
$I_D$	Drain current (DC)	$T_{mb} = 25$ °C	-	60	A
$I_D$	Drain current (DC)	$T_{mb} = 100$ °C	-	44	A
$I_{DM}$	Drain current (pulse peak value)	$T_{mb} = 25$ °C	-	240	A
$P_{tot}$	Total power dissipation	$T_{mb} = 25$ °C	-	150	W
$T_{stg}$	Storage temperature	-	-55	175	°C
$T_j$	Junction Temperature	-	-	175	°C

**THERMAL RESISTANCES**

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th j-mb}$	From junction to mounting base		-	-	1.0	K/W
$R_{th j-a}$	From junction to ambient		-	60	-	K/W

**PowerMOS transistor  
Logic level FET**

BUK556-60H

**STATIC CHARACTERISTICS** $T_j = 25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(\text{BR})\text{DSS}}$	Drain-source breakdown voltage	$V_{GS} = 0 \text{ V}; I_D = 0.25 \text{ mA}$	60	-	-	V
$V_{GS(\text{TO})}$	Gate threshold voltage	$V_{DS} = V_{GS}; I_D = 1 \text{ mA}$	1.0	1.5	2.0	V
$I_{DSS}$	Zero gate voltage drain current	$V_{DS} = 60 \text{ V}; V_{GS} = 0 \text{ V}$	-	1	10	$\mu\text{A}$
$I_{DSS}$	Zero gate voltage drain current	$V_{DS} = 60 \text{ V}; V_{GS} = 0 \text{ V}; T_j = 125^\circ\text{C}$	-	0.1	1.0	mA
$I_{GSS}$	Gate source leakage current	$V_{GS} = \pm 15 \text{ V}; V_{DS} = 0 \text{ V}$	-	10	100	nA
$R_{DS(\text{ON})}$	Drain-source on-state resistance	$V_{GS} = 5 \text{ V}; I_D = 25 \text{ A}$	-	18	22	$\text{m}\Omega$

**DYNAMIC CHARACTERISTICS** $T_j = 25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$g_{fs}$	Forward transconductance	$V_{DS} = 25 \text{ V}; I_D = 25 \text{ A}$	17	30	-	S
$C_{iss}$	Input capacitance	$V_{GS} = 0 \text{ V}; V_{DS} = 25 \text{ V}; f = 1 \text{ MHz}$	-	2200	2800	pF
$C_{oss}$	Output capacitance		-	700	1000	pF
$C_{rss}$	Feedback capacitance		-	280	400	pF
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 30 \text{ V}; I_D = 3 \text{ A}$	-	40	50	ns
$t_r$	Turn-on rise time	$V_{GS} = 5 \text{ V}; R_{GS} = 50 \Omega$	-	150	250	ns
$t_{d(off)}$	Turn-off delay time		-	350	450	ns
$t_f$	Turn-off fall time	$R_{gen} = 50 \Omega$	-	190	250	ns
$L_d$	internal drain inductance	Measured from contact screw on tab to centre of die	-	5	-	nH
$L_d$	internal drain inductance	Measured from drain lead 6 mm from package to centre of die	-	5	-	nH
$L_s$	internal source inductance	Measured from source lead 6 mm from package to source bond pad	-	12.5	-	nH

**REVERSE DIODE LIMITING VALUES AND CHARACTERISTICS** $T_j = 25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$I_{DR}$	Continuous reverse drain current	-	-	-	60	A
$I_{DRM}$	Pulsed reverse drain current	-	-	-	240	A
$V_{SD}$	Diode forward voltage	$I_F = 50 \text{ A}; V_{GS} = 0 \text{ V}$	-	1.1	2.0	V
$t_{rr}$	Reverse recovery time	$I_F = 50 \text{ A}; -dl_F/dt = 100 \text{ A}/\mu\text{s}$	-	80	-	ns
$Q_{rr}$	Reverse recovery charge	$V_{GS} = -10 \text{ V}; V_R = 30 \text{ V}$	-	0.4	-	$\mu\text{C}$

**AVALANCHE LIMITING VALUE**

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$W_{DSS}$	Drain-source non-repetitive unclamped inductive turn-off energy	$I_D = 50 \text{ A}; V_{DD} \leq 25 \text{ V}; V_{GS} = 5 \text{ V}; R_{GS} = 50 \Omega; T_{mb} = 25^\circ\text{C}$	-	-	150	mJ

# PowerMOS transistor

## Logic level FET

BUK556-60H




Fig. 1. Normalised power dissipation.  
 $PD\% = 100 \cdot P_D / P_{D, 25^\circ C} = f(T_{mb})$




Fig. 4. Transient thermal impedance.  
 $Z_{th j-mb} = f(t); \text{parameter } D = t_p/T$




Fig. 2. Normalised continuous drain current.  
 $ID\% = 100 \cdot I_D / I_{D, 25^\circ C} = f(T_{mb}); \text{conditions: } V_{GS} \geq 10 \text{ V}$




Fig. 5. Typical output characteristics,  $T_j = 25^\circ C$ .  
 $I_D = f(V_{DS}); \text{parameter } V_{GS}$




Fig. 3. Safe operating area.  $T_{mb} = 25^\circ C$   
 $I_D \& I_{DM} = f(V_{DS}); I_{DM} \text{ single pulse; parameter } t_p$




Fig. 6. Typical on-state resistance,  $T_j = 25^\circ C$ .  
 $R_{DS(ON)} = f(I_D); \text{parameter } V_{GS}$

# PowerMOS transistor

## Logic level FET

BUK556-60H




Fig.7. Typical transfer characteristics.  
 $I_D = f(V_{GS})$ ; conditions:  $V_{DS} = 25$  V; parameter  $T_j$




Fig.10. Gate threshold voltage.  
 $V_{GS(TO)} = f(T_j)$ ; conditions:  $I_D = 1$  mA;  $V_{DS} = V_{GS}$




Fig.8. Typical transconductance,  $T_j = 25$  °C.  
 $g_{fs} = f(I_D)$ ; conditions:  $V_{DS} = 15$  V




Fig.11. Sub-threshold drain current.  
 $I_D = f(V_{GS})$ ; conditions:  $T_j = 25$  °C;  $V_{DS} = V_{GS}$




Fig.9. Normalised drain-source on-state resistance.  
 $a = R_{DS(ON)}/R_{DS(ON)25°C} = f(T_j)$ ;  $I_D = 25$  A;  $V_{GS} = 5$  V




Fig.12. Typical capacitances,  $C_{iss}$ ,  $C_{oss}$ ,  $C_{rss}$ .  
 $C = f(V_{DS})$ ; conditions:  $V_{GS} = 0$  V;  $f = 1$  MHz

# PowerMOS transistor

## Logic level FET

BUK556-60H




Fig.13. Typical turn-on gate-charge characteristics.  
 $V_{GS} = f(Q_G)$ ; conditions:  $I_D = 50 \text{ A}$ ; parameter  $V_{DS}$




Fig.15. Normalised avalanche energy rating.  
 $W_{DSS\%} = f(T_{mb})$ ; conditions:  $I_D = 50 \text{ A}$




Fig.14. Typical reverse diode current.  
 $I_F = f(V_{SDS})$ ; conditions:  $V_{GS} = 0 \text{ V}$ ; parameter  $T_j$




Fig.16. Avalanche energy test circuit.  
 $W_{DSS} = 0.5 \cdot L I_D^2 \cdot BV_{DSS} / (BV_{DSS} - V_{DD})$

**PowerMOS transistor  
Logic level FET**

**BUK556-60H**

**MECHANICAL DATA**

*Dimensions in mm*

Net Mass: 2 g




Fig.17. TO220AB; pin 2 connected to mounting base.

**Notes**

1. Observe the general handling precautions for electrostatic-discharge sensitive devices (ESDs) to prevent damage to MOS gate oxide.
2. Refer to mounting instructions for TO220 envelopes.
3. Epoxy meets UL94 V0 at 1/8".

**PowerMOS transistor  
Logic level FET****BUK556-60H****DEFINITIONS**

<b>Data sheet status</b>	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
<b>Limiting values</b>	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
<b>Application information</b>	
Where application information is given, it is advisory and does not form part of the specification.	
<b>© Philips Electronics N.V. 1996</b>	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

**LIFE SUPPORT APPLICATIONS**

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.