


**Rectifier diodes  
ultrafast, rugged**

**BYW29EB, BYW29ED series**

**FEATURES**

- Low forward volt drop
- Fast switching
- Soft recovery characteristic
- Reverse surge capability
- High thermal cycling performance
- Low thermal resistance

**SYMBOL**



**QUICK REFERENCE DATA**

|                                     |
|-------------------------------------|
| $V_R = 150\text{ V} / 200\text{ V}$ |
| $V_F \leq 0.895\text{ V}$           |
| $I_{F(AV)} = 8\text{ A}$            |
| $I_{RRM} = 0.2\text{ A}$            |
| $t_{tr} \leq 25\text{ ns}$          |

**GENERAL DESCRIPTION**


Ultra-fast, epitaxial rectifier diodes intended for use as output rectifiers in high frequency switched mode power supplies.

The BYW29EB series is supplied in the SOT404 surface mounting package.  
The BYW29ED series is supplied in the SOT428 surface mounting package.


**PINNING**

| PIN | DESCRIPTION          |
|-----|----------------------|
| 1   | no connection        |
| 2   | cathode <sup>1</sup> |
| 3   | anode                |
| tab | cathode              |

**SOT404**



**SOT428**



**LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

| SYMBOL      | PARAMETER                                 | CONDITIONS   | MIN. | MAX. |      | UNIT             |
|-------------|---|--|------|------|------|------------------|
|             |   |  |      |      |      |                  |
| $V_{RRM}$   | Peak repetitive reverse voltage           | <b>BYW29EB/ BYW29ED</b>  | -    | -150 | -200 | V                |
| $V_{RWM}$   | Working peak reverse voltage              |  | -    | 150  | 200  | V                |
| $V_R$       | Continuous reverse voltage                |  | -    | 150  | 200  | V                |
| $I_{F(AV)}$ | Average rectified forward current         | square wave; $\delta = 0.5$ ; $T_{mb} \leq 128\text{ }^\circ\text{C}$                        | -    | 8    |      | A                |
| $I_{FRM}$   | Repetitive peak forward current           | square wave; $\delta = 0.5$ ; $T_{mb} \leq 128\text{ }^\circ\text{C}$                        | -    | 16   |      | A                |
| $I_{FSM}$   | Non-repetitive peak forward current       | $t = 10\text{ ms}$   | -    | 80   |      | A                |
|             |   | $t = 8.3\text{ ms}$  | -    | 88   |      | A                |
| $I_{RRM}$   | Peak repetitive reverse surge current     | sinusoidal; with reapplied $V_{RRM(max)}$<br>$t_p = 2\text{ }\mu\text{s}$ ; $\delta = 0.001$ | -    | 0.2  |      | A                |
| $I_{RSM}$   | Peak non-repetitive reverse surge current | $t_p = 100\text{ }\mu\text{s}$   | -    | 0.2  |      | A                |
| $T_j$       | Operating junction temperature            |  | -    | 150  |      | $^\circ\text{C}$ |
| $T_{stg}$   | Storage temperature                       |  | - 40 | 150  |      | $^\circ\text{C}$ |

1. It is not possible to make connection to pin 2 of the SOT428 or SOT404 packages.

**Rectifier diodes  
ultrafast, rugged**
**BYW29EB, BYW29ED series**
**ESD LIMITING VALUE**

| SYMBOL | PARAMETER                                 | CONDITIONS  | MIN. | MAX. | UNIT |
|--------|---|---|------|------|------|
| $V_C$  | Electrostatic discharge capacitor voltage | Human body model;<br>$C = 250 \text{ pF}$ ; $R = 1.5 \text{ k}\Omega$ | -    | 8    | kV   |

**THERMAL RESISTANCES**







| SYMBOL                | PARAMETER                                    | CONDITIONS  | MIN. | TYP. | MAX. | UNIT |
|-----------------------|--|---|------|------|------|------|
| $R_{th \text{ j-mb}}$ | Thermal resistance junction to mounting base | SOT404 and SOT428 packages, pcb mounted, minimum footprint, FR4 board | -    | -    | 2.7  | K/W  |
| $R_{th \text{ j-a}}$  | Thermal resistance junction to ambient       |   | -    | 50   | -    | K/W  |

**ELECTRICAL CHARACTERISTICS**
 $T_j = 25 \text{ }^\circ\text{C}$  unless otherwise specified

| SYMBOL    | PARAMETER                | CONDITIONS   | MIN. | TYP. | MAX.  | UNIT          |
|-----------|--------------------------|--|------|------|-------|---------------|
| $V_F$     | Forward voltage          | $I_F = 8 \text{ A}$ ; $T_j = 150^\circ\text{C}$  | -    | 0.8  | 0.895 | V             |
|           |                          | $I_F = 8 \text{ A}$  | -    | 0.92 | 1.05  | V             |
|           |                          | $I_F = 20 \text{ A}$   | -    | 1.1  | 1.3   | V             |
| $I_R$     | Reverse current          | $V_R = V_{RWM}$  | -    | 2    | 10    | $\mu\text{A}$ |
|           |                          | $V_R = V_{RWM}$ ; $T_j = 100^\circ\text{C}$  | -    | 0.2  | 0.6   | mA            |
| $Q_{rr}$  | Reverse recovered charge | $I_F = 2 \text{ A}$ ; $V_R \geq 30 \text{ V}$ ; $-di_F/dt = 20 \text{ A}/\mu\text{s}$  | -    | 4    | 11    | nC            |
| $t_{rr1}$ | Reverse recovery time    | $I_F = 1 \text{ A}$ ; $V_R \geq 30 \text{ V}$ ; $-di_F/dt = 100 \text{ A}/\mu\text{s}$ | -    | 20   | 25    | ns            |
| $t_{rr2}$ | Reverse recovery time    | $I_F = 0.5 \text{ A}$ to $I_R = 1 \text{ A}$ ; $I_{rec} = 0.25 \text{ A}$              | -    | 15   | 20    | ns            |
| $V_{fr}$  | Forward recovery voltage | $I_F = 1 \text{ A}$ ; $di_F/dt = 10 \text{ A}/\mu\text{s}$                             | -    | 1    | -     | V             |






Rectifier diodes  
ultrafast, rugged

BYW29EB, BYW29ED series



Rectifier diodes  
ultrafast, rugged


BYW29EB, BYW29ED series




Rectifier diodes  
ultrafast, rugged

BYW29EB, BYW29ED series

**MECHANICAL DATA**



**MOUNTING INSTRUCTIONS**



**Notes**

- 1. Epoxy meets UL94 V0 at 1/8".

Rectifier diodes  
ultrafast, rugged

BYW29EB, BYW29ED series

**MECHANICAL DATA**

Dimensions in mm

Net Mass: 1.1 g




Fig.14. SOT428 : centre pin connected to tab.

**MOUNTING INSTRUCTIONS**

Dimensions in mm




Fig.15. SOT428 : minimum pad sizes for surface mounting.

**Notes**

- 1. Plastic meets UL94 V0 at 1/8".

Rectifier diodes  
ultrafast, rugged

BYW29EB, BYW29ED series

## DEFINITIONS

|  |   |
|--|---|
| <b>Data sheet status</b>   |   |
| Objective specification  | This data sheet contains target or goal specifications for product development.       |
| Preliminary specification  | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification  | This data sheet contains final product specifications.                                |
| <b>Limiting values</b>   |   |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. |   |
| <b>Application information</b>   |   |
| Where application information is given, it is advisory and does not form part of the specification.  |   |
| © Philips Electronics N.V. 1998  |   |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.  |   |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.   |   |

## LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

Rectifier diodes  
ultrafast, rugged

BYW29EB, BYW29ED series

## DEFINITIONS

|  |   |
|--|---|
| <b>Data sheet status</b>   |   |
| Objective specification  | This data sheet contains target or goal specifications for product development.       |
| Preliminary specification  | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification  | This data sheet contains final product specifications.                                |
| <b>Limiting values</b>   |   |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. |   |
| <b>Application information</b>   |   |
| Where application information is given, it is advisory and does not form part of the specification.  |   |
| © Philips Electronics N.V. 1998  |   |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.  |   |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.   |   |

## LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.