




CD4543B BCD-to-7-Segment Latch/Decoder/Driver for Liquid Crystals

Features

- Wide supply voltage:3.0V to 18V
- range High noise immunity:0.45 V_{DD} (typ.)
- Low power TTL Compatibility:Fan out of 2 driving 74L or 1 driving 74LS
- Low power dissipation:50 nA/package (typ.) at V_{DD} =5.0V
- Latch storage
- Blanking input
- Blank for all illegal inputs
- Direct-drive LCD, LED and VF displays
- Pin-for-pin replacement for CD4056B (with pin 7 tied to Vss)
- Pin-for-pin replacement for Motorola MC14543B



Ordering Information

DEVICE	Package Type	MARKING	Packing	Packing Qty
CD4543BE/ CD4543BN	DIP-16	CD4543B	TUBE	1000pcs/box
CD4543BM/TR	SOP-16	CD4543B	REEL	2500pcs/reel
CD4543BMT/TR	TSSOP-16	CD4543B	REEL	2500pcs/reel

General Description


The CD4543BM is a monolithic CMOS BCD-to-7-segment latch/decoder/driver for use with liquid crystal and other types of displays. The circuit provides the functions of a 4-bit storage latch and an 8421 BCD-to-7-segment decoder and driver. The device has the capability to invert the logic levels of the output combination. The phase(Ph), blanking (BI) and latch disable (LD) inputs are used to reverse the truth table phase, blank the display, and store a BCD code, respectively. For liquid crystal(LC) readouts, a square wave is applied to the Ph input of the circuit and the electrically common backplane of the display, and the outputs of the circuit are connected directly to the segments of the LC readout. For other types of readouts, such as light emitting diode (LED), incandescent, gas discharge, and fluorescent readouts, connection diagrams are given on this data sheet.

All inputs are protected against static discharge by diode clamps to V_{DD} and V_{SS} .

Applications

- Instrument (e.g., counter, DVM, etc.) display driver
- Computer/calculator display driver
- Cockpit display driver
- Various clock, watch, and timer users

Connection Diagram and



Truth Table

inputs							Outputs							Display
LD	BI	Ph*	D	C	B	A	a	b	c	d	e	f	g	
X	1	0	X	X	X	X	0	0	0	0	0	0	0	Blank
1	0	0	0	0	0	0	1	1	1	1	1	1	0	0
1	0	0	0	0	0	1	0	1	1	0	0	0	0	1
1	0	0	0	0	1	0	1	1	0	1	1	0	1	2
1	0	0	0	0	1	1	1	1	1	1	0	0	1	3
1	0	0	0	1	0	0	0	1	1	0	0	1	1	4
1	0	0	0	1	0	1	1	0	1	1	0	1	1	5
1	0	0	0	1	1	0	1	0	1	1	1	1	1	6
1	0	0	0	1	1	1	1	1	1	0	0	0	0	7
1	0	0	1	0	0	0	1	1	1	1	1	1	1	8
1	0	0	1	0	0	1	1	1	1	1	0	1	1	9
1	0	0	1	0	1	0	0	0	0	0	0	0	0	Blank
1	0	0	1	0	1	1	0	0	0	0	0	0	0	Blank
1	0	0	1	1	0	0	0	0	0	0	0	0	0	Blank
1	0	0	1	1	0	1	0	0	0	0	0	0	0	Blank
1	0	0	1	1	1	0	0	0	0	0	0	0	0	Blank
1	0	0	1	1	1	1	0	0	0	0	0	0	0	Blank
0	0	0	X	X	X	X	**							**
†	†	1	†				Inverse of Output Combinations Above							Display As Above

X = Don't care

† = Above combinations

* = For liquid crystal readouts, apply a square wave to Ph.

For common cathode LED readouts, select Ph = 0.

For common anode LED readouts, select Ph = 1.

** = Depends upon the BCD code previously applied when LD = 1.

Display Format



Absolute Maximum Ratings (Notes 1&2)

Condition		Min	Max	UNITS
DC Supply Voltage(V_{DD})		-0.5	+18	V_{DC}
Input Voltage (V_{IN})		-0.5	$V_{DD}+0.5$	V_{DC}
Storage Temp. Range(T_s)		-65	+150	$^{\circ}C$
Power Dissipation (P_D)	Dual-In-Line	700		mW
	Small Outline	500		mW
Lead Temperature(T_L) (Soldering, 10 seconds)		245		$^{\circ}C$

Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but specific performance is not ensured.

Recommended Operating Conditions (Note 2)

Condition		Min	Max	UNITS
DC Supply Voltage(V_{DD})		3	15	V_{DC}
Input Voltage (V_{IN})		0	V_{DD}	V_{DC}
Operating Temperature Range (T_A)		-40	+85	$^{\circ}C$

DC Electrical Characteristics (Note 2)

Symbol	Parameter	Conditions	-40 $^{\circ}C$		+25 $^{\circ}C$			+85 $^{\circ}C$		Units
			Min	Max	Min	Typ	Max	Min	Max	
I_{DD}	Quiescent Device Current	$V_{DD}=5V, V_{IN}=V_{DD}$ or V_{SS}	-	20	-	-	20	-	150	μA
		$V_{DD}=10V, V_{IN}=V_{DD}$ or V_{SS}	-	40	-	-	40	-	300	
		$V_{DD}=15V, V_{IN}=V_{DD}$ or V_{SS}	-	80	-	-	80	-	600	
V_{OL}	Low Level Output Voltage	$V_{DD}=5V$	-	0.05	-	0	0.05	-	0.05	V
		$V_{DD}=10V, I_{OL}<1\mu A$	-	0.05	-	0	0.05	-	0.05	
		$V_{DD}=15V$	-	0.05	-	0	0.05	-	0.05	
V_{OH}	High Level Output Voltage	$V_{DD}=5V$	4.95	-	4.95	5	-	4.95	-	V
		$V_{DD}=10V, I_{OL}<1\mu A$	9.95	-	9.95	10	-	9.95	-	
		$V_{DD}=15V$	14.95	-	14.95	15	-	14.59	-	
V_{IL}	Low Level Input Voltage	$V_{DD}=5V, V_O=0.5V$ or $4.5V$	-	1.5	-	-	1.5	-	1.5	V
		$V_{DD}=10V, V_O=1V$ or $9V$	-	3.0	-	-	3.0	-	3.0	
		$V_{DD}=15V, V_O=1.5V$ or $13.5V$	-	4.0	-	-	4.0	-	4.0	
V_{IH}	High Level Input Voltage	$V_{DD}=5V, V_O=0.5V$ or $4.5V$	3.5	-	3.5	-	-	3.5	-	V
		$V_{DD}=10V, V_O=1V$ or $9V$	7.0	-	7.0	-	-	7.0	-	
		$V_{DD}=15V, V_O=1.5V$ or $13.5V$	11.0	-	11.0	-	-	11.0	-	
I_{OL}	Low Level Output Current (Note 3)	$V_{DD}=5V, V_O=0.4V$	0.52	-	0.51	-	-	0.36	-	mA
		$V_{DD}=10V, V_O=0.5V$	1.3	-	1.3	-	-	0.9	-	
		$V_{DD}=15V, V_O=1.5V$	3.6	-	3.4	-	-	2.4	-	
I_{OH}	High Level Output Current (Note 3)	$V_{DD}=5V, V_O=4.6V$	-0.52	-	-0.44	-	-	-0.36	-	mA
		$V_{DD}=10V, V_O=9.5V$	-1.3	-	-1.1	-	-	-0.9	-	
		$V_{DD}=15V, V_O=13.5V$	-3.6	-	-3.0	-	-	-2.4	-	
I_{IN}	Input Current	$V_{DD}=15V, V_{IN}=0V$	-	-0.3	-	-10^{-5}	-0.3	-	-1.0	μA
		$V_{DD}=15V, V_{IN}=15V$	-	0.3	-	10^{-5}	0.3	-	1.0	

AC Electrical Characteristics* $T_A=25^{\circ}\text{C}$, $C_L=50\text{ pF}$, $V_{SS}=0$, unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ	Max	Units
t_r	Output Rise Time	VDD=5V VDD=10V VDD=15V	-	100 50 40	200 100 80	ns
t_f	Output Fall Time	VDD=5V VDD=10V VDD=15V	-	100 50 40	200 100 80	ns
t_{PLH}	Turn-ON Propagation Delay Time	VDD=5V VDD=10V VDD=15V	-	450 170 110	1100 440 330	ns
t_{PHL}	Turn-OFF Propagation Delay Time	VDD=5V VDD=10V VDD=15V	-	500 180 120	1100 440 330	ns
t_{SET-UP}	Set-Up Time	VDD=5V VDD=10V VDD=15V	-	-5 -2 0	80 30 20	ns
t_{HOLD}	Hold Time	VDD=5V VDD=10V VDD=15V	-	30 20 15	120 45 30	ns
PW_{LD}	Latch Disable Pulse Width	VDD=5V VDD=10V VDD=15V	-	50 30 20	250 100 80	ns
C_{IN}	Input Capacitance	Per input	-	5	7.5	pF
C_{PD}	Power Dissipation Capacitance	See Cpo Measurement Waveforms (Note 4)	-	300	-	pF

* AC Parameters are guaranteed by DC correlated testing.


Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed; they are not meant to imply that the devices should be operated at these limits. The tables of "Recommended Operating Conditions" and "Electrical Characteristics" provide conditions for actual device operation.

Note 2: $V_{SS}=0\text{V}$ unless otherwise specified.

Note 3: I_{OH} and I_{OL} are tested one output at a time.


Note 4: C_{PD} determines the no load AC power consumption of a CMOS device. For a complete explanation, see "MM54C/74C Family Characteristics" Application Note AN-90.

Logic Diagram




Typical Applications


Liquid Crystal (LC) Readout



Incandescent Readout




Light Emitting Diode (LED) Readout




Note: Bipolar transistors may be added for gain (for $V_{DD} \leq 10V$ or $I_{OUT} \geq 10\text{ mA}$)

Typical Applications(Continued)


Fluorescent Readout



Gas Discharge Readout



3½-Digit DVM with LCD Display




Display 9.999when overflowed. All digits can also be blanked at overflow by typing OFL to BI on the CD4543's.




Switching Time Waveforms

CPO MEASUREMENT WAVEFORMS




Inputs Bland Ph low, and inputs D and LD high. f in respect to a system clock.
All outputs connected to respective C loads.


Dynamic Signal Waveforms



Inputs D, Ph and BI Low, and Inputs A, B and LD High



(Inputs D, Ph and BI Low, and inputs A and B Hi




Data DCBA Strobe into Latches



Physical Dimensions


SOP-16



Dimensions In Millimeters(SOP-16)

Symbol:	A	A1	B	C	C1	D	Q	a	b
Min:	1.35	0.05	9.80	5.80	3.80	0.40	0°	0.35	1.27 BSC
Max:	1.55	0.20	10.0	6.20	4.00	0.80	8°	0.45	

DIP-16




Dimensions In Millimeters(DIP-16)

Symbol:	A	B	D	D1	E	L	L1	a	b	c	d
Min:	6.10	18.94	8.10	7.42	3.10	0.50	3.00	1.50	0.85	0.40	2.54 BSC
Max:	6.68	19.56	10.9	7.82	3.55	0.70	3.60	1.55	0.90	0.50	

Physical Dimensions

TSSOP-16



Dimensions In Millimeters(TSSOP-16)									
Symbol:	A	A1	B	C	C1	D	Q	a	b
Min:	0.85	0.05	4.90	6.20	4.30	0.40	0°	0.20	0.65 BSC
Max:	0.95	0.20	5.10	6.60	4.50	0.80	8°	0.25	

About Us

Founded in 2017, Shenzhen Tudi Semiconductor Co., Ltd. specializes in the research and development of semiconductor components. Our product range includes design, constant current driving, power management, amplifiers, comparators, interfaces and drivers, logic devices, EE PROM memory, high and low voltage MOS, time bases and clocks, specialized circuits, and analog and mixed-signal solutions. We are dedicated to becoming a well-known and reliable chip supplier and developer both domestically and internationally. By managing every aspect of our operations, we maintain a comprehensive and scientific quality management system, providing high-quality, cost-effective semiconductor chip solutions and top-notch, comprehensive services.

For more information, visit our official website: www.sztdbdt.com

Important Notice and Disclaimer

Shenzhen Tudi Semiconductor Co., Ltd. is dedicated to providing our customers with accurate and reliable technical and reliability data, which includes datasheets, design resources like reference designs, application guidance, web tools, and safety information among other resources. However, it is crucial to understand that we do not guarantee the absence of defects in this provided information.

All provided information and resources should be verified through actual tests by the users. We do not offer any explicit or implied warranties, which includes, but is not limited to, implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party intellectual property rights.

The resources we provide are intended to assist skilled developers in using Tudi products effectively. This support encompasses selecting the appropriate products for their specific applications, designing, validating, and testing these applications, and ensuring compliance with applicable standards, safety, security, or other requirements.

Please note, Tudi and the Tudi logo are registered trademarks of Shenzhen Tudi Semiconductor Co., Ltd. All other trademarks mentioned belong to their respective owners. For detailed information on any changes, users are encouraged to refer to the revision history included in any updated documents. Be aware that resources may change without prior notice. Shenzhen Tudi Semiconductor Co., Ltd. will not be held responsible for any patent infringement or infringement of third-party intellectual property rights that may arise from the use of our products.