




CEP3205/CEB3205

N-Channel Enhancement Mode Field Effect Transistor

PRELIMINARY

FEATURES

- 55V, 108.5A, $R_{DS(ON)} = 8.5m\Omega$ @ $V_{GS} = 10V$.
- Super high dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handling capability.
- Lead free product is acquired.
- TO-220 & TO-263 package.



ABSOLUTE MAXIMUM RATINGS $T_C = 25^{\circ}C$ unless otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	V_{DS}	55	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	108.5	A
Drain Current-Pulsed ^a	I_{DM}	434	A
Maximum Power Dissipation @ $T_C = 25^{\circ}C$ - Derate above $25^{\circ}C$	P_D	200	W
		1.3	W/ $^{\circ}C$
Operating and Store Temperature Range	T_J, T_{stg}	-55 to 175	$^{\circ}C$

Thermal Characteristics

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	0.75	$^{\circ}C/W$
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	$^{\circ}C/W$

This is preliminary information on a new product in development now .
Details are subject to change without notice .

Rev 1. 2007.Feb
<http://www.cetsemi.com>



CEP3205/CEB3205

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS} = 0V, I_D = 250\mu A$	55			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 55V, V_{GS} = 0V$			25	μA
Gate Body Leakage Current, Forward	I_{GSSF}	$V_{GS} = 20V, V_{DS} = 0V$			100	nA
Gate Body Leakage Current, Reverse	I_{GSSR}	$V_{GS} = -20V, V_{DS} = 0V$			-100	nA
On Characteristics [°]						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS} = V_{DS}, I_D = 250\mu A$	2		4	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 64A$		6.5	8.5	mΩ
Dynamic Characteristics [°]						
Forward Transconductance	g_{FS}	$V_{DS} = 25V, I_D = 64A$		30		S
Input Capacitance	C_{iss}	$V_{DS} = 25V, V_{GS} = 0V, f = 1.0\text{ MHz}$		2940		pF
Output Capacitance	C_{oss}			1030		pF
Reverse Transfer Capacitance	C_{rss}			30		pF
Switching Characteristics [°]						
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 28V, I_D = 62A, V_{GS} = 10V, R_{GEN} = 4.5\Omega$		27	54	ns
Turn-On Rise Time	t_r			14	28	ns
Turn-Off Delay Time	$t_{d(off)}$			56	112	ns
Turn-Off Fall Time	t_f	$V_{DS} = 44V, I_D = 62A, V_{GS} = 10V$		18	36	ns
Total Gate Charge	Q_g			75.2	100	nC
Gate-Source Charge	Q_{gs}			22.9		nC
Gate-Drain Charge	Q_{gd}			20.3		nC
Drain-Source Diode Characteristics and Maximun Ratings						
Drain-Source Diode Forward Current	I_S				108	A
Drain-Source Diode Forward Voltage [°]	V_{SD}	$V_{GS} = 0V, I_S = 64A$			1.3	V
Notes : a.Repetitive Rating : Pulse width limited by maximum junction temperature. b.Pulse Test : Pulse Width ≤ 300μs, Duty Cycle ≤ 2%. c.Guaranteed by design, not subject to production testing.						



CEP3205/CEB3205




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current



CEP3205/CEB3205




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area




Figure 9. Switching Test Circuit




Figure 10. Switching Waveforms




Figure 11. Normalized Thermal Transient Impedance Curve