

# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier

Mimix  
BROADBAND™

August 2006 - Rev 31-Aug-06

CGB7006-SC (-BD)  
RoHS

## Features

- ✕ 33.5 dBm Output IP3 @ 850 MHz
- ✕ 4.1 dB Noise Figure @ 850 MHz
- ✕ 15.2 dB Gain @ 850 MHz
- ✕ 18.0 dBm P1dB @ 850 MHz
- ✕ Low Performance Variation Over Temperature
- ✕ Low Cost: Die Form or SOT-89 Package
- ✕ 100% DC On-Wafer Testing
- ✕ ESD Protection on All Die: >1000V HBM
- ✕ Low Thermal Resistance: <85°C/Watt

## Description


The CGB7006-SC (-BD) is a Darlington Configured, high dynamic range, utility gain block amplifier. Designed for applications operating within the DC to 6.0 GHz frequency range, Mimix's broadband, cascadeable, gain block amplifiers are ideal solutions for transmit, receive and IF applications.

These MMIC amplifiers are available in bare die form or an industry standard SOT-89 package. Mimix's InGaP HBT technology and an industry low thermal resistance offers a thermally robust and reliable gain block solution.

The InGaP HBT die have extra pads to enable thorough DC testing. This unique test capability and the inclusion of ESD protection on all die, significantly enhances the quality, reliability and ruggedness of these products.

With a single bypass capacitor, optional RF choke and two DC blocking capacitors, this gain block amplifier offers significant ease of use in a broad range of applications.

Functional Block Diagram (SOT-89)



## Absolute Maximum Ratings

|                             |                |
|-----------------------------|----------------|
| Max Device Voltage          | +6.0 V         |
| Max Device Current          | 130 mA         |
| Max Device Dissipated Power | 0.65 W         |
| RF Input Power              | +17 dBm        |
| Storage Temperature         | -55°C to 150°C |
| Junction Temperature        | 150°C          |
| Operating Temperature       | -40°C to +85°C |
| Thermal Resistance          | 80° C/W        |
| EDS (HBM)                   | 1000 V         |

Operation of this device above any of these parameters may cause permanent damage.

## Applications

- ✕ PA Driver Amp, IF Amp, LO Buffer Amp
- ✕ Cellular, PCS, GSM, UMTS
- ✕ Wireless Data and SATCOM
- ✕ Transmit and Receive Functions
- ✕ CATV

## Electrical Characteristics

Unless otherwise specified, the following specifications are guaranteed at room temperature in a Mimix test fixture.

| Parameter                                        | Temperature (°C) | 850 MHz |      |      | 1950 MHz |      |      | 2400 MHz |      |      | 3500 MHz |      |      | Units |
|--------------------------------------------------|------------------|---------|------|------|----------|------|------|----------|------|------|----------|------|------|-------|
|                                                  |                  | Min.    | Typ. | Max. | Min.     | Typ. | Max. | Min.     | Typ. | Max. | Min.     | Typ. | Max. |       |
| Small Signal Gain                                | +25              | 14.0    | 15.2 | 16.4 | 13.3     | 14.5 | 15.7 | 13.0     | 14.2 | 15.4 |          | 13.5 |      | dB    |
|                                                  | -40 to +85       | 13.8    | 15.2 | 16.6 | 13.1     | 14.5 | 15.9 | 12.8     | 14.2 | 15.6 |          | 13.5 |      | dB    |
| Output P1dB                                      | +25              | 17.0    | 18.0 |      | 16.5     | 17.5 |      | 15.8     | 16.8 |      |          | 15.5 |      | dBm   |
|                                                  | -40 to +85       | 16.5    | 18.0 |      | 16.2     | 17.5 |      | 15.6     | 16.8 |      |          | 15.5 |      | dBm   |
| Output IP3                                       | +25              | 32.0    | 33.5 |      | 30.5     | 32.0 |      | 29.0     | 30.5 |      |          | 28.0 |      | dBm   |
|                                                  | -40 to +85       | 31.5    | 33.5 |      | 29.5     | 32.0 |      | 28.5     | 30.5 |      |          | 28.0 |      | dBm   |
| Noise Figure                                     | +25              |         | 4.1  | 5.0  |          | 4.1  | 5.0  |          | 4.2  | 5.0  |          | 4.4  |      | dB    |
|                                                  | -40 to +85       |         | 4.1  | 5.3  |          | 4.1  | 5.3  |          | 4.2  | 5.4  |          | 4.4  |      | dB    |
| Operating Current                                | +25              | 60      | 64   | 68   | 60       | 64   | 68   | 60       | 64   | 68   |          | 64   |      | mA    |
|                                                  | -40 to +85       | 57      | 64   | 71   | 57       | 64   | 71   | 57       | 64   | 71   |          | 64   |      | mA    |
| Input Return Loss                                | +25              | 15      | 19   |      | 12       | 17   |      | 13       | 17   |      |          | 12   |      | dB    |
|                                                  | -40 to +85       | 14      | 9    |      | 11       | 17   |      | 12       | 17   |      |          | 12   |      | dB    |
| Output Return Loss                               | +25              | 18      | 25   |      | 12       | 17   |      | 11.0     | 17   |      |          | 19   |      | dB    |
|                                                  | -40 to +85       | 17      | 25   |      | 11       | 17   |      | 10.5     | 17   |      |          | 19   |      | dB    |
| Pout @ -45 dBc, ACP<br>IS-95, 9 Forward Channels | +25              |         | 12   |      |          | 12   |      |          |      |      |          |      |      | dBm   |
|                                                  | -40 to +85       |         | 12   |      |          | 12   |      |          |      |      |          |      |      | dBm   |

Notes: 1. Test Conditions in Mimix eval board,  $V_s = 8$  V,  $I_d = 64$  mA Typ.,  $R_{bias} = 47 \Omega$ ,  $Z_s = Z_L = 50 \Omega$ , OIP3 tone spacing = 1 MHz, Pout per tone = 3 dBm.  
2. Values reflect performance in recommended application circuit.

Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099  
Tel: 281.988.4600 Fax: 281.988.4615 mimixbroadband.com

Page 1 of 8

Characteristic Data and Specifications are subject to change without notice. ©2006 Mimix Broadband, Inc.  
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.

www.DataSheet4U.com






# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier

Mimix  
BROADBAND™

August 2006 - Rev 31-Aug-06

CGB7006-SC (-BD)  
RoHS

## Typical S-Parameter and Noise Performance



Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099  
Tel: 281.988.4600 Fax: 281.988.4615 [mimixbroadband.com](http://mimixbroadband.com)

Page 2 of 8

Characteristic Data and Specifications are subject to change without notice. ©2006 Mimix Broadband, Inc.  
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.



# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier

**Mimix**  
BROADBAND™





August 2006 - Rev 31-Aug-06

**CGB7006-SC (-BD)**  
RoHS

## Typical Power and Linearity Performance



### Linearity Performance - Base Station ACP - IS-95



Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099  
Tel: 281.988.4600 Fax: 281.988.4615 mimixbroadband.com

Page 3 of 8

Characteristic Data and Specifications are subject to change without notice. ©2006 Mimix Broadband, Inc.  
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.

# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier

**Mimix**  
BROADBAND™

August 2006 - Rev 31-Aug-06

**CGB7006-SC (-BD)**  
**RoHS**

**Typical Scattering Parameters** (Vd = +5.08V, Icc = 62 mA, T = 23°C, device in a 50 ohm system)

| Frequency<br>(MHz) | (Mag) | S <sub>11</sub><br>(Ang) | (Mag) | S <sub>21</sub><br>(Ang) | (Mag) | S <sub>12</sub><br>(Ang) | (Mag) | S <sub>22</sub><br>(Ang) |
|--------------------|-------|--------------------------|-------|--------------------------|-------|--------------------------|-------|--------------------------|
| 100                | 0.039 | -174.5                   | 5.99  | 174.90                   | 0.114 | -1.56                    | 0.039 | -10.97                   |
| 200                | 0.041 | -166.2                   | 5.96  | 169.80                   | 0.114 | -3.31                    | 0.041 | -22.43                   |
| 300                | 0.043 | -160.1                   | 5.95  | 164.90                   | 0.114 | -4.91                    | 0.043 | -33.03                   |
| 400                | 0.045 | -155.0                   | 5.92  | 160.00                   | 0.114 | -6.50                    | 0.046 | -41.32                   |
| 500                | 0.048 | -149.6                   | 5.90  | 155.10                   | 0.114 | -8.03                    | 0.050 | -48.80                   |
| 600                | 0.052 | -146.0                   | 5.88  | 150.20                   | 0.115 | -9.64                    | 0.055 | -55.93                   |
| 700                | 0.057 | -143.6                   | 5.86  | 145.30                   | 0.115 | -11.20                   | 0.059 | -62.24                   |
| 800                | 0.062 | -141.6                   | 5.83  | 140.50                   | 0.115 | -12.75                   | 0.063 | -67.62                   |
| 900                | 0.067 | -139.6                   | 5.81  | 135.70                   | 0.116 | -14.43                   | 0.068 | -72.66                   |
| 1000               | 0.073 | -138.8                   | 5.78  | 130.90                   | 0.116 | -16.03                   | 0.074 | -77.48                   |
| 1100               | 0.078 | -138.3                   | 5.75  | 126.10                   | 0.117 | -17.72                   | 0.079 | -81.90                   |
| 1200               | 0.084 | -138.0                   | 5.72  | 121.30                   | 0.117 | -19.43                   | 0.084 | -85.36                   |
| 1300               | 0.091 | -138.1                   | 5.69  | 116.50                   | 0.118 | -21.01                   | 0.089 | -89.25                   |
| 1400               | 0.096 | -138.7                   | 5.66  | 111.80                   | 0.119 | -22.77                   | 0.095 | -92.61                   |
| 1500               | 0.103 | -139.2                   | 5.62  | 107.00                   | 0.120 | -24.47                   | 0.100 | -95.85                   |
| 1600               | 0.110 | -140.0                   | 5.59  | 102.30                   | 0.120 | -26.12                   | 0.105 | -98.76                   |
| 1700               | 0.116 | -141.1                   | 5.55  | 97.63                    | 0.121 | -27.85                   | 0.111 | -101.70                  |
| 1800               | 0.123 | -142.4                   | 5.51  | 92.96                    | 0.122 | -29.71                   | 0.116 | -104.70                  |
| 1900               | 0.129 | -143.7                   | 5.48  | 88.36                    | 0.123 | -31.41                   | 0.122 | -107.40                  |
| 2000               | 0.136 | -145.2                   | 5.44  | 83.74                    | 0.124 | -33.23                   | 0.127 | -110.20                  |
| 2100               | 0.143 | -147.0                   | 5.41  | 79.10                    | 0.125 | -35.03                   | 0.133 | -112.70                  |
| 2200               | 0.149 | -148.7                   | 5.37  | 74.51                    | 0.126 | -36.84                   | 0.139 | -115.50                  |
| 2300               | 0.156 | -150.7                   | 5.33  | 69.96                    | 0.128 | -38.68                   | 0.144 | -118.10                  |
| 2400               | 0.162 | -152.8                   | 5.30  | 65.42                    | 0.129 | -40.59                   | 0.149 | -120.90                  |
| 2500               | 0.168 | -154.9                   | 5.26  | 60.88                    | 0.130 | -42.48                   | 0.155 | -123.70                  |
| 2600               | 0.174 | -157.2                   | 5.22  | 56.41                    | 0.131 | -44.31                   | 0.160 | -126.20                  |
| 2700               | 0.180 | -159.5                   | 5.19  | 51.95                    | 0.133 | -46.20                   | 0.165 | -129.00                  |
| 2800               | 0.186 | -162.1                   | 5.16  | 47.52                    | 0.134 | -48.18                   | 0.171 | -131.90                  |
| 2900               | 0.192 | -165.0                   | 5.13  | 43.08                    | 0.136 | -50.11                   | 0.176 | -135.20                  |
| 3000               | 0.198 | -167.7                   | 5.10  | 38.61                    | 0.137 | -52.05                   | 0.181 | -138.20                  |
| 3100               | 0.203 | -170.6                   | 5.08  | 34.22                    | 0.139 | -54.06                   | 0.187 | -141.40                  |
| 3200               | 0.209 | -173.6                   | 5.05  | 29.77                    | 0.141 | -56.16                   | 0.192 | -144.70                  |
| 3300               | 0.215 | -176.9                   | 5.03  | 25.36                    | 0.142 | -58.20                   | 0.197 | -148.20                  |
| 3400               | 0.221 | -179.6                   | 5.01  | 20.91                    | 0.145 | -60.38                   | 0.202 | -151.80                  |
| 3500               | 0.226 | -176.1                   | 4.98  | 16.48                    | 0.146 | -62.47                   | 0.207 | -155.20                  |
| 3600               | 0.232 | -172.7                   | 4.96  | 12.05                    | 0.148 | -64.69                   | 0.212 | -158.90                  |
| 3700               | 0.237 | -169.0                   | 4.94  | 7.66                     | 0.151 | -66.87                   | 0.216 | -162.70                  |
| 3800               | 0.242 | -165.0                   | 4.93  | 3.24                     | 0.153 | -69.07                   | 0.220 | -167.00                  |
| 3900               | 0.246 | -160.6                   | 4.91  | -1.21                    | 0.155 | -71.40                   | 0.224 | -171.10                  |
| 4000               | 0.251 | -156.4                   | 4.90  | -5.64                    | 0.157 | -73.64                   | 0.227 | -175.40                  |
| 4100               | 0.255 | -152.0                   | 4.89  | -10.07                   | 0.160 | -76.03                   | 0.231 | -180.00                  |
| 4200               | 0.258 | -147.3                   | 4.88  | -14.55                   | 0.162 | -78.46                   | 0.234 | -175.20                  |
| 4300               | 0.262 | -142.2                   | 4.88  | -19.05                   | 0.165 | -80.86                   | 0.237 | -170.10                  |
| 4400               | 0.266 | -137.0                   | 4.88  | -23.58                   | 0.168 | -83.39                   | 0.239 | -164.50                  |
| 4500               | 0.270 | -131.5                   | 4.87  | -28.17                   | 0.171 | -86.02                   | 0.241 | -158.90                  |
| 4600               | 0.273 | -126.1                   | 4.87  | -32.75                   | 0.174 | -88.62                   | 0.244 | -153.00                  |
| 4700               | 0.277 | -120.5                   | 4.87  | -37.38                   | 0.176 | -91.28                   | 0.248 | -147.00                  |
| 4800               | 0.281 | -114.3                   | 4.88  | -42.06                   | 0.180 | -94.09                   | 0.252 | -140.40                  |
| 4900               | 0.287 | -107.8                   | 4.88  | -46.79                   | 0.183 | -96.98                   | 0.256 | -133.50                  |
| 5000               | 0.292 | -101.1                   | 4.88  | -51.64                   | 0.186 | -99.92                   | 0.260 | -126.10                  |

Continues Next Page. S-Parameter Data Files are available online at: [www.mimixbroadband.com](http://www.mimixbroadband.com)

Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099  
Tel: 281.988.4600 Fax: 281.988.4615 [mimixbroadband.com](http://mimixbroadband.com)

Page 4 of 8

Characteristic Data and Specifications are subject to change without notice. ©2006 Mimix Broadband, Inc.  
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.

# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier

**Mimix**  
BROADBAND™

August 2006 - Rev 31-Aug-06

**CGB7006-SC (-BD)**  
**RoHS**

**Typical Scattering Parameters** (Vd = +5.08V, Icc = 62 mA, T = 23°C, device in a 50 ohm system)

| Frequency<br>(MHz) | (Mag) | S <sub>11</sub><br>(Ang) | (Mag) | S <sub>21</sub><br>(Ang) | (Mag) | S <sub>12</sub><br>(Ang) | (Mag) | S <sub>22</sub><br>(Ang) |
|--------------------|-------|--------------------------|-------|--------------------------|-------|--------------------------|-------|--------------------------|
| 5100               | 0.298 | 94.52                    | 4.88  | -56.50                   | 0.189 | -103.0                   | 0.265 | 119.00                   |
| 5200               | 0.304 | 87.85                    | 4.89  | -61.36                   | 0.192 | -106.0                   | 0.271 | 111.70                   |
| 5300               | 0.312 | 80.74                    | 4.89  | -66.39                   | 0.196 | -109.2                   | 0.280 | 103.90                   |
| 5400               | 0.321 | 73.09                    | 4.89  | -71.54                   | 0.199 | -112.5                   | 0.289 | 95.56                    |
| 5500               | 0.331 | 65.45                    | 4.89  | -76.72                   | 0.202 | -115.9                   | 0.298 | 87.18                    |
| 5600               | 0.343 | 58.07                    | 4.88  | -81.88                   | 0.205 | -119.5                   | 0.310 | 79.10                    |
| 5700               | 0.356 | 50.40                    | 4.88  | -87.26                   | 0.208 | -123.0                   | 0.325 | 71.06                    |
| 5800               | 0.370 | 42.60                    | 4.87  | -92.77                   | 0.211 | -126.8                   | 0.341 | 62.28                    |
| 5900               | 0.384 | 34.37                    | 4.84  | -98.37                   | 0.213 | -130.8                   | 0.359 | 53.49                    |
| 6000               | 0.400 | 26.43                    | 4.81  | -104.00                  | 0.215 | -134.6                   | 0.378 | 45.11                    |
| 6100               | 0.418 | 18.66                    | 4.77  | -109.60                  | 0.216 | -138.6                   | 0.400 | 36.81                    |
| 6200               | 0.435 | 11.03                    | 4.72  | -115.40                  | 0.217 | -142.6                   | 0.423 | 28.76                    |
| 6300               | 0.452 | 3.33                     | 4.66  | -121.20                  | 0.218 | -146.8                   | 0.446 | 20.96                    |
| 6400               | 0.470 | -4.49                    | 4.59  | -127.00                  | 0.218 | -151.0                   | 0.472 | 13.18                    |
| 6500               | 0.488 | -12.03                   | 4.50  | -132.90                  | 0.217 | -155.2                   | 0.496 | 5.55                     |
| 6600               | 0.506 | -19.24                   | 4.40  | -138.70                  | 0.215 | -159.4                   | 0.521 | -1.78                    |
| 6700               | 0.523 | -26.11                   | 4.30  | -144.50                  | 0.214 | -163.5                   | 0.545 | -8.68                    |
| 6800               | 0.537 | -32.99                   | 4.19  | -150.30                  | 0.211 | -167.7                   | 0.569 | -15.38                   |
| 6900               | 0.551 | -39.84                   | 4.08  | -156.00                  | 0.208 | -171.8                   | 0.592 | -21.94                   |
| 7000               | 0.565 | -46.61                   | 3.95  | -161.70                  | 0.205 | -175.9                   | 0.614 | -28.48                   |
| 7100               | 0.577 | -52.93                   | 3.81  | -167.20                  | 0.200 | -179.8                   | 0.634 | -34.66                   |
| 7200               | 0.587 | -58.95                   | 3.68  | -172.70                  | 0.196 | 176.3                    | 0.652 | -40.64                   |
| 7300               | 0.595 | -64.82                   | 3.55  | -178.00                  | 0.192 | 172.5                    | 0.668 | -46.24                   |
| 7400               | 0.602 | -70.70                   | 3.42  | 176.70                   | 0.187 | 168.8                    | 0.684 | -51.69                   |
| 7500               | 0.608 | -76.42                   | 3.28  | 171.60                   | 0.182 | 165.2                    | 0.699 | -57.04                   |
| 7600               | 0.615 | -81.75                   | 3.14  | 166.60                   | 0.177 | 161.9                    | 0.712 | -62.18                   |
| 7700               | 0.619 | -86.78                   | 3.01  | 161.70                   | 0.172 | 158.6                    | 0.723 | -67.01                   |
| 7800               | 0.620 | -91.54                   | 2.89  | 157.10                   | 0.167 | 155.5                    | 0.733 | -71.58                   |
| 7900               | 0.621 | -96.31                   | 2.77  | 152.40                   | 0.163 | 152.4                    | 0.741 | -75.96                   |
| 8000               | 0.620 | -101.10                  | 2.65  | 147.80                   | 0.158 | 149.6                    | 0.749 | -80.18                   |
| 8100               | 0.622 | -105.60                  | 2.54  | 143.40                   | 0.154 | 146.6                    | 0.757 | -84.30                   |
| 8200               | 0.621 | -109.60                  | 2.42  | 139.20                   | 0.149 | 143.9                    | 0.764 | -88.24                   |
| 8300               | 0.618 | -113.50                  | 2.32  | 135.00                   | 0.145 | 141.4                    | 0.769 | -91.84                   |
| 8400               | 0.614 | -117.30                  | 2.23  | 131.00                   | 0.141 | 138.8                    | 0.773 | -95.36                   |
| 8500               | 0.609 | -121.30                  | 2.14  | 126.90                   | 0.137 | 136.5                    | 0.777 | -98.78                   |
| 8600               | 0.605 | -125.20                  | 2.05  | 122.90                   | 0.133 | 133.9                    | 0.781 | -102.10                  |
| 8700               | 0.602 | -128.80                  | 1.97  | 119.10                   | 0.130 | 131.7                    | 0.784 | -105.30                  |
| 8800               | 0.596 | -132.00                  | 1.89  | 115.30                   | 0.126 | 129.6                    | 0.787 | -108.40                  |
| 8900               | 0.588 | -135.30                  | 1.81  | 111.50                   | 0.123 | 127.4                    | 0.788 | -111.30                  |
| 9000               | 0.580 | -138.80                  | 1.75  | 107.80                   | 0.121 | 125.4                    | 0.789 | -114.10                  |
| 9100               | 0.573 | -142.40                  | 1.68  | 104.10                   | 0.118 | 123.3                    | 0.790 | -116.90                  |
| 9200               | 0.566 | -145.70                  | 1.61  | 100.40                   | 0.115 | 121.1                    | 0.792 | -119.60                  |
| 9300               | 0.559 | -148.70                  | 1.55  | 96.82                    | 0.112 | 119.2                    | 0.793 | -122.30                  |
| 9400               | 0.549 | -151.50                  | 1.50  | 93.27                    | 0.110 | 117.2                    | 0.795 | -124.90                  |
| 9500               | 0.539 | -154.60                  | 1.44  | 89.72                    | 0.108 | 115.4                    | 0.794 | -127.30                  |
| 9600               | 0.528 | -157.90                  | 1.39  | 86.22                    | 0.106 | 113.5                    | 0.794 | -129.80                  |
| 9700               | 0.520 | -161.00                  | 1.34  | 82.65                    | 0.104 | 111.5                    | 0.795 | -132.20                  |
| 9800               | 0.512 | -163.70                  | 1.29  | 79.26                    | 0.102 | 109.8                    | 0.795 | -134.50                  |
| 9900               | 0.501 | -166.10                  | 1.24  | 75.89                    | 0.100 | 108.0                    | 0.795 | -136.70                  |
| 10000              | 0.487 | -168.60                  | 1.20  | 72.49                    | 0.098 | 106.5                    | 0.795 | -138.90                  |

S-Parameter Data Files are available online at: [www.mimixbroadband.com](http://www.mimixbroadband.com)

Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099  
Tel: 281.988.4600 Fax: 281.988.4615 [mimixbroadband.com](http://mimixbroadband.com)

Page 5 of 8

Characteristic Data and Specifications are subject to change without notice. ©2006 Mimix Broadband, Inc.  
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.



# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier

**Mimix**  
BROADBAND™

August 2006 - Rev 31-Aug-06



**CGB7006-SC (-BD)**  
RoHS

## Application Circuit

Note: This schematic represents the topology of the application circuit recommended by Mimix.

| Recommended Bias Resistor Values for $I_D = 63 \text{ mA}$ |             |             |             |              |
|------------------------------------------------------------|-------------|-------------|-------------|--------------|
| Supply Voltage (V)                                         | 7V          | 8V          | 10V         | 12V          |
| Rbias (R1 Description: 1206 1/4W 1%)                       | 31 $\Omega$ | 47 $\Omega$ | —           | —            |
| Rbias (R1 Description: 1210 1/2W 1%)                       | —           | —           | 78 $\Omega$ | 110 $\Omega$ |

Note: Rbias provides DC bias stability over temperature.



| Ref Designator | Value             | Description                                        | Size        |
|----------------|-------------------|----------------------------------------------------|-------------|
| C1, C2         | 1000 pF           | MCH185A101JK                                       | 0805        |
| C3             | 1.0 $\mu\text{F}$ | VITR 1.0 $\mu\text{F}$ 25V CER<br>CAP 0805 X7R 10% | 0805        |
| L1             | 56 nH             | Coilcraft 0603 CS 10%                              | 0603        |
| R1             |                   | RBias = $(V_s - V_d) / I_d$                        | 1206 / 1210 |
| C4             |                   | DNP (Do Not Place)                                 | N/A         |



Mimix  
BROADBAND™

**CGB7006-SC (-BD)**  
**X RoHS**


Technical drawing of a rectangular component with dimensions in millimeters and inches. The component features a central rectangular body with a trapezoidal feature on top. Dimensions are provided in millimeters (mm) and inches (in).

**Dimensions (mm) and (inches):**

- Overall width: 4.50 [0.177]
- Overall height: 0.71 [0.028]
- Top trapezoidal feature width: 1.73 [0.068]
- Central body height: 2.50 [0.096]
- Central body width: 3.00 [0.118]
- Central body text: XXXXXXX XXXXXX ZYYWW
- Slot 1 width: 0.46 [0.018]
- Slot 2 width: 1.50 [0.059]
- Slot 3 width: 0.76 [0.030]
- Slot 1 offset: 0.41 [0.016]
- Slot 2 offset: 0.99 [0.039]
- Slot 3 offset: 0.71 [0.028]
- Right trapezoidal feature height: 4.41 [0.163]
- Right trapezoidal feature width: 0.38 [0.015]
- Right trapezoidal feature offset: 0.38 [0.015]

**Dimensions in millimeters [inches]**

MARKINGS:  
 XXXXXXX = MIMIX MODEL NO.  
 XXXXXX = WAFER LOT NO.  
 ZYYWW = DATE CODE (YR/WEEK)  
 FIRST LETTER COUNTRY OF ORIGIN IF OTHER THAN USA



A micrograph of the chip layout showing a rectangular die with dimensions 480  $\mu\text{m}$  (width) and 450  $\mu\text{m}$  (height). The layout includes several labeled components: 'RF IN' (two locations), 'GND' (two locations), and 'RF OUT' (one location). The components are arranged within a central rectangular area, with 'RF IN' and 'RF OUT' positioned near the corners and 'GND' components positioned near the center and edges.

Notes:  
RF OUT bonding pad is 75  $\mu\text{m}$  x 155  $\mu\text{m}$ .  
All other pads are 75  $\mu\text{m}$  x 75  $\mu\text{m}$ .



**Caution: ESD Sensitive**  
Appropriate precautions in handling, packaging and testing devices must be observed.

# DC-6.0 GHz InGaP HBT, MMIC or Packaged Matched Gain Block Amplifier



August 2006 - Rev 31-Aug-06

**CGB7006-SC (-BD)**  
**XRoHS**

## Handling and Assembly Information

**CAUTION!** - Mimix Broadband MMIC Products contain gallium arsenide (GaAs) which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- Do not ingest.
- Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.
- Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.

**Life Support Policy** - Mimix Broadband's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President and General Counsel of Mimix Broadband. As used herein: (1) Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user. (2) A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**Package Attachment** - This packaged product from Mimix Broadband is provided as a rugged surface mount package compatible with high volume solder installation. Care should be taken not to apply heavy pressure to the top or base material to avoid package damage. Vacuum tools or other suitable pick and place equipment may be used to pick and place this part. Care should be taken to ensure that there are no voids or gaps in the solder connection so that good RF, DC and ground connections are maintained. Voids or gaps can eventually lead not only to RF performance degradation, but reduced reliability and life of the product due to thermal stress.

**Mimix Lead-Free RoHS Compliant Program** - Mimix has an active program in place to meet customer and governmental requirements for eliminating lead (Pb) and other environmentally hazardous materials from our products. All Mimix RoHS compliant components are form, fit and functional replacements for their non-RoHS equivalents. Lead plating of our RoHS compliant parts is 100% matt tin (Sn) over copper alloy and is backwards compatible with current standard SnPb low-temperature reflow processes as well as higher temperature (260°C reflow) "Pb Free" processes.

## Ordering Information

| Part Number for Ordering | Description                                                                   |
|--------------------------|-------------------------------------------------------------------------------|
| CGB7006-BD               | Bare die in GelPak                                                            |
| CGB7006-SC-0G00          | Matte Tin plated RoHS compliant SOT-89 surface mount package in bulk quantity |
| CGB7006-SC-0G0T          | Matte Tin plated RoHS compliant SOT-89 surface mount package in tape and reel |
| CGB7006-SP-0G00          | Matte Tin plated RoHS compliant SOT-86 surface mount package in bulk quantity |
| CGB7006-SP-0G0T          | Matte Tin plated RoHS compliant SOT-86 surface mount package in tape and reel |
| PB-CGB7006-SC-0000       | Evaluation Board for SOT-89 packaged device with SMA connectors               |
| PB-CGB7006-SP-0000       | Evaluation Board for SOT-86 packaged device with SMA connectors               |

We also offer the plastic packages with SnPb (Tin-Lead) or NiPdAu plating. Please contact your regional sales manager for more information regarding different plating types