


PHASE NOISE (1 Hz BW, typical)



FEATURES

- Frequency Range: 806 - 824 MHz
- Tuning Voltage: 0.5-4.5 Vdc
- MINI-14MS- - Style Package

APPLICATIONS

- Digital Cellular
- VHF Communications
- Portable Terminal Radio

PERFORMANCE SPECIFICATIONS

	VALUE	UNITS
Oscillation Frequency Range	806 - 824	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-109	dBc/Hz
Harmonic Suppression (2nd, typ.)	-35	dBc
Tuning Voltage	0.5-4.5	Vdc
Tuning Sensitivity (avg.)	26	MHz/V
Power Output	-5±4	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	100	pF
Pushing	<1	MHz/V
Pulling (14dB Return Loss, Any Phase)	<4	MHz
Operating Temperature Range	-35 to 85	°C
Package Style	MINI-14MS-LOW	

POWER SUPPLY REQUIREMENTS

Supply Voltage (Vcc, nom.)	5	Vdc
Supply Current (Icc, typ.)	11	mA


All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES


- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS

