




PHASE NOISE (1 Hz BW, typical)



FEATURES

- Frequency Range: 2880 - 2980 MHz
- Tuning Voltage: 0-5 Vdc
- MINI-16-L - Style Package

APPLICATIONS

- Point to Point Radio
- Basestation
- Frequency Synthesizer

PERFORMANCE SPECIFICATIONS

	VALUE	UNITS
Oscillation Frequency Range	2880 - 2980	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-101	dBc/Hz
Harmonic Suppression (2nd, typ.)	-12	dBc
Tuning Voltage	0-5	Vdc
Tuning Sensitivity (avg.)	31	MHz/V
Power Output	3±3	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	50	pF
Pushing	<7	MHz/V
Pulling (14dB Return Loss, Any Phase)	<6	MHz
Operating Temperature Range	-40 to 85	°C
Package Style	MINI-16-L	

POWER SUPPLY REQUIREMENTS

Supply Voltage (Vcc, nom.)	5	Vdc
Supply Current (Icc, typ.)	20	mA


All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES


- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS

