



ISO9001 & ISO14001 & TS16949 **CHILISIN ELECTRONICS CORP.**

**RoHS & Halogen Free & REACH Compliance.**

Form No.: QF-1274  
Edition: 2

## SPECIFICATION FOR APPROVAL

Customer :

Customer P/N:

Drawing No :

Quantity : **0** Pcs. Date : **2017/7/14**

Chilisin P/N : **CPY201212T-100T-NP**

### SPECIFICATION ACCEPTED BY:

COMPONENT  
ENGINEER

ELECTRICAL  
ENGINEER

MECHANICAL  
ENGINEER

APPROVED

REJECTED

#### 奇力新電子股份有限公司

Chilisin Electronics Corp  
No. 29, Alley 301, Tehhsin Rd.,  
Hukou, Hsinchu 303, Taiwan  
TEL : +886-3- 599-2646  
FAX : +886-3- 599-9176  
E-mail : sales@chilisin.com.tw  
http : //www.chilisin.com.tw

#### 東莞奇力新電子有限公司

Chilisin Electronics (Dongguan) Co., Ltd.  
No. 78, Puxing Rd., Yuliangwei Administration Area,  
Qingxi Town, Dongguan City, Guangdong, China  
TEL : +86-769-8773-0251~3  
FAX : +86-769-8773-0232  
E-mail : cect@chilisin.com.tw

#### 奇力新電子(河南)有限公司

Chilisin Electronics (Henan) Co., Ltd.  
XiuWu Xian, industry gathering area  
JiaoZuo, Henan China  
Postal Code:454350  
TEL:+86-391-717-0682  
FAX:+86-391-717-0666

#### 蘇州奇益新電子有限公司

SUZHOU QI YIXIN Electronics Co., Ltd.  
No.143,Song Shan Rd., Suzhou New District,  
Suzhou, China  
Postal Code:215129  
TEL:+86-512-6841-2350  
FAX:+86-512-6841-2356  
E-mail : suzhou@chilisin.com.tw

Drawn by  
**張瑞滿 Rammi**

Checked by  
**邱明傑 Joseph.Chiu**

Approved by  
**鍾瑞民 jacky.chung**



# CPY201212T Series Specification

## 2 || Part Numbering:



**Storage Temperature:**  $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$  (after PCB)

#### 4 || Marking:


No Marking

## 5 Standard Testing Condition

	Unless otherwise specified	In case of doubt
Temperature	Ordinary Temperature(15 to 35°C)	20 to 30°C
Humidity	Ordinary Humidity(25 to 85% RH)	50 to 80 %RH

## CPY201212T Series Specification

### 6 Configuration and Dimensions:



Dimensions in mm

TYPE	CPY201212
A	2.00±0.20
B	1.25±0.20
C	1.25±0.20
D	0.50±0.30

### 7 Electrical Characteristics:

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)Max.	Rated Current (mA)Max.	Tolerance (±%)
CPY201212T-100□-NP	10	1 MHz, 200 mV	0.5	400	20,30

**NOTE:** □-tolerance M=±20% / T=±30%


1. Operating temperature range - 40 °C ~ 105 °C (Including self - temperature rise)
2. Rate Current : Applied the current to coils, the temperature rise shall not be more than 30 °C

"-N" FOR COMPLETELY LEAD FREE TYPE (INCLUDING FERRITE BODY & SOLDER)

## CPY201212T Series Specification

### 8 CPY201212T Series

#### 8.1 Construction:



#### 8.2 Material List:

No	Part	Material
1	Ferrite Substance	NiO-CuO-ZnO-Ferrite
2	Silver electrode	Ag
3	Silver electrode	Ag
4	Cu plating	Cu
5	Ni plating	Ni
6	Sn plating	Sn

## CPY201212T Series Specification

### 9 Reliability Of Ferrite Multilayer Chip Inductor


#### 1-1.Mechanical Performance

No	Item	Specification	Test Method
1-1-1	Flexure Strength	The forces applied on the right conditions must not damage the terminal electrode and the ferrite	Test device shall be soldered on the substrate Substrate Dimension: 100x40x1.6mm Deflection: 2.0mm Keeping Time: 30sec *For 100505, substrate dimension is 100x40x0.8mm
1-1-2	Vibration		Test device shall be soldered on the substrate Oscillation Frequency: 10 to 55 to 10Hz for 1min Amplitude: 1.5mm Time: 2hrs for each axis (X, Y & Z), total 6hrs
1-1-3	Resistance to Soldering Heat	Appearance: No damage More than 75% of the terminal electrode should be covered with solder. Inductance: within $\pm 20\%$ of initial value	Pre-heating: 150°C, 1min Solder Composition: Sn/Ag3.0/Cu0.5(Pb-Free) Solder Temperature: 260 $\pm 5$ °C Immersion Time: 10 $\pm 1$ sec
1-1-4	Solder ability	The electrodes shall be at least 95% covered with new solder coating	Pre-heating: 150°C, 1min Solder Composition: Sn/Ag3.0/Cu0.5(Pb-Free) Solder Temperature: 245 $\pm 5$ °C (Pb-Free) Immersion Time: 4 $\pm 1$ sec

#### 1-2.Environmental Performance

No	Item	Specification	Test Method		
1-2-1	Temperature Cycle	Appearance: No damage Inductance:within±20% of initial value	One cycle:		
			Step	Temperature (°C)	Time (min)
			1	-40±3	30
			2	25±2	3
			3	105±3	30
			4	25±2	3
			Total: 100cycles		
1-2-2	Humidity Resistance	Measured after exposure in the room condition for 24hrs			
		Temperature: 40±2°C Relative Humidity: 90 ~ 95% / Time: 1000hrs Measured after exposure in the room condition for 24hrs			
1-2-3	High Temperature Resistance	Temperature: 85±3°C Relative Humidity: 20% Applied Current: Rated Current / Time: 1000hrs Measured after exposure in the room condition for 24hrs			
		Temperature: -40±3°C Relative Humidity: 0% / Time: 1000hrs Measured after exposure in the room condition for 24hrs			
1-2-4	Low Temperature Resistance				

## CPY201212T Series Specification



Lead-Free(LF) 標準溫度分析範圍

Refer to J-STD-020C

管制項目 Item.	升温區 Ramp-up	預熱區 Pre-heating	迴焊區 Reflow	Peak Temp	冷卻區 Cooling
溫度範圍 Temp. scope	R.T. ~ 150°C	150°C ~ 200°C	217°C	260±5°C	Peak Temp. ~ 150°C
標準時間 Time spec.	—	60 ~ 180 sec	60 ~ 150 sec	20 ~ 40 sec	—
實際時間 Time result	—	75 ~ 100 sec	90 ~ 120 sec	20 ~ 35 sec	—

NOTE :


1. Re-flow possible times : within 2 times
2. Nitrogen adopted is recommended while in re-flow

## CPY201212T Series Specification

### 10 Packaging:

#### 10.1 Packaging -Cover Tape


The force for tearing off cover tape is 10 to 100 grams in the arrow direction.



#### 10.2 Packaging Quantity

TYPE	PCS/REEL
CP160808	4000
CP201209	4000
CP201212	3000
CP 321611	3000

#### 10.3 Reel Dimensions



Dimensions in mm


TYPE	A	B	C	D
CP Series	178	60	12	1.5




## CPY201212T Series Specification

### 10 Packaging:

#### 10.4 Tape Dimensions in mm



### 11 Recommended Land Pattern:



Dimensions in mm

TYPE	A	B	C
CP160808	0.7 ~ 0.8	1.8 ~ 2.0	0.6 ~ 0.8
CP201209	1.0 ~ 1.2	2.6 ~ 4.0	1.0 ~ 1.2
CP201212	1.0 ~ 1.2	2.6 ~ 4.0	1.0 ~ 1.2
CP321611	2.0	4.2 ~ 5.2	1.2

### 12 Note:

1. Please make sure that your product has been evaluated and confirmed against your specifications when our product is mounted to your product.
2. Do not knock nor drop.
3. All the items and parameters in this product specification have been prescribed on the premise that our product is used for the purpose, under the condition and in the environment agreed upon between you and us. You are requested not to use our product deviating from such agreement.
4. Please keep the distance between transformer/coil and other components (refer to the standard IEC 950)
5. The moisture sensitivity level (MSL) of products is classified as level 1.





ISO9001 & ISO14001 & TS16949 **CHILISIN ELECTRONICS CORP.**

## CPY201212T Series Specification

**13** Graph: CPY201212T-100T-NP

