#### CR5F-010 SERIES

# SILICON GLASS PASSIVATED JUNCTION FAST RECOVERY RECTIFIER

5.0 AMP, 100 THRU 1000 VOLT





www.centralsemi.com

# **DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CR5F-010 series types are axial lead silicon rectifiers designed for DC power supply and inverter applications where fast recovery times are needed.

**MARKING: FULL PART NUMBER** 

<b>MAXIMUM RATINGS:</b> (T <sub>A</sub> =25°C unless otherwise noted)		CR5F						
• **	SYMBOL	<u>-010</u>	<u>-020</u>	<u>-040</u>	-060	<u>-080</u>	<u>-100</u>	UNITS
Peak Repetitive Reverse Voltage	$V_{RRM}$	100	200	400	600	800	1000	V
DC Blocking Voltage	$v_R$	100	200	400	600	800	1000	V
RMS Reverse Voltage	V <sub>R(RMS)</sub>	70	140	280	420	560	700	V
Average Forward Current (T <sub>A</sub> =55°C)	IO			5	.0			Α
Peak Forward Surge Current	IFSM			12	25			Α
Operating and Storage Junction Temperature	T <sub>J</sub> , T <sub>stg</sub>			-65 to	+150			°C

### **ELECTRICAL CHARACTERISTICS:** (T<sub>A</sub>=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MAX	UNITS
$I_{R}$	$V_R$ =Rated $V_{RRM}$	5.0	μΑ
$I_{R}$	V <sub>R</sub> =Rated V <sub>RRM</sub> , T <sub>A</sub> =100°C	100	μΑ
$V_{F}$	I <sub>F</sub> =5.0A	1.3	V
t <sub>rr</sub>	I <sub>F</sub> =0.5A, I <sub>R</sub> =1.0A, I <sub>rr</sub> =0.25A (100V, 200V, 400V)	150	ns
t <sub>rr</sub>	I <sub>F</sub> =0.5A, I <sub>R</sub> =1.0A, I <sub>rr</sub> =0.25A (600V)	250	ns
t <sub>rr</sub>	I <sub>E</sub> =0.5A, I <sub>R</sub> =1.0A, I <sub>rr</sub> =0.25A (800V, 1000V)	500	ns


#### **CR5F-010 SERIES**

# SILICON GLASS PASSIVATED JUNCTION FAST RECOVERY RECTIFIER

5.0 AMP, 100 THRU 1000 VOLT



# **DO-201AD CASE - MECHANICAL OUTLINE**



DIMENSIONS					
	INC	HES	MILLIMETERS		
SYMBOL	MIN	MAX	MIN	MAX	
Α	1.000	-	25.40	-	
В	0.283	0.375	7.20	9.53	
С	0.189	0.210	4.80	5.33	
D	0.047	0.052	1.20	1.32	

DO-201AD (REV: R1)

MARKING: FULL PART NUMBER

#### **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

#### REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### **CONTACT US**

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

**Worldwide Distributors:** 

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <a href="https://www.centralsemi.com/terms">www.centralsemi.com/terms</a>

www.centralsemi.com (001)



# Product End of Life Notification

PDN ID:	PDN01057
<b>Notification Date:</b>	8/19/16
Last Buy Date:	2/19/17
Last Shipment Date	8/19/17

Summary: The CR5F-010 series of Fast Recovery Rectifiers, with the exception of CR5F-060 and CR5F-100, are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement
CR5F-010 BK	CR5F-060 BK
CR5F-020 BK	CR5F-060 BK
CR5F-040 BK	CR5F-060 BK
CR5F-080 BK	CR5F-100 BK
CR5F-120 BK	CR5F-100 BK

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002