




Isolation Transformers

For Analog Devices ADuM4070
Isolated Switching Regulator



- Developed to work with Analog Devices ADuM4070 Isolated switching regulator with integrated feedback
- Power rating: 2 Watts
- 5000 Vrms, one second isolation from primary to secondary.

Core material Ferrite

Terminations Tin-silver-copper over tin over nickel over phos bronze

Weight 10.1 g

Ambient temperature -40°C to +125°C

Storage temperature Component: -40°C to +125°C.

Tape and reel packaging: -40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 175 per 13" reel Plastic tape: 44 mm wide, 0.4 mm thick, 32 mm pocket spacing, 11.9 mm pocket depth

PCB washing Tested with pure water or alcohol only. For other solvents, see Doc787_PCB_Washing.pdf

Part number ¹	Inductance ² min (μH)	Turns ratio	Pri / output voltages				DCR max (Ohms) ³		Leakage inductance ⁴ max (μH)	Volt-time product ⁵ (V-μsec)
			pri	output (pin5)	output (pins 6 & 8)	output (pin 7)	pri	sec		
CR7983-CL_	256	1 : 2	5 V	+3.3 to +15 V	0 V	No output	0.190	0.350	0.75	18.0
CR7984-CL_	256	1 : 3	5 V	+12 to +24 V	+6 to +12 V	0 V	0.170	0.450	0.75	18.0
CR7985-CL_	256	1 : 5	5 V	+5 to +15 V	0 V	-5 to -15 V	0.170	2.00	0.72	18.0

1. When ordering, please specify a **packaging** code:

CR7985-CLD

Packaging: D = 13" machine ready reel. EIA-481 embossed plastic tape (175 per full reel).

B = Less than full reel. In tape, but not machine ready.
To have a leader and trailer added (\$25 charge), use code letter D instead.

2. Inductance is for the primary, measured from pins 12–11 at 1 kHz, 0.1 Vrms.



3. DCR is for each winding of the primary and secondary.

4. Leakage inductance is for the primary windings, measured from pins 12–11 with all secondary windings shorted.

5. Based on V_{IN} max, F_{SW} min and number of primary turns

6. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



Analog Devices is a trademark of Analog Devices, Inc.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 1090 Revised 05/03/13

© Coilcraft Inc., 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.