CSHD8-60 CSHD8-100 CSHD8-200

SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 8.0 AMP, 60 THRU 200 VOLT



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CSHD8-60, CSHD8-100 and CSHD8-200 are silicon Schottky rectifiers with an 8.0 Amp forward current rating and a very high reverse voltage capability. The reverse capability of these devices makes them the ideal solution for high efficiency, high voltage applications such as solid state lighting, DC-DC converters, and a host of other power management uses.

MARKING: FULL PART NUMBER



FEATURES:

- · High reverse voltage capability
- Energy efficient, low forward voltage (V_F)
- · Low reverse leakage at elevated temperature
- · High surge capability

MAXIMUM RATINGS: (T _A =25°C) Peak Repetitive Reverse Voltage	SYMBOL V _{RRM}	CSHD8-60 60	CSHD8-100 100	200	UNITS V
DC Blocking Voltage	V_{R}	60	100	200	V
RMS Reverse Voltage	V _{R(RMS)}	42	70	140	V
Average Forward Current (T _L =75°C)	lo		8.0		Α
Peak Forward Surge Current, tp=8.3ms	IFSM		85		Α
Voltage Rate of Change (Rated V _R)	dv/dt		10,000		V/µs
Operating and Storage Junction Temperature	T _J , T _{stg}		-65 to +175		°C
Typical Thermal Resistance	Θ_{JI}		5.0		°C/W


ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted) SYMBOL **TEST CONDITIONS UNITS** V_R=Rated V_{RRM} 50 I_R μΑ I_R V_R=Rated V_{RRM}. T_J=100°C 20 mΑ I_F=8.0A (CSHD8-60) 0.75 ٧ V_{F} I_F=8.0A (CSHD8-100) 0.80 V_{F} V V_{F} I_F=8.0A (CSHD8-200) 0.90


CSHD8-60 CSHD8-100 CSHD8-200

SURFACE MOUNT SILICON **SCHOTTKY RECTIFIERS** 8.0 AMP, 60 THRU 200 VOLT



DPAK CASE - MECHANICAL OUTLINE






LEAD CODE:

- 1) Anode
- 2) Cathode 3) Anode
- 4) Cathode

Pin 2 is common to the tab (4)

MARKING: FULL PART NUMBER




DIMENSIONS							
	INCHES		MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
Α	0.083	0.108	2.10	2.75			
В	0.016	0.032	0.40	0.81			
С	0.035	0.063	0.89	1.60			
D	0.203	0.228	5.15	5.79			
E	0.020	-	0.51	-			
F	0.018	0.024	0.45	0.60			
G	0.051	0.071	1.30	1.80			
Н	0.248	0.268	6.30	6.81			
J	0.197	0.217	5.00	5.50			
K	0.209	0.245	5.30	6.22			
L	0.025	0.040	0.64	1.02			
М	0.090	0.115	2.30	2.91			
N	0.012	0.045	0.30	1.14			
Р	0.180		4.60				
R	0.090		2.30				
DPAK (REV: R0)							

DPAK (REV: R0)

R4 (11-June 2015)

CSHD8-60 CSHD8-100 CSHD8-200





SERVICES

- · Bonded Inventory
- · Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development/Multi Discrete Modules (MDM™)
- · Bare Die Available for Hybrid Applications

LIMITATIONS AND DAMAGES DISCLAIMER: In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R4 (11-June 2015)