

Power Supplies

DC to AC Inverters

For 1 Bulb, 5W Diming

CXA Series CXA-L0612A-VJL

This DC to AC inverter unit is designed for dimming-type cold cathode lamps. This inverter can be used for lighting a wide range of single cold cathode fluorescent lamps.


FEATURES

- Use of output current control avoids effects resulting from input voltage, load, and distributed capacitance variation.
- This inverter unit is appropriate for use with 6 to 13 inch LCDs since the typical open circuit voltage(initial lamp ignition voltage) is 1.8kVrms.
- Safe design that includes a built-in overcurrent protection element.
- Insulation is simplified due to flat backside surface of board.
- Excellent inverter for ignition of U-shaped cold cathode fluorescent lamps.

TEMPERATURE AND HUMIDITY RANGES

Temperature range	Operating	0 to +60°C
	Storage	-20 to +85°C
Humidity range		95(%)RH max.
		[Maximum wet-bulb temperature:38°C]

SHAPES AND DIMENSIONS



*1 Substrate(PWB: Printed wiring board): Inflammable material UL94V-0(FR-4 or CEM-3) t=1mm

*2 CN1: Molex Japan Co., Ltd. 53261-0510

*3 CN2: Japan Solderless Terminal Co., Ltd. SM02(8.0)B-BHS-1

Weight: 14.5g typ.

Dimensions in mm


TERMINAL NUMBERS AND FUNCTIONS

CN1

Terminal No.	Functions
CN1-1	V _{in} Input voltage E _{dc} :9.6 to 15V
CN1-2	GND 0V
CN1-3	V _{rrmt} Reote voltage E _{dc} :0/5 to 15V[5 to 15V operating]
CN1-4	V _{br} Brightness dimmer voltage E _{dc} :0 to 4V [0V maximum brightness]
CN1-5	NC Do not connect. Used by internal circuitry.

CN2

Terminal No.	Functions
CN2-1	V _{HIGH} Output [High voltage] Irms:1.6 to 6mA
CN2-2	NC
CN2-3	V _{LOW} Output[Low voltage]:(2V)



Power Supplies

DC to AC Inverters

For 1 Bulb, 5W Diming


CXA Series CXA-L0612A-VJL

ELECTRICAL CHARACTERISTICS


Item			Specifications			Conditions				Brightness
			min.	typ.	max.	Vin(V)	Vbr(V)	Ta(°C)	RL(kΩ)	
Output current	Irms(mA)	Iout	5.3	6	6.7	9.6 to 15	0	0 to +60	90 to 130	Maximum
			5.4	6	6.6	9.6 to 15	0	23±5	100	Maximum
			1.3	1.6	1.9	9.6 to 15	4	23±5	520	Minimum
Input current	Idc(A)	Iin	—	0.4	0.65	12	0	0 to +60	90 to 130	
Oscillation frequency	(kHz)	FL	48	58	68	9.6 to 15	0	0 to +60	90 to 130	
Open circuit output voltage	Erms(V)	Vopen	1500	1800	—	9.6 to 15	0 to 3	0 to +60	∞	

TYPICAL CONNECTIONS


EXAMPLE OF VOLTAGE DIMMER CONTROL



EXAMPLE OF POTENTIOMETER DIMMER CONTROL



NO DIMMER CONTROL



*1 Vrmt (remote voltage) shall be ON after Vin was ON.

*2 SW a:ON, b:OFF

OUTPUT CURRENT vs. BRIGHTNESS DIMMER VOLTAGE CHARACTERISTICS

