

PSoC™ Automotive Multitouch generation 7L

Datasheet Summary

Note that this is a Summary Datasheet. To access the full version of this datasheet, register in [My Infineon Collaboration Platform \(MyICP\)](#).

Features

- Automotive Electronics Council (AEC)-Q100 qualified
- Single-chip system solution that integrates touch controller with MCU functions
- Target Application
 - Entry and mid-level central information display (CID) systems
- 32-bit MCU subsystem
 - 48-MHz Arm® Cortex®-M0+ CPU
 - 12-bit SAR ADC for system monitoring (voltage, temperature) and other features (such as day/night sensor)
 - Four timer counter pulse width modulators (TCPWMs)
 - Three serial communication blocks (SCBs) that can be individually configured as SPI/I²C/UART
 - Up to 48 KB flash for user-specific system MCU functionality
 - Up to 4 KB SRAM for user-specific system MCU functionality
 - Up to 29 programmable GPIO pins with interrupt functionality
- Multitouch capacitive touchscreen controller
 - Register-configurable
 - Noise-suppression technologies for display and EMI
 - Effective 20 V drive for higher signal-to-noise ratio (SNR)^[1]
 - Auto armor technology improves both electromagnetic emissions and immunity
 - External display synchronization
 - Water rejection and wet-finger tracking using dual sense capability
 - Multitouch glove with automatic mode switching
 - Ten fingers with thin glove (≤ 1 mm thick)
 - Two fingers with thick glove (≤ 5 mm thick)
 - Large object rejection
 - Automatic baseline tracking to environmental changes
 - Low-power look-for-touch mode
 - Field upgrades via bootloader
 - Touchscreen sensor self-test
 - Low-power CAPSENSE™ wake-up button with power consumption of 50 µA
 - Low-power wake-on-touchscreen with power consumption of 120 µA

Note

1. Effective voltage when using 17 multi-phase TX and 5 V V_{CCTX} supply.

Features

- System performance (configuration dependent)
 - Screen sizes up to 11-inch diagonal
 - 5 mm electrode pitch; 8:3 aspect ratio
 - Screen sizes up to 12.3-inch diagonal
 - 5.7 mm electrode pitch; 8:3 aspect ratio
 - Up to 72 sense pins supporting different aspect ratios, up to 1200 intersections (46 × 26)
 - Reports up to ten fingers
 - Small finger support down to 4 mm
 - Refresh rate up to 250 Hz; other rates configurable
 - TX frequency up to 350 kHz
- Power (configuration-dependent)
 - 1.71 V to 1.95 V and 3.0 V to 5.5 V logic and digital I/Os supply
 - 3.0 V to 5.5 V analog supply
 - 20 mW average power
 - 20 µW typical Deep Sleep power
- Sensor and system design (configuration-dependent)
 - Supports a variety of touchscreen sensors and stackups
 - Manhattan, diamond
 - Sensor-on-lens (SOL)
 - On-cell
 - Plastic (PET) and glass-sensor substrates
 - LCD, AMOLED, and IPS displays
 - Metal mesh
- Communication interface
 - I²C slave at 100 kbps, 400 kbps, 1 Mbps, and 3.4 Mbps
 - SPI slave bit rates up to 8 Mbps
- Development and debug environment
 - Arm® MDK for system MCU
 - Touch tuning host emulator (TTHE) to configure touch
 - MTK for debugging
 - PSoC™ programmer for programming
- Packages
 - 100LD TQFP 14 × 14 × 1.4 mm (0.5 mm pitch)
 - 128LD TQFP 14 × 20 × 1.4 mm (0.5 mm pitch)
- Ambient temperature range
 - Automotive-A: -40°C to 85°C
 - Automotive-S: -40°C to 105°C


1 Ordering information

Table 1 lists the CYAT817L touchscreen controllers.

Table 1 **Ordering information**

Product	Number of sense pins	No. of fingers	Touch only	Touch+ MCU functions	No. of GPIOs	Package	Temperature
CYAT817L-100AA72	72	10	✓	–	13	100LD TQFP	–40°C to +85°C
CYAT817L-100AS72	72	10	✓	–	13	100LD TQFP	–40°C to +105°C
CYAT817LS-100AA72	72	10	–	✓	13	100LD TQFP	–40°C to +85°C
CYAT817LS-100AS72	72	10	–	✓	13	100LD TQFP	–40°C to +105°C
CYAT817L-128AA72	72	10	✓	–	29	128LD TQFP	–40°C to +85°C
CYAT817L-128AS72	72	10	✓	–	29	128LD TQFP	–40°C to +105°C
CYAT817LS-128AA72	72	10	–	✓	29	128LD TQFP	–40°C to +85°C
CYAT817LS-128AS72	72	10	–	✓	29	128LD TQFP	–40°C to +105°C

1.1 Ordering code definitions



Revision history

Document revision	Date	Description of changes
**	2022-07-26	Initial release.
*A	2024-05-21	Updated Package information in Features . Updated Package information in Table 1 . Updated template. Updated to reflect correct metadata.
*B	2024-08-02	No content updates. Only ECN metadata updated.

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2024-08-02

Published by

**Infineon Technologies AG
81726 Munich, Germany**

**© 2024 Infineon Technologies AG.
All Rights Reserved.**

Do you have a question about this document?

Email:
erratum@infineon.com

**Document reference
002-35927 Rev. *B**

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.