

## Low Voltage, 0.6 $\Omega$ , Dual SPDT Analog Switch

### DESCRIPTION

The DG2735A is low voltage, low on-resistance, dual single-pole/double-throw (SPDT) monolithic CMOS analog switches designed for high performance switching of analog signals. Combining low-power, high speed, low on-resistance, and small package size, the DG2735A is ideal for portable and battery power applications.

The DG2735A have an operation range from 1.65 V to 4.3 V single supply. The DG2735A has two separate control pins with for the separated two SPDT switched.

The DG2735A is guaranteed 1.65 V logic compatible, allowing the easy interface with low voltage DSP or MCU control logic and ideal for one cell Li-ion battery direct power.

The switch conducts signals within power rails equally well in both directions when on, and blocks up to the power supply level when off. Break-before-make is guaranteed.

The DG2735A is built on Vishay Siliconix's sub micron CMOS low voltage process technology and provides greater than 300 mA latch-up protection, as tested per JESD78.

As a committed partner to the community and the environment, Vishay Siliconix manufactures this product with lead (Pb)-free device terminations. DG2735A is offered in a miniQFN package. The miniQFN package has a nickel-palladium-gold device termination and is represented by the lead (Pb)-free "-E4" suffix. The nickel-palladium-gold device terminations meet all JEDEC standards for reflow and MSL ratings.

### FEATURES

- Low voltage operation (1.65 V to 4.3 V)
- Low on-resistance -  $R_{ON}$ : 0.6  $\Omega$  at 2.7 V
- Fast switching:  $t_{ON}$  = 64 ns at 2.7 V  
 $t_{OFF}$  = 42 ns at 2.7 V
- Latch-up current > 300 mA (JESD78)
- **Halogen-free according to IEC 61249-2-21 definition**
- **Compliant to RoHS directive 2002/95/EC**



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**


### BENEFITS

- Reduced power consumption
- High accuracy
- Reduce board space
- TTL/1.65 V logic compatible

### APPLICATIONS

- Cellular phones
- Speaker headset switching
- Audio and video signal routing
- PCMCIA cards
- Battery operated systems
- Portable media player handheld test instruments

### FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION



**TRUTH TABLE**

Logic	NC	NO
0	ON	OFF
1	OFF	ON

**ORDERING INFORMATION**

Temp. Range	Package	Part Number
- 40 °C to 85 °C	miniQFN10	DG2735ADN-T1-GE4

**ABSOLUTE MAXIMUM RATINGS** ( $T_A = 25\text{ °C}$ , unless otherwise noted)

Parameter	Symbol	Limit	Unit
Reference to GND	$V_+$	- 0.3 to 5.0	V
	IN, COM, NC, NO <sup>a</sup>	- 0.3 to ( $V_+ + 0.3$ )	
Current (Any terminal except NO, NC or COM)		30	mA
Continuous Current (NO, NC, or COM)		$\pm 250$	
Peak Current (Pulsed at 1 ms, 10 % duty cycle)		$\pm 500$	
Storage Temperature (D Suffix)		- 65 to 150	°C
Power Dissipation (Packages) <sup>b</sup>	miniQFN10 <sup>c</sup>	208	mW

Notes:

a. Signals on NC, NO, or COM or IN exceeding  $V_+$  will be clamped by internal diodes. Limit forward diode current to maximum current ratings.

b. All leads welded or soldered to PC board.

c. Derate 4.0 mW/°C above 70 °C.

**SPECIFICATIONS** ( $V_+ = 3\text{ V}$ )

Parameter	Symbol	Test Conditions Unless Otherwise Specified V+ = 3 V, ± 10 %,VIN = 0.4 V or 1.65 V <sup>e</sup>	Temp. <sup>a</sup>	Limits - 40 °C to 85 °C			Unit
				Min. <sup>b</sup>	Typ. <sup>c</sup>	Max. <sup>b</sup>	
Analog Switch							
Analog Signal Range <sup>d</sup>	VANALOG	rDS(on)	Full	0		V+	V
On-Resistance	RDS(on)	V+ = 2.7 V, INO/NC = 100 mA, VCOM = 0.5 V	Room		0.5	0.6	Ω
		V+ = 2.7 V, INO/NC = 100 mA, VCOM = 1.5 V					
		V+ = 2.7 V, INO/NC = 100 mA, VCOM = 0.5 V	Full		0.6		
		V+ = 2.7 V, INO/NC = 100 mA, VCOM = 1.5 V					
		V+ = 4.3 V, INO/NC = 100 mA, VCOM = 0.9 V	Room		0.4	0.5	
		V+ = 4.3 V, INO/NC = 100 mA, VCOM = 2.5 V					
		V+ = 4.3 V, INO/NC = 100 mA, VCOM = 0.9 V	Full		0.4		
		V+ = 4.3 V, INO/NC = 100 mA, VCOM = 2.5 V					
RON Match <sup>d</sup>	ΔRON	V+ = 2.7 V, INO/NC = 100 mA, VCOM = 0.5 V, 1.5 V	Room		0.06	0.08	
		V+ = 4.3 V, INO/NC = 100 mA, VCOM = 0.9 V, 2.5 V					
RON resistance flatness <sup>d</sup>	RON flatness	V+ = 2.7 V, INO/NC = 100 mA, VCOM = 0.5 V, 1.5 V	Room			0.15	
Switch Off Leakage Current	INO/NC(off)	V+ = 4.3 V, VNO/NC = 0.3 V/4.0 V, VCOM = 4.0 V/0.3 V	Room	- 10		10	nA
			Full	- 50		50	
	ICOM(off)		Room	- 10		10	
			Full	- 50		50	
Channel-On Leakage Current	ICOM(on)	V+ = 4.3 V, VNO/NC = VCOM = 4.0 V/0.3 V	Room	- 20		20	
			Full	- 100		100	
Digital Control							
Input High Voltage	VINH		Full	1.65			V
Input Low Voltage	VINL		Full			0.4	
Input Capacitance	CIN		Full		6		pF
Input Current	IINL or IINH	VIN = 0 or V+	Full	- 1		1	μA





SPECIFICATIONS (V+ = 3 V)							
Parameter	Symbol	Test Conditions Unless Otherwise Specified V+ = 3 V, ± 10 %,V <sub>IN</sub> = 0.4 V or 1.65 V <sup>e</sup>	Temp. <sup>a</sup>	Limits - 40 °C to 85 °C			Unit
				Min. <sup>b</sup>	Typ. <sup>c</sup>	Max. <sup>b</sup>	
Dynamic Characteristics							
Break-Before-Make Time <sup>e</sup>	t <sub>BBM</sub>	V+ = 3.6 V, V <sub>NO</sub> , V <sub>NC</sub> = 1.5 V, R <sub>L</sub> = 50 Ω, C <sub>L</sub> = 35 pF	Room	1	11		ns
Turn-On Time <sup>e</sup>	t <sub>ON</sub>		Room		44	75	
			Full			80	
Turn-Off Time <sup>e</sup>	t <sub>OFF</sub>		Room		26	55	
			Full			60	
Off-Isolation <sup>d</sup>	O <sub>IRR</sub>	R <sub>L</sub> = 50 Ω, C <sub>L</sub> = 5 pF, f = 100 kHz	Room		- 70		dB
Crosstalk <sup>d</sup>	X <sub>TALK</sub>				- 70		
3dB bandwidth <sup>d</sup>		R <sub>L</sub> = 50 Ω, C <sub>L</sub> = 5 pF	Room		30		MHz
NO, NC Off Capacitance <sup>d</sup>	C <sub>NO(off)</sub>	V <sub>IN</sub> = 0 V, or V+, f = 1 MHz	Room		52		pF
	C <sub>NC(off)</sub>				52		
Channel On Capacitance <sup>d</sup>	C <sub>NO(on)</sub>				168		
	C <sub>NC(on)</sub>				168		
Power Supply							
Power Supply Range	V+			1.65		4.3	V
Power Supply Current	I+	V <sub>IN</sub> = 0 or V+	Full			1.0	μA

Notes:


- Room = 25 °C, Full = as determined by the operating suffix.
- The algebraic convention whereby the most negative value is a minimum and the most positive a maximum, is used in this data sheet.
- Typical values are for design aid only, not guaranteed nor subject to production testing.
- Guarantee by design, not subjected to production test.
- V<sub>IN</sub> = input voltage to perform proper function.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


## TYPICAL CHARACTERISTICS (T<sub>A</sub> = 25 °C, unless otherwise noted)




**TYPICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$ , unless otherwise noted)




**$R_{ON}$  vs.  $V_{COM}$  and Single Supply Voltage**




**$R_{ON}$  vs.  $V_{COM}$  and Single Supply Voltage**




**$R_{ON}$  vs.  $V_{COM}$  and Single Supply Voltage**



**$I_+$  - Supply Current vs. Temperature**








**Supply Current vs.  $V_{IN}$**




**Supply Current vs. Switching Frequency**

**TYPICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$ , unless otherwise noted)




### TEST CIRCUITS




$C_L$  (includes fixture and stray capacitance)

$$V_{OUT} = V_{COM} \left( \frac{R_L}{R_L + R_{ON}} \right)$$




Logic "1" = Switch On  
Logic input waveforms inverted for switches that have the opposite logic sense.

**Figure 1. Switching Time**





$C_L$  (includes fixture and stray capacitance)




**Figure 2. Break-Before-Make Interval**

## TEST CIRCUITS




IN depends on switch configuration: input polarity determined by sense of switch.

**Figure 3. Charge Injection**




**Figure 4. Off-Isolation**



**Figure 5. Channel Off/On Capacitance**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?67590](http://www.vishay.com/ppg?67590).

## MINI QFN-10L CASE OUTLINE



DIM	MILLIMETERS			INCHES		
	MIN.	NAM.	MAX.	MIN.	NAM.	MAX.
A	0.50	0.55	0.60	0.0197	0.0217	0.0236
A1	0.00	-	0.05	0.000	-	0.002
b	0.15	0.20	0.25	0.006	0.008	0.010
c	0.15 REF			0.006 REF		
D	1.75	1.80	1.85	0.069	0.071	0.073
E	1.35	1.40	1.45	0.053	0.055	0.057
e	0.40 BSC			0.016 BSC		
L	0.35	0.40	0.45	0.014	0.016	0.018
L1	0.45	0.50	0.55	0.0177	0.0197	0.0217

ECN T-07039-Rev. A, 12-Feb-07  
DWG: 5957





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.