


## Features

- Low On-Resistance
- Ideal for Notebook Computer, Portable Phone, PCMCIA Cards, and Battery Power Circuits
- **Lead Free By Design/RoHS Compliant (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **ESD Protected Gate**
- "Green" Device (Note 3)

## Mechanical Data

- Case: SC-59
- Case Material - Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish – Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Marking Information: See Page 4
- Ordering & Date Code Information: See Page 4
- Weight: 0.008 grams (approximate)



SC-59		
Dim	Min	Max
A	0.30	0.50
B	1.40	1.80
C	2.50	3.00
D	0.85	1.05
E	0.30	0.70
G	1.70	2.10
H	2.70	3.10
J	—	0.10
K	1.00	1.40
L	0.55	0.70
M	0.10	0.35
$\alpha$	0°	8°
All Dimensions in mm		

## Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Drain Current	$I_D$	1.2 4.0	A
		Continuous Pulsed	
Total Power Dissipation	$P_d$	500	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	250	$^\circ\text{C}/\text{W}$
Operating and Storage Temperature Range	$T_i, T_{STG}$	-55 to +150	$^\circ\text{C}$

- Notes:
1. Pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ .
  2. No purposefully added lead.
  3. Diodes Inc's "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).

## Electrical Characteristics @T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 1)						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	20	—	—	V	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA
Zero Gate Voltage Drain Current @ T <sub>j</sub> = 25°C	I <sub>DSS</sub>	—	—	10	μA	V <sub>DS</sub> = 24V, V <sub>GS</sub> = 0V
Gate-Body Leakage	I <sub>GSS</sub>	—	—	±10	μA	V <sub>GS</sub> = ±12V, V <sub>DS</sub> = 0V
ON CHARACTERISTICS (Note 1)						
Gate Threshold Voltage	V <sub>GS(th)</sub>	0.7	—	1.40	V	V <sub>DS</sub> = 10V, I <sub>D</sub> = 1.0mA
Static Drain-Source On-Resistance	R <sub>DS (ON)</sub>	— —	— —	0.100 0.160	Ω	V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 0.5A V <sub>GS</sub> = 2.5V, I <sub>D</sub> = 0.5A
Forward Transfer Admittance	Y <sub>fs</sub>	—	3.3	—	S	V <sub>DS</sub> = 10V, I <sub>D</sub> = 0.5A
Diode Forward Voltage	V <sub>SD</sub>	—	0.8	1.1	V	V <sub>GS</sub> = 0V, I <sub>S</sub> = 1.0A
DYNAMIC CHARACTERISTICS						
Input Capacitance	C <sub>iss</sub>	—	180	—	pF	V <sub>DS</sub> = 10V, V <sub>GS</sub> = 0V, f = 1.0MHz
Output Capacitance	C <sub>oss</sub>	—	120	—	pF	
Reverse Transfer Capacitance	C <sub>rss</sub>	—	45	—	pF	
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	t <sub>D(ON)</sub>	—	10	—	ns	V <sub>DD</sub> = 10V, I <sub>D</sub> = 0.5A, V <sub>GS</sub> = 5.0V, R <sub>GEN</sub> = 50Ω
Turn-Off Delay Time	t <sub>D(OFF)</sub>	—	50	—	ns	
Turn-On Rise Time	t <sub>r</sub>	—	15	—	ns	
Turn-Off Fall Time	t <sub>f</sub>	—	45	—	ns	




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 On-Resistance vs. Gate Voltage




Fig. 4 On-Resistance vs. Drain Current




Fig. 5 On-Resistance Variation with Temperature




Fig. 6 Gate Threshold Voltage vs Temperature




Fig. 7 Reverse Drain Current vs Source-Drain Voltage





Fig. 8: Typical Junction Capacitance

## Ordering Information (Note 4)

Device	Packaging	Shipping
DMN2114SN-7	SC-59	3000/Tape & Reel

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



NS2 = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year ex: T = 2006  
 M = Month ex: 9 = September

### Date Code Key

Year	2006	2007	2008	2009	2010	2011	2012
Code	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.