



DESCRIPTION

The DS32W~DS320W are available in SOD-123FL Package

ORDERING INFORMATION

Package Type	Part Number
SOD-123FL	DS32W
	DS34W
	DS36W
	DS38W
	DS310W
	DS312W
	DS315W
	DS320W
Note	SPQ: 3,000pcs/Reel
AiT provides all RoHS Compliant Products	

PIN DESCRIPTION



FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Available in SOD-123FL Package

MECHANICAL DATA

Case: SOD-123FL

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 15mg 0.00048oz



ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter		Symbol	DS32W	DS34W	DS36W	DS38W	DS310W	DS312W	DS315W	DS320W	Unit
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS Voltage		V _{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage		V _{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current		I _{F(AV)}	3.0								A
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)		I _{FSM}	80				70				A
Max Instantaneous Forward Voltage at 3A		V _F	0.55		0.70		0.85		0.95		V
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _A =25°C T _A =100°C	I _R	0.5 10		0.3 5						mA
Typical Junction Capacitance ^{NOTE1}		C _J	250		160						pF
Typical Thermal Resistance ^{NOTE2}		R _{θJA}	65								°C/W
Operating Junction Temperature Range		T _J	-55 ~ +125								°C
Storage Temperature Range		T _{STG}	-55 ~ +150								°C

NOTE1: Measured at 1MHz and applied reverse voltage of 4V D.C.

NOTE2: P.C.B. mounted with 0.2 x 0.2" (5 x 5 mm) copper pad areas.



TYPICAL CHARACTERISTICS

Figure. 1 Forward Current Derating Curve




Figure. 2 Typical Reverse Characteristics




Figure. 3 Typical Forward Characteristic




Figure. 4 Typical Junction Capacitance




Figure. 5 Maximum Non-Repetitive Peak Forward Surge Current





Figure. 6 Typical Transient Thermal Impedance







PACKAGE INFORMATION

Dimension in SOD-123FL (Unit: mm)

Plastic surface mounted package; 2 leads



The recommended mounting pad size



UNIT		A	C	D	E	e	g	H _E	\angle
mm	Max	1.1	0.20	2.9	1.9	1.1	0.9	3.8	7°
	Min	0.9	0.12	2.6	1.7	0.8	0.7	3.5	
mil	Max	43	7.9	114	75	43	35	150	
	Min	35	4.7	102	67	31	23	138	



IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.