

## N- and P-Channel 30 V (D-S) MOSFET

### PRODUCT SUMMARY

|           | V <sub>DS</sub> (V) | R <sub>DS(on)</sub> (Ω)            | I <sub>D</sub> (A) <sup>a</sup> | Q <sub>g</sub> (Typ.) |
|-----------|---------------------|------------------------------------|---------------------------------|-----------------------|
| N-Channel | 30                  | 0.013 at V <sub>GS</sub> = 10 V    | 8 <sup>e</sup>                  | 6.2                   |
|           |                     | 0.014 at V <sub>GS</sub> = 8 V     | 8 <sup>e</sup>                  |                       |
|           |                     | 0.015 at V <sub>GS</sub> = 4.5 V   | 8                               |                       |
| P-Channel | - 30                | 0.032 at V <sub>GS</sub> = - 10 V  | - 8 <sup>e</sup>                | 18.5                  |
|           |                     | 0.034 at V <sub>GS</sub> = - 8 V   | - 8 <sup>e</sup>                |                       |
|           |                     | 0.040 at V <sub>GS</sub> = - 4.5 V | - 7.5                           |                       |

### FEATURES



- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFET
- 100 % R<sub>g</sub> and UIS Tested
- Compliant to RoHS Directive 2002/95/EC



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### APPLICATIONS

- Motor Drive
- Mobile Power Bank



### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25 °C, unless otherwise noted)

| Parameter                                          | Symbol                            | N-Channel            | P-Channel             | Unit |
|----------------------------------------------------|-----------------------------------|----------------------|-----------------------|------|
| Drain-Source Voltage                               | V <sub>DS</sub>                   | 30                   | - 30                  | V    |
| Gate-Source Voltage                                | V <sub>GS</sub>                   | ± 12                 | ± 12                  |      |
| Continuous Drain Current (T <sub>J</sub> = 150 °C) | I <sub>D</sub>                    | 8 <sup>e</sup>       | - 8 <sup>e</sup>      | A    |
|                                                    |                                   | 6.8                  | - 6.8                 |      |
|                                                    |                                   | 6.8 <sup>b, c</sup>  | - 6.6 <sup>b, c</sup> |      |
|                                                    |                                   | 5.4 <sup>b, c</sup>  | - 5.3 <sup>b, c</sup> |      |
| Pulsed Drain Current (10 μs Pulse Width)           | I <sub>DM</sub>                   | 40                   | - 40                  |      |
| Source-Drain Current Diode Current                 | I <sub>S</sub>                    | 2.6                  | - 2.6                 |      |
|                                                    |                                   | 1.6 <sup>b, c</sup>  | - 1.6 <sup>b, c</sup> |      |
| Pulsed Source-Drain Current                        | I <sub>SM</sub>                   | 40                   | - 40                  | mJ   |
| Single Pulse Avalanche Current                     | I <sub>AS</sub>                   | 10                   | - 20                  |      |
| Single Pulse Avalanche Energy                      | E <sub>AS</sub>                   | 5                    | 20                    | W    |
| Maximum Power Dissipation                          | P <sub>D</sub>                    | 3.1                  | 3.2                   |      |
|                                                    |                                   | 2                    | 2.1                   |      |
|                                                    |                                   | 2 <sup>b, c</sup>    | 2 <sup>b, c</sup>     |      |
|                                                    |                                   | 1.28 <sup>b, c</sup> | 1.28 <sup>b, c</sup>  |      |
| Operating Junction and Storage Temperature Range   | T <sub>J</sub> , T <sub>stg</sub> | - 55 to 150          |                       | °C   |

### THERMAL RESISTANCE RATINGS

| Parameter                                   | Symbol            | N-Channel |      | P-Channel |      | Unit |
|---------------------------------------------|-------------------|-----------|------|-----------|------|------|
|                                             |                   | Typ.      | Max. | Typ.      | Max. |      |
| Maximum Junction-to-Ambient <sup>b, d</sup> | R <sub>thJA</sub> | 50        | 62.5 | 47        | 62.5 | °C/W |
| Maximum Junction-to-Foot (Drain)            | R <sub>thJF</sub> | 30        | 40   | 29        | 38   |      |

Notes:

a. Based on T<sub>C</sub> = 25 °C.

b. Surface mounted on 1" x 1" FR4 board.

c. t = 10 s.

d. Maximum under steady state conditions is 120 °C/W (n-channel) and 110 °C/W (p-channel).

e. Package limited.

**SPECIFICATIONS** ( $T_J = 25\text{ }^{\circ}\text{C}$ , unless otherwise noted)

| Parameter                                     | Symbol                                                                              | Test Conditions                                                                           |      | Min.  | Typ. <sup>a</sup> | Max.  | Unit  |  |
|-----------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|------|-------|-------------------|-------|-------|--|
| Static                                        |                                                                                     |                                                                                           |      |       |                   |       |       |  |
| Drain-Source Breakdown Voltage                | V <sub>DS</sub>                                                                     | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                            | N-Ch | 30    |                   |       | V     |  |
|                                               |                                                                                     | V <sub>GS</sub> = 0 V, I <sub>D</sub> = - 250 μA                                          | P-Ch | - 30  |                   |       |       |  |
| V <sub>DS</sub> Temperature Coefficient       | ΔV <sub>DS</sub> /T <sub>J</sub>                                                    | I <sub>D</sub> = 250 μA                                                                   | N-Ch |       | 40                |       | mV/°C |  |
|                                               |                                                                                     | I <sub>D</sub> = - 250 μA                                                                 | P-Ch |       | - 34              |       |       |  |
| V <sub>GS(th)</sub> Temperature Coefficient   | ΔV <sub>GS(th)</sub> /T <sub>J</sub>                                                | I <sub>D</sub> = 250 μA                                                                   | N-Ch |       | - 4.1             |       |       |  |
|                                               |                                                                                     | I <sub>D</sub> = - 250 μA                                                                 | P-Ch |       | 5                 |       |       |  |
| Gate Threshold Voltage                        | V <sub>GS(th)</sub>                                                                 | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                               | N-Ch | 0.5   |                   | 1.0   | V     |  |
|                                               |                                                                                     | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = - 250 μA                             | P-Ch | - 0.5 |                   | - 1.0 |       |  |
| Gate-Body Leakage                             | I <sub>GSS</sub>                                                                    | V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ± 12 V                                           | N-Ch |       |                   | ± 100 | nA    |  |
|                                               |                                                                                     | V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ± 12 V                                           | P-Ch |       |                   | ± 100 |       |  |
| Zero Gate Voltage Drain Current               | I <sub>DSS</sub>                                                                    | V <sub>DS</sub> = 30 V, V <sub>GS</sub> = 0 V                                             | N-Ch |       |                   | 1     | μA    |  |
|                                               |                                                                                     | V <sub>DS</sub> = - 30 V, V <sub>GS</sub> = 0 V                                           | P-Ch |       |                   | - 1   |       |  |
|                                               |                                                                                     | V <sub>DS</sub> = 30 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 55 °C                     | N-Ch |       |                   | 10    |       |  |
|                                               |                                                                                     | V <sub>DS</sub> = - 30 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 55 °C                   | P-Ch |       |                   | - 10  |       |  |
| On-State Drain Current <sup>b</sup>           | I <sub>D(on)</sub>                                                                  | V <sub>DS</sub> = 5 V, V <sub>GS</sub> = 10 V                                             | N-Ch | 20    |                   |       | A     |  |
|                                               |                                                                                     | V <sub>DS</sub> = - 5 V, V <sub>GS</sub> = - 10 V                                         | P-Ch | - 20  |                   |       |       |  |
| Drain-Source On-State Resistance <sup>b</sup> | R <sub>DS(on)</sub>                                                                 | V <sub>GS</sub> = 10 V, I <sub>D</sub> = 6.8 A                                            | N-Ch |       | 0.012             | 0.013 | Ω     |  |
|                                               |                                                                                     | V <sub>GS</sub> = - 10 V, I <sub>D</sub> = - 8 A                                          | P-Ch |       | 0.031             | 0.032 |       |  |
|                                               |                                                                                     | V <sub>GS</sub> = 8 V, I <sub>D</sub> = 6.7 A                                             | N-Ch |       | 0.013             | 0.014 |       |  |
|                                               |                                                                                     | V <sub>GS</sub> = - 8 V, I <sub>D</sub> = - 6.5 A                                         | P-Ch |       | 0.032             | 0.034 |       |  |
|                                               |                                                                                     | V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 6.6 A                                           | N-Ch |       | 0.014             | 0.015 |       |  |
|                                               |                                                                                     | V <sub>GS</sub> = - 4.5 V, I <sub>D</sub> = - 5 A                                         | P-Ch |       | 0.037             | 0.040 |       |  |
| Forward Transconductance <sup>b</sup>         | g <sub>fs</sub>                                                                     | V <sub>DS</sub> = 15 V, I <sub>D</sub> = 6.8 A                                            | N-Ch |       | 27                |       | S     |  |
|                                               |                                                                                     | V <sub>DS</sub> = - 15 V, I <sub>D</sub> = - 6.7 A                                        | P-Ch |       | 25                |       |       |  |
| Dynamic <sup>a</sup>                          |                                                                                     |                                                                                           |      |       |                   |       |       |  |
| Input Capacitance                             | C <sub>iss</sub>                                                                    | N-Channel<br>V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 0 V, f = 1 MHz                     | N-Ch |       | 510               |       | pF    |  |
|                                               |                                                                                     |                                                                                           | P-Ch |       | 620               |       |       |  |
| Output Capacitance                            | C <sub>oss</sub>                                                                    | P-Channel<br>V <sub>DS</sub> = - 20 V, V <sub>GS</sub> = 0 V, f = 1 MHz                   | N-Ch |       | 95                |       |       |  |
|                                               |                                                                                     |                                                                                           | P-Ch |       | 115               |       |       |  |
| Reverse Transfer Capacitance                  | C <sub>rss</sub>                                                                    |                                                                                           | N-Ch |       | 33                |       |       |  |
|                                               |                                                                                     |                                                                                           | P-Ch |       | 57                |       |       |  |
| Total Gate Charge                             | Q <sub>g</sub>                                                                      | V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 10 V, I <sub>D</sub> = 10 A                     | N-Ch |       | 6                 | 10    | nC    |  |
|                                               |                                                                                     | V <sub>DS</sub> = - 20 V, V <sub>GS</sub> = - 10 V, I <sub>D</sub> = - 10 A               | P-Ch |       | 41.5              | 63    |       |  |
|                                               | N-Channel<br>V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 10 A | N-Ch                                                                                      |      | 5.8   | 7                 |       |       |  |
|                                               |                                                                                     | P-Ch                                                                                      |      | 16    | 22                |       |       |  |
| Gate-Source Charge                            | Q <sub>gs</sub>                                                                     | P-Channel<br>V <sub>DS</sub> = - 20 V, V <sub>GS</sub> = - 4.5 V, I <sub>D</sub> = - 10 A | N-Ch |       | 1.6               |       |       |  |
|                                               |                                                                                     |                                                                                           | P-Ch |       | 4.3               |       |       |  |
| Gate-Drain Charge                             | Q <sub>gd</sub>                                                                     |                                                                                           | N-Ch |       | 1.4               |       |       |  |
|                                               |                                                                                     |                                                                                           | P-Ch |       | 7                 |       |       |  |
| Gate Resistance                               | R <sub>g</sub>                                                                      | f = 1 MHz                                                                                 | N-Ch | 0.3   | 1.1               | 2.3   | Ω     |  |
|                                               |                                                                                     |                                                                                           | P-Ch | 1.2   | 5.7               | 9.6   |       |  |

| SPECIFICATIONS (T <sub>J</sub> = 25 °C, unless otherwise noted) |                     |                                                                                                                                          |                                                                                 |      |                   |       |      |    |
|-----------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|------|-------------------|-------|------|----|
| Parameter                                                       | Symbol              | Test Conditions                                                                                                                          |                                                                                 | Min. | Typ. <sup>a</sup> | Max.  | Unit |    |
| Dynamic <sup>a</sup>                                            |                     |                                                                                                                                          |                                                                                 |      |                   |       |      |    |
| Turn-On Delay Time                                              | t <sub>d(on)</sub>  | N-Channel<br>V <sub>DD</sub> = 20 V, R <sub>L</sub> = 3.7 Ω<br>I <sub>D</sub> ≅ 5.4 A, V <sub>GEN</sub> = 10 V, R <sub>g</sub> = 1 Ω     | N-Ch                                                                            |      | 4                 | 8     | ns   |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 10                | 16    |      |    |
| Rise Time                                                       | t <sub>r</sub>      |                                                                                                                                          | N-Ch                                                                            |      | 10                | 17    |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 9                 | 15    |      |    |
| Turn-Off Delay Time                                             | t <sub>d(off)</sub> | P-Channel<br>V <sub>DD</sub> = - 20 V, R <sub>L</sub> = 2 Ω<br>I <sub>D</sub> ≅ - 10 A, V <sub>GEN</sub> = - 10 V, R <sub>g</sub> = 1 Ω  | N-Ch                                                                            |      | 16                | 22    |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 23                | 26    |      |    |
| Fall Time                                                       | t <sub>f</sub>      |                                                                                                                                          | N-Ch                                                                            |      | 5                 | 9     |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 10                | 16    |      |    |
| Turn-On Delay Time                                              | t <sub>d(on)</sub>  | N-Channel<br>V <sub>DD</sub> = 20 V, R <sub>L</sub> = 3.7 Ω<br>I <sub>D</sub> ≅ 5.4 A, V <sub>GEN</sub> = 4.5 V, R <sub>g</sub> = 1 Ω    | N-Ch                                                                            |      | 10                | 16    |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 26                | 35    |      |    |
| Rise Time                                                       | t <sub>r</sub>      |                                                                                                                                          | N-Ch                                                                            |      | 11                | 20    |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 16                | 26    |      |    |
| Turn-Off Delay Time                                             | t <sub>d(off)</sub> | P-Channel<br>V <sub>DD</sub> = - 20 V, R <sub>L</sub> = 2 Ω<br>I <sub>D</sub> ≅ - 10 A, V <sub>GEN</sub> = - 4.5 V, R <sub>g</sub> = 1 Ω | N-Ch                                                                            |      | 13                | 22    |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 16                | 26    |      |    |
| Fall Time                                                       | t <sub>f</sub>      |                                                                                                                                          | N-Ch                                                                            |      | 5                 | 9     |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 16                | 26    |      |    |
| Drain-Source Body Diode Characteristics                         |                     |                                                                                                                                          |                                                                                 |      |                   |       |      |    |
| Continuous Source-Drain Diode Current                           | I <sub>S</sub>      | T <sub>C</sub> = 25 °C                                                                                                                   | N-Ch                                                                            |      |                   | 2.6   | A    |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      |                   | - 2.6 |      |    |
| Pulse Diode Forward Current <sup>a</sup>                        | I <sub>SM</sub>     |                                                                                                                                          | N-Ch                                                                            |      |                   | 40    |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      |                   | - 40  |      |    |
| Body Diode Voltage                                              | V <sub>SD</sub>     | I <sub>S</sub> = 5.4 A                                                                                                                   | N-Ch                                                                            |      | 0.81              | 1.2   | V    |    |
|                                                                 |                     | I <sub>S</sub> = - 2 A                                                                                                                   | P-Ch                                                                            |      | - 0.77            | - 1.2 |      |    |
| Body Diode Reverse Recovery Time                                | t <sub>rr</sub>     | N-Channel<br>I <sub>F</sub> = 5 A, dI/dt = 100 A/μs, T <sub>J</sub> = 25 °C                                                              | N-Ch                                                                            |      | 12                | 25    | ns   |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 31                | 57    |      |    |
| Body Diode Reverse Recovery Charge                              | Q <sub>rr</sub>     |                                                                                                                                          | P-Channel<br>I <sub>F</sub> = - 5 A, dI/dt = - 100 A/μs, T <sub>J</sub> = 25 °C | N-Ch |                   | 10    | 17   | nC |
|                                                                 |                     |                                                                                                                                          |                                                                                 | P-Ch |                   | 29    | 47   |    |
| Reverse Recovery Fall Time                                      | t <sub>a</sub>      |                                                                                                                                          |                                                                                 | N-Ch |                   | 10    |      | ns |
|                                                                 |                     |                                                                                                                                          |                                                                                 | P-Ch |                   | 13    |      |    |
| Reverse Recovery Rise Time                                      | t <sub>b</sub>      |                                                                                                                                          | N-Ch                                                                            |      | 7                 |       |      |    |
|                                                                 |                     |                                                                                                                                          | P-Ch                                                                            |      | 23                |       |      |    |


Notes:

a. Guaranteed by design, not subject to production testing.


b. Pulse test; pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$ .

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


**N-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current and Gate Voltage**



**Capacitance**




**Gate Charge**




**On-Resistance vs. Junction Temperature**


**N-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage






Single Pulse Power, Junction-to-Ambient



\*  $V_{GS} >$  minimum  $V_{GS}$  at which  $R_{DS(on)}$  is specified


Safe Operating Area, Junction-to-Ambient

**N-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




\* The power dissipation  $P_D$  is based on  $T_{J(max)} = 150$  °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

**N-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




**Normalized Thermal Transient Impedance, Junction-to-Ambient**




**Normalized Thermal Transient Impedance, Junction-to-Foot**


**P-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current and Gate Voltage**



**Capacitance**




**Gate Charge**




**On-Resistance vs. Junction Temperature**


**P-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Single Pulse Power, Junction-to-Ambient




\*  $V_{GS}$  > minimum  $V_{GS}$  at which  $R_{DS(on)}$  is specified  
**Safe Operating Area, Junction-to-Ambient**


**P-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)



**Current Derating\***




**Power Derating, Junction-to-Foot**




**Power Derating, Junction-to-Ambient**

\* The power dissipation  $P_D$  is based on  $T_{J(max)} = 150$  °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

**P-CHANNEL TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)




**Normalized Thermal Transient Impedance, Junction-to-Ambient**



**Normalized Thermal Transient Impedance, Junction-to-Foot**


**SOIC (NARROW): 8-LEAD**  
JEDEC Part Number: MS-012



| DIM            | MILLIMETERS |      | INCHES    |       |
|----------------|-------------|------|-----------|-------|
|                | Min         | Max  | Min       | Max   |
| A              | 1.35        | 1.75 | 0.053     | 0.069 |
| A <sub>1</sub> | 0.10        | 0.20 | 0.004     | 0.008 |
| B              | 0.35        | 0.51 | 0.014     | 0.020 |
| C              | 0.19        | 0.25 | 0.0075    | 0.010 |
| D              | 4.80        | 5.00 | 0.189     | 0.196 |
| E              | 3.80        | 4.00 | 0.150     | 0.157 |
| e              | 1.27 BSC    |      | 0.050 BSC |       |
| H              | 5.80        | 6.20 | 0.228     | 0.244 |
| h              | 0.25        | 0.50 | 0.010     | 0.020 |
| L              | 0.50        | 0.93 | 0.020     | 0.037 |
| q              | 0°          | 8°   | 0°        | 8°    |
| S              | 0.44        | 0.64 | 0.018     | 0.026 |

ECN: C-06527-Rev. I, 11-Sep-06  
DWG: 5498

**RECOMMENDED MINIMUM PADS FOR SO-8**



Recommended Minimum Pads  
Dimensions in Inches/(mm)

## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Din-Tek Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Din-Tek"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Din-Tek makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Din-Tek disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Din-Tek's knowledge of typical requirements that are often placed on Din-Tek products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Din-Tek's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Din-Tek products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Din-Tek product could result in personal injury or death. Customers using or selling Din-Tek products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Din-Tek personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Din-Tek. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Din-Tek Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Din-Tek documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Din-Tek Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Din-Tek documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

---